

CSE408


Closest pair & Convex Hull Problem, Insertion Sort

Lecture #13

The most-well known algorithm design strategy:

1. Divide instance of problem into two or more smaller instances
2. Solve smaller instances recursively
3. Obtain solution to original (larger) instance by combining these solutions

universitystudy.in




It general leads to a recursive algorithm!

Closest-Pair Problem by Divide-and-Conquer



Step 0 Sort the points by x (list one) and then by y (list two).

Step 1 Divide the points given into two subsets S_1 and S_2 by a vertical line $x = c$ so that half the points lie to the left or on the line and half the points lie to the right or on the line.



Closest Pair by Divide-and-Conquer (cont.)



Step 2 Find recursively the closest pairs for the left and right subsets.

Step 3 Set $d = \min\{d_1, d_2\}$


We can limit our attention to the points in the symmetric vertical strip of width $2d$ as possible closest pair. Let C_1 and C_2 be the subsets of points in the left subset S_1 and of the right subset S_2 , respectively, that lie in this vertical strip. The points in C_1 and C_2 are stored in increasing order of their y coordinates, taken from the second list.

Step 4 For every point $P(x,y)$ in C_1 , we inspect points in C_2 that may be closer to P than d . There can be no more than **6 such points** (because $d \leq d_2$)!

Closest Pair by Divide-and-Conquer: Worst Case



The worst case scenario is depicted below:



Efficiency of the Closest-Pair Algorithm



Running time of the algorithm (without sorting) is:

$$T(n) = 2T(n/2) + M(n), \text{ where } M(n) \in \Theta(n)$$

By the Master Theorem (with $a = 2$, $b = 2$, $d = 1$)

$$T(n) \in \Theta(n \log n)$$

So the total time is $\Theta(n \log n)$.

Convex hull: smallest convex set that includes given points. An $O(n^3)$ brute force time is given in Levitin, Ch 3.


Assume points are sorted by x -coordinate values

Identify extreme points P_1 and P_2 (leftmost and rightmost)

Compute *upper hull* recursively:

- find point P_{\max} that is farthest away from line P_1P_2
- compute the upper hull of the points to the left of line P_1P_{\max}
- compute the upper hull of the points to the left of line $P_{\max}P_2$

Compute *lower hull* in a similar manner



Finding point farthest away from line P_1P_2 can be done in linear time

Time efficiency: $T(n) = T(x) + T(y) + T(z) + T(v) + O(n)$,

where $x + y + z + v \leq n$.

- worst case: $\Theta(n^2)$ $T(n) = T(n-1) + O(n)$
- average case: $\Theta(n)$ (under reasonable assumptions about distribution of points given)

If points are not initially sorted by x-coordinate value, this can be accomplished in $O(n \log n)$ time

Several $O(n \log n)$ algorithms for convex hull are known

Insertion Sort



Iteration i . Repeatedly swap element i with the one to its left if smaller.

Property. After i th iteration, $a[0]$ through $a[i]$ contain first $i+1$ elements in ascending order.

Array index	0	1	2	3	4	5	6	7	8	9
Value	2.78	7.42	0.56	1.12	1.17	0.32	6.21	4.42	3.14	7.71

Iteration 0: **step 0.**

Insertion Sort



Iteration i . Repeatedly swap element i with the one to its left if smaller.

Property. After i th iteration, $a[0]$ through $a[i]$ contain first $i+1$ elements in ascending order.

Array index	0	1	2	3	4	5	6	7	8	9
Value	2.78	7.42	0.56	1.12	1.17	0.32	6.21	4.42	3.14	7.71

Iteration 1: **step 0.**

Insertion Sort



Iteration i. Repeatedly swap element i with the one to its left if smaller.

Property. After i th iteration, $a[0]$ through $a[i]$ contain first $i+1$ elements in ascending order.

Array index	0	1	2	3	4	5	6	7	8	9
Value	2.78	0.56	7.42	1.12	1.17	0.32	6.21	4.42	3.14	7.71

Iteration 2: **step 0.**

Insertion Sort



Iteration i . Repeatedly swap element i with the one to its left if smaller.

Property. After i th iteration, $a[0]$ through $a[i]$ contain first $i+1$ elements in ascending order.

Array index	0	1	2	3	4	5	6	7	8	9
Value	0.56	2.78	7.42	1.12	1.17	0.32	6.21	4.42	3.14	7.71



Iteration 2: **step 1.**

Insertion Sort



Iteration i . Repeatedly swap element i with the one to its left if smaller.

Property. After i th iteration, $a[0]$ through $a[i]$ contain first $i+1$ elements in ascending order.

Array index	0	1	2	3	4	5	6	7	8	9
Value	0.56	2.78	7.42	1.12	1.17	0.32	6.21	4.42	3.14	7.71

Iteration 2: **step 2.**


Insertion Sort



Iteration i . Repeatedly swap element i with the one to its left if smaller.

Property. After i th iteration, $a[0]$ through $a[i]$ contain first $i+1$ elements in ascending order.

Array index	0	1	2	3	4	5	6	7	8	9
Value	0.56	2.78	1.12	7.42	1.17	0.32	6.21	4.42	3.14	7.71



Iteration 3: **step 0.**

Insertion Sort



Iteration i . Repeatedly swap element i with the one to its left if smaller.

Property. After i th iteration, $a[0]$ through $a[i]$ contain first $i+1$ elements in ascending order.

Array index	0	1	2	3	4	5	6	7	8	9
Value	0.56	1.12	2.78	7.42	1.17	0.32	6.21	4.42	3.14	7.71

Iteration 3: **step 1.**

Insertion Sort



Iteration i . Repeatedly swap element i with the one to its left if smaller.

Property. After i th iteration, $a[0]$ through $a[i]$ contain first $i+1$ elements in ascending order.

Array index	0	1	2	3	4	5	6	7	8	9
Value	0.56	1.12	2.78	7.42	1.17	0.32	6.21	4.42	3.14	7.71

Iteration 3: **step 2.**


Insertion Sort



Iteration i. Repeatedly swap element i with the one to its left if smaller.

Property. After i th iteration, $a[0]$ through $a[i]$ contain first $i+1$ elements in ascending order.

Array index	0	1	2	3	4	5	6	7	8	9
Value	0.56	1.12	2.78	1.17	7.42	0.32	6.21	4.42	3.14	7.71



Iteration 4: **step 0.**


Insertion Sort



Iteration i . Repeatedly swap element i with the one to its left if smaller.

Property. After i th iteration, $a[0]$ through $a[i]$ contain first $i+1$ elements in ascending order.

Array index	0	1	2	3	4	5	6	7	8	9
Value	0.56	1.12	1.17	2.78	7.42	0.32	6.21	4.42	3.14	7.71



Iteration 4: **step 1.**

Insertion Sort



Iteration i . Repeatedly swap element i with the one to its left if smaller.

Property. After i th iteration, $a[0]$ through $a[i]$ contain first $i+1$ elements in ascending order.

Array index	0	1	2	3	4	5	6	7	8	9
Value	0.56	1.12	1.17	2.78	7.42	0.32	6.21	4.42	3.14	7.71

Iteration 4: **step 2.**


Insertion Sort



Iteration i . Repeatedly swap element i with the one to its left if smaller.

Property. After i th iteration, $a[0]$ through $a[i]$ contain first $i+1$ elements in ascending order.

Array index	0	1	2	3	4	5	6	7	8	9
Value	0.56	1.12	1.17	2.78	0.32	7.42	6.21	4.42	3.14	7.71



Iteration 5: **step 0.**


Insertion Sort



Iteration i. Repeatedly swap element i with the one to its left if smaller.

Property. After i th iteration, $a[0]$ through $a[i]$ contain first $i+1$ elements in ascending order.

Array index	0	1	2	3	4	5	6	7	8	9
Value	0.56	1.12	1.17	0.32	2.78	7.42	6.21	4.42	3.14	7.71



Iteration 5: **step 1.**

Insertion Sort



Iteration i . Repeatedly swap element i with the one to its left if smaller.

Property. After i th iteration, $a[0]$ through $a[i]$ contain first $i+1$ elements in ascending order.

Array index	0	1	2	3	4	5	6	7	8	9
Value	0.56	1.12	0.32	1.17	2.78	7.42	6.21	4.42	3.14	7.71



Iteration 5: **step 2.**

Insertion Sort



Iteration i . Repeatedly swap element i with the one to its left if smaller.

Property. After i th iteration, $a[0]$ through $a[i]$ contain first $i+1$ elements in ascending order.

Array index	0	1	2	3	4	5	6	7	8	9
Value	0.56	0.32	1.12	1.17	2.78	7.42	6.21	4.42	3.14	7.71

Iteration 5: step 3.

Insertion Sort



Iteration i . Repeatedly swap element i with the one to its left if smaller.

Property. After i th iteration, $a[0]$ through $a[i]$ contain first $i+1$ elements in ascending order.

Array index	0	1	2	3	4	5	6	7	8	9
Value	0.32	0.56	1.12	1.17	2.78	7.42	6.21	4.42	3.14	7.71



Iteration 5: **step 4.**

Insertion Sort



Iteration i . Repeatedly swap element i with the one to its left if smaller.

Property. After i th iteration, $a[0]$ through $a[i]$ contain first $i+1$ elements in ascending order.

Array index	0	1	2	3	4	5	6	7	8	9
Value	0.32	0.56	1.12	1.17	2.78	7.42	6.21	4.42	3.14	7.71

Iteration 5: **step 5.**


Insertion Sort



Iteration i . Repeatedly swap element i with the one to its left if smaller.

Property. After i th iteration, $a[0]$ through $a[i]$ contain first $i+1$ elements in ascending order.

Array index	0	1	2	3	4	5	6	7	8	9
Value	0.32	0.56	1.12	1.17	2.78	6.21	7.42	4.42	3.14	7.71



Iteration 6: **step 0.**

Insertion Sort



Iteration i . Repeatedly swap element i with the one to its left if smaller.

Property. After i th iteration, $a[0]$ through $a[i]$ contain first $i+1$ elements in ascending order.

Array index	0	1	2	3	4	5	6	7	8	9
Value	0.32	0.56	1.12	1.17	2.78	6.21	7.42	4.42	3.14	7.71

Iteration 6: **step 1.**


Insertion Sort



Iteration i . Repeatedly swap element i with the one to its left if smaller.

Property. After i th iteration, $a[0]$ through $a[i]$ contain first $i+1$ elements in ascending order.

Array index	0	1	2	3	4	5	6	7	8	9
Value	0.32	0.56	1.12	1.17	2.78	6.21	4.42	7.42	3.14	7.71



Iteration 7: **step 0.**


Insertion Sort



Iteration i. Repeatedly swap element i with the one to its left if smaller.

Property. After i th iteration, $a[0]$ through $a[i]$ contain first $i+1$ elements in ascending order.

Array index	0	1	2	3	4	5	6	7	8	9
Value	0.32	0.56	1.12	1.17	2.78	4.42	6.21	7.42	3.14	7.71



Iteration 7: **step 1.**

Insertion Sort



Iteration i . Repeatedly swap element i with the one to its left if smaller.

Property. After i th iteration, $a[0]$ through $a[i]$ contain first $i+1$ elements in ascending order.

Array index	0	1	2	3	4	5	6	7	8	9
Value	0.32	0.56	1.12	1.17	2.78	4.42	6.21	7.42	3.14	7.71

Iteration 7: **step 2.**

Insertion Sort



Iteration i . Repeatedly swap element i with the one to its left if smaller.

Property. After i th iteration, $a[0]$ through $a[i]$ contain first $i+1$ elements in ascending order.

Array index	0	1	2	3	4	5	6	7	8	9
Value	0.32	0.56	1.12	1.17	2.78	4.42	6.21	3.14	7.42	7.71



Iteration 8: **step 0.**


Insertion Sort



Iteration i . Repeatedly swap element i with the one to its left if smaller.

Property. After i th iteration, $a[0]$ through $a[i]$ contain first $i+1$ elements in ascending order.

Array index	0	1	2	3	4	5	6	7	8	9
Value	0.32	0.56	1.12	1.17	2.78	4.42	3.14	6.21	7.42	7.71



Iteration 8: **step 1.**

Insertion Sort



Iteration i . Repeatedly swap element i with the one to its left if smaller.

Property. After i th iteration, $a[0]$ through $a[i]$ contain first $i+1$ elements in ascending order.

Array index	0	1	2	3	4	5	6	7	8	9
Value	0.32	0.56	1.12	1.17	2.78	3.14	4.42	6.21	7.42	7.71



Iteration 8: **step 2.**

Insertion Sort



Iteration i . Repeatedly swap element i with the one to its left if smaller.

Property. After i th iteration, $a[0]$ through $a[i]$ contain first $i+1$ elements in ascending order.

Array index	0	1	2	3	4	5	6	7	8	9
Value	0.32	0.56	1.12	1.17	2.78	3.14	4.42	6.21	7.42	7.71

Iteration 8: **step 3.**

Insertion Sort



Iteration i . Repeatedly swap element i with the one to its left if smaller.

Property. After i th iteration, $a[0]$ through $a[i]$ contain first $i+1$ elements in ascending order.

Array index	0	1	2	3	4	5	6	7	8	9
Value	0.32	0.56	1.12	1.17	2.78	3.14	4.42	6.21	7.42	7.71

Iteration 9: **step 0.**

Insertion Sort



Iteration i. Repeatedly swap element i with the one to its left if smaller.

Property. After i th iteration, $a[0]$ through $a[i]$ contain first $i+1$ elements in ascending order.

Array index	0	1	2	3	4	5	6	7	8	9
Value	0.32	0.56	1.12	1.17	2.78	3.14	4.42	6.21	7.42	7.71

Iteration 10: **DONE.**