

MCP Quick Reference for OpenCode

Essential MCP Server Configs

Copy-paste these directly into your `opencode.jsonc` :

Context7 (Documentation)

```
"context7": {  
  "type": "remote",  
  "url": "https://mcp.context7.com/mcp",  
  "enabled": true  
}
```

Usage: Add `use context7` to any prompt to get latest library docs.

GitHub MCP

```
"github": {  
  "type": "remote",  
  "url": "https://api.githubcopilot.com/mcp/",  
  "oauth": {},  
  "enabled": false  
}
```

Usage: `opencode mcp auth github` then add `use the github tool`.

 **Warning:** Adds 10,000+ tokens. Keep disabled globally.

Grep by Vercel (Code Search)

```
"gh_grep": {  
  "type": "remote",  
  "url": "https://mcp.grep.app",  
  "enabled": true  
}
```

Usage: `use the gh_grep tool` to find examples of `[pattern]`

PostgreSQL

```
"postgres": {
  "type": "local",
  "command": ["npx", "-y", "@modelcontextprotocol/server-postgres",
    "${env:DATABASE_URL}"],
  "enabled": true
}
```

SQLite

```
"sqlite": {
  "type": "local",
  "command": ["npx", "-y", "@modelcontextprotocol/server-sqlite", "--db-path",
    ".data.db"],
  "enabled": true
}
```

Playwright (Browser Automation)

```
"playwright": {
  "type": "local",
  "command": ["npx", "-y", "@playwright/mcp"],
  "enabled": false
}
```

Enable per-agent:

```
"agent": {
  "e2e-tester": {
    "tools": { "playwright_*": true }
  }
}
```

Sentry

```
"sentry": {
  "type": "remote",
  "url": "https://mcp.sentry.dev/mcp",
  "oauth": {}
}
```

Auth: `opencode mcp auth sentry`

gopls (Go Language Server)

```
"gopls": {  
  "type": "local",  
  "command": ["gopls", "mcp"],  
  "enabled": true  
}
```

Prerequisites: `go install golang.org/x/tools/gopls@latest`

Docker

```
"docker": {  
  "type": "local",  
  "command": ["npx", "-y", "@docker/mcp"],  
  "enabled": false  
}
```

Supabase

```
"supabase": {  
  "type": "local",  
  "command": ["npx", "-y", "@supabase/mcp-server-supabase"],  
  "environment": {  
    "SUPABASE_URL": "{env:SUPABASE_URL}",  
    "SUPABASE_SERVICE_ROLE_KEY": "{env:SUPABASE_SERVICE_ROLE_KEY}"  
  }  
}
```

Linear (Issue Tracking)

```
"linear": {  
  "type": "local",  
  "command": ["npx", "-y", "@linear/mcp-server"],  
  "environment": {  
    "LINEAR_API_KEY": "{env:LINEAR_API_KEY}"  
  }  
}
```

Composio (1000+ integrations via single endpoint)

```
"composio": {
  "type": "remote",
  "url": "https://mcp.composio.dev",
  "headers": {
    "X-Composio-API-Key": "{env:COMPOSIO_API_KEY}"
  }
}
```

MCP CLI Commands Cheat Sheet

```
# List all configured servers and their status
opencode mcp list

# Debug connectivity for a specific server
opencode mcp debug <server-name>

# Authenticate via OAuth
opencode mcp auth <server-name>

# View OAuth authentication status for all servers
opencode mcp auth list

# Remove stored OAuth tokens
opencode mcp logout <server-name>
```

Token Cost Reference

Server	Approx. tokens added
Context7	~500-1,000
Filesystem	~200
SQLite	~300
Playwright	~1,000
GitHub MCP	~10,000-15,000 ⚠️
Composio	~500 (meta-tools only)

Tips

1. **Disable globally, enable per-agent** for heavy servers
2. **Use glob patterns** to disable all tools of a server: `"github_*": false`
3. **Use `{env:VAR}` syntax** for all secrets — never hardcode
4. **Test connectivity** before adding to config: `opencode mcp debug <name>`

5. **Use gateway MCPs** (Composio) instead of many individual servers