

SHELLUX CHEMICALS NIG

(Marine Coatings & Applications)

25, Olanrewaju Ariyibi Street,

Website: www.shelluxchemicals.com

Abule Onilu by Odo Eran,

Email: info@shelluxchemicals.com

Along Isheri/Lasu Road,

Igando-Lagos.

Tel- +234-7065312219, +234-8084357102.

Shellux Chemicals Nigeria is the business of production, sells and distribution of high quality marine paints and Allied Products.

Products (Epoxy Paints)

- Marine Paints Topcoats, we supply customers color request.
- Anti-fouling paints
- Coat tar black
- Primers of color request
- Appropriate Thinners
- Zinc Phosphate epoxy paint
- Appropriate paint activator (Curing agent)



Uses:


- For Protection of ship bottoms, and cargo tanks
- For submerged / splash zone areas of marine structures
- For external protection of buried pipelines.

Method of Applications;

Spray, Brush, or Roller

They are 2 pack system except Anti-fouling paints A=paints, B= Activator, C= Thinner mixing ratio= 4A : 1B : 1C.

Typical Application on Lagos Sites; Applied on ship piles- on jetties for container-bonded terminals



TECHNICAL DATA SHEET

SHELLUX CHEMICALS NIGERIA

Ref: TDS-1001ps

25, Olanrewaju Ariyibi Street,

Product Name: Red Oxide Epoxy Primer

Abule Onilu by Odo Eran,

Product Code: GP 1001ps

Along Isheri/Lasu Road,

Category: Epoxy System.

Igando-Lagos.

Tel- +234-7065312219, +234-8084357102.

S/N	PROPERTIES	SPECIFICATIONS
1	COLOUR	RED OXIDE
2	APPEARANCE	MATT
3	FINISH	SMOOTH
4	SPECIFIC GRAVITY	1.3KG/LT
5	VISCOSITY	60SEC-BY VISCOSITY CUP
6	COVERAGE	65 SQ FT/L/COAT
7	MIXING PROPORTION	4A + 1B + 1C
8	THINNER	EPOXY THINNER
9	DRYING TIME TOUCH DRY SURFACE DRY HARD DRY	15MINS 1HR 8HRS
10	OVERCOAT INTERVAL	OVER NIGHT
11	SCRATCH HARD	UP TO 2KG.WT
12	FLEXIBILITY	EXCELLENT
13	POT LIFE	4 YEARS
14	SHELF LIFE	2 YEAR
15	APPLICATIONS	HIGHLY CORROSIVE MATERIALS
16	METHOD OF APPLICATION	BRUSH, ROLLER OR SPRAYING
17	KEEP OUT OF CHILDREN AND INCASE OF ACCIDENT	REPORT TO THE MEDICAL PERSONNEL.

Revised and Edited May, 2019.

Website: www.shelluxchemicals.coms

TECHNICAL DATA SHEET

SHELLUX CHEMICALS NIGERIA

Ref: TDS-1005ps

25, Olanrewaju Ariyibi Street,

Product Name: Top-Coat

Abule Onilu by Odo Eran,

Product Code: Depends on Colour

Along Isheri/Lasu Road,

Category: Epoxy System.

Igando-Lagos.

Tel- +234-7065312219, +234-8084357102.

S/N	PROPERTIES	SPECIFICATIONS
1	COLOUR	As per requirement
2	APPEARANCE	Glossy/Semi Glossy/ Matt
3	FINISH	SMOOTH
4	SPECIFIC GRAVITY	1.3KG/Lt
5	VISCOSITY	60SEC-BY VISCOSITY CUP
6	COVERAGE	65 SQ FT/L/COAT
7	MIXING PROPORTION	4A + 1B + 1C
8	THINNER	EPOXY THINNER
9	DRYING TIME TOUCH DRY SURFACE DRY HARD DRY	35MINS 1HR 8HRS
10	OVERCOAT INTERVAL	OVER NIGHT
11	SCRATCH HARD	UP TO 2KG.WT
12	FLEXIBILITY	EXCELLENT
13	POT LIFE	4 YEARS
14	SHELF LIFE	2 YEAR
15	APPLICATIONS	HIGHLY CORROSIVE MATERIALS
16	METHOD OF APPLICATION	BRUSH, ROLLER OR SPRAYING
17	KEEP OUT OF CHILDREN AND INCASE OF ACCIDENT	REPORT TO THE MEDICAL PERSONNEL.

Revised and Edited May, 2019.

Website: www.shelluxchemicals.coms

TECHNICAL DATA SHEET

SHELLUX CHEMICALS NIGERIA

Ref: TDS-2013Af

25, Olanrewaju Ariyibi Street,

Product Name: Anti- Fouling Paint

Abule Onilu by Odo Eran,

Product Code: Gp 2013Af

Along Isheri/Lasu Road,

Category: Epoxy System.

Igando-Lagos.

Tel- +234-7065312219, +234-8084357102.

S/N	PROPERTIES	SPECIFICATIONS
1	COLOUR	Dark Brown
2	APPEARANCE	Matt
3	FINISH	SMOOTH
4	SPECIFIC GRAVITY	1.3KG/Lt
5	VISCOSITY	60SEC-BY VISCOSITY CUP
6	COVERAGE	65 SQ FT/L/COAT
7	MIXING PROPORTION	4A + 2C
8	THINNER	EPOXY THINNER
9	DRYING TIME TOUCH DRY SURFACE DRY HARD DRY	15MINS 1HR 8HRS
10	OVERCOAT INTERVAL	OVER NIGHT
11	SCRATCH HARD	UP TO 2KG.WT
12	FLEXIBILITY	EXCELLENT
13	POT LIFE	4 YEARS
14	SHELF LIFE	2 YEAR
15	APPLICATIONS	HIGHLY CORROSIVE MATERIALS
16	METHOD OF APPLICATION	BRUSH, ROLLER OR SPRAYING
17	KEEP OUT OF CHILDREN AND INCASE OF ACCIDENT	REPORT TO THE MEDICAL PERSONNEL.

Revised and Edited May, 2019.

Website: www.shelluxchemicals.coms

TECHNICAL DATA SHEET

SHELLUX CHEMICALS NIGERIA

Ref: TDS-1100

25, Olanrewaju Ariyibi Street,

Product Name: Coal Tar Black

Abule Onilu by Odo Eran,

Product Code: Gp 1100CB

Along Isheri/Lasu Road,

Category: Epoxy System.

Igando-Lagos.

Tel- +234-7065312219, +234-8084357102.

S/N	PROPERTIES	SPECIFICATIONS
1	COLOUR	Black
2	APPEARANCE	Semi-Gloss
3	FINISH	SMOOTH
4	SPECIFIC GRAVITY	1.25KG/Lt
5	VISCOSITY	60SEC-BY VISCOSITY CUP
6	COVERAGE	65 SQ FT/L/COAT
7	MIXING PROPORTION	4A + 2C
8	THINNER	EPOXY THINNER
9	DRYING TIME TOUCH DRY SURFACE DRY HARD DRY	15MINS 1HR 8HRS
10	OVERCOAT INTERVAL	OVER NIGHT
11	SCRATCH HARD	UP TO 2KG.WT
12	FLEXIBILITY	EXCELLENT
13	POT LIFE	4 YEARS
14	SHELF LIFE	2 YEAR
15	APPLICATIONS	HIGHLY CORROSIVE MATERIALS
16	METHOD OF APPLICATION	BRUSH, ROLLER OR SPRAYING
17	KEEP OUT OF CHILDREN AND INCASE OF ACCIDENT	REPORT TO THE MEDICAL PERSONNEL.

Revised and Edited May, 2019.

Website: www.shelluxchemicals.coms

TECHNICAL DATA SHEET

SHELLUX CHEMICALS NIGERIA

Ref: TDS-3018ZE

25, Olanrewaju Ariyibi Street,

Product Name: Zinc Phosphate Epoxy Paint

Abule Onilu by Odo Eran,

Product Code: Gp 3018ZE

Along Isheri/Lasu Road,

Category: Epoxy System.

Igando-Lagos.

Tel- +234-7065312219, +234-8084357102.

S/N	PROPERTIES	SPECIFICATIONS
1	COLOUR	Dark Brown
2	APPEARANCE	Semi-Gloss/Gloss
3	FINISH	SMOOTH
4	SPECIFIC GRAVITY	1.3KG/L
5	VISCOSITY	60SEC-BY VISCOSITY CUP
6	COVERAGE	65 SQ FT/L/COAT
7	MIXING PROPORTION	4A + 2C
8	THINNER	EPOXY THINNER
9	DRYING TIME TOUCH DRY SURFACE DRY HARD DRY	15MINS 1HR 8HRS
10	OVERCOAT INTERVAL	OVER NIGHT
11	SCRATCH HARD	UP TO 2KG.WT
12	FLEXIBILITY	EXCELLENT
13	POT LIFE	4 YEARS
14	SHELF LIFE	2 YEAR
15	APPLICATIONS	HIGHLY CORROSIVE MATERIALS
16	METHOD OF APPLICATION	BRUSH, ROLLER OR SPRAYING
17	KEEP OUT OF CHILDREN AND INCASE OF ACCIDENT	REPORT TO THE MEDICAL PERSONNEL.

Revised and Edited May, 2019.

Website: www.shelluxchemicals.coms