

MATLAB Onramp

Conclusion

Summary

Summary of MATLAB Onramp

Basic Syntax

Example	Description
<code>x = pi</code>	Create variables and assign values with the equal sign (=). The left side (x) is the variable name, and the right side (pi) is its value.
<code>y = sin(-5)</code>	Provide inputs to a function using parentheses.

Desktop Management

Function	Example	Description
<code>save</code>	save <code>data.mat</code>	Save your current workspace to a MAT-file.
<code>load</code>	load <code>data.mat</code>	Load the variables in a MAT-file to the workspace.
<code>clear</code>	clear	Clear all variables from the workspace.
<code>clc</code>	clc	Clear all text from the Command Window.
<code>format</code>	format <code>long</code>	Change how numeric output appears in the Command Window.

Array Types

Example	Description
<code>4</code>	scalar
<code>[3 5]</code>	row vector
<code>[1;3]</code>	column vector
<code>[3 4 5; 6 7 8]</code>	matrix

Evenly Spaced Vectors

Example	Description
<code>1:4</code>	Create a vector from 1 to 4, spaced by 1, using the colon operator (:) .
<code>1:0.5:4</code>	Create a vector from 1 to 4, spaced by 0.5.
<code>linspace(1,10,5)</code>	Create a vector with 5 elements. The values are evenly spaced from 1 to 10.

Matrix Creation

Example	Description
<code>rand(2)</code>	Create a square matrix with 2 rows and 2 columns.
<code>zeros(2,3)</code>	Create a rectangular matrix with 2 rows and 3 columns of 0s.

<code>ones(2,3)</code>	Create a rectangular matrix with 2 rows and 3 columns of 1 s.
------------------------	---

Array Indexing

Example	Description
<code>A(end,2)</code>	Access the element in the second column of the last row.
<code>A(2,:)</code>	Access the entire second row.
<code>A(1:3,:)</code>	Access all columns of the first three rows.
<code>A(2) = 11</code>	Change the value of the second element of an array to 11.

Array Operations

Example	Description
<pre>[1 2; 3 4] + 1 ans = 2 3 4 5</pre>	Perform array addition .
<pre>[1 1; 1 1]*[2 2; 2 2] ans = 4 4 4 4</pre>	Perform matrix multiplication .
<pre>[1 1; 1 1].*[2 2; 2 2] ans = 2 2 2 2</pre>	Perform element-wise multiplication .

Multiple Outputs

Example	Description
<code>[xrow,xcol] = size(x)</code>	Save the number of rows and columns in x to two different variables.
<code>[xMax,idx] = max(x)</code>	Calculate the maximum value of x and its corresponding index value.

Documentation

Example	Description
<code>doc randi</code>	Open the documentation page for the <code>randi</code> function.

Plots

Example	Description
<code>plot(x,y,"ro--",LineWidth=5)</code>	Plot a red (r) dashed (--) line with a circle (o) marker, with a heavy line width.
<code>hold on</code>	Add the next line to the existing plot.
<code>hold off</code>	Create new axes for the next plotted line.
<code>title("My Title")</code>	Add a title to a plot.
<code>xlabel("x")</code> <code>ylabel("y")</code>	Add labels to axes.
<code>legend("a","b","c")</code>	Add a legend to a plot.

Tables

Example	Description
<code>data.HeightYards</code>	Extract the variable HeightYards from the table data.
<code>data.HeightMeters = data.HeightYards*0.9144</code>	Derive a table variable from existing data.

Logical Indexing

Example	Description
<code>[5 10 15] > 12</code>	Compare the elements of a vector to the value 12.
<code>v1(v1 > 6)</code>	Extract all elements of v1 that are greater than 6.
<code>x(x==999) = 1</code>	Replace all values in x that are equal to 999 with the value 1.

Programming

Example	Description
<pre> if x > 0.5 y = 3 else y = 4 end </pre>	If x is greater than 0.5, set y to 3. Otherwise, set y to 4.
<pre> for c = 1:3 disp(c) end </pre>	The loop counter (c) progresses through the values 1:3 (1, 2, and 3). The loop body displays each value of c.

