4/5#1 \$2 86529 - 5" DIA THRU TO WIRE CHANNEL DIA WOOD DOOR OR FRAME (SIDE VIEW) RECOMMENDED 6" BELOW AUPPER HINGE NOTE: FOR WOOD FIRE DOORS, CONSULT DOOR MANUFACTURER FOR APPROVED LOCATION. REINFORCEMENT .060" (16 GA.) MINIMUM ល្បីយ FRAME FOR POOR EPT IN FRAME MUST ALIGN METAL DOOR OR FRAME (SIDE VIEW) (m) OF EPT IN DOOR เกโต OUTSIDE OF DOOR -<u>1</u>4 س 21. WITH FACE P m m m m √1@ W14 DOOR (OPEN 180°) WHEN INSTALLED . 33" MAX. ញ្ជាំ TYPICAL ALL DIMENSIONS ARE METAL: #10-24 TAPPED HOLE 12 PLACES -14 3 REINF. WOOD: HOLES PREPARED DURING INSTALL FRAME Power Transfer Unit **VON DUPRIN** EPT2, EPT10, & PNT 1 **TEMPLATE** NOTES: SEE MASTER SHEET #10001 FOR SUGGESTED REINFORCING DATE:

40250 a

05-28-13

NUMBER: