

SPECIFICATIONS

Model	Specification	MU5502 (2WD)
Engine	Type	Kubota V2403-M-DI-TE3, Inline FIP E-CDIS, 4 Cylinder, Liquid Cooled
	Displacement	2434 cc
	Backup Torque	35%
	Air Filter	Dry type, dual element
	Clutch	Double Clutch
Transmission	Gear Box	12 Forward + 4 Reverse Main Transmission Synchromesh
	Speeds	Forward 1.8- 30.8 kmph Reverse 5.1 - 14 kmph
Brakes	Type	Oil Immersed Multi Disc Brakes
Front Axle	Type	Fix / Variable 2WD
Hydraulics	Lifting Capacity	1,800 kgf and 2,100 kgf at lift point
	Pump Capacity	29.2 lpm / 36.5 lpm (T)
Steering	Type	Power (Hydraulic Double acting)
Power Take Off	Type	Independent, Dual PTO
	PTO RPM	STD : 540 @2160 ERPM ECO : 750 @2200 ERPM
Wheels & Tyres	Front	7.5 x16/6.5 x 20
	Rear	16.9 x 28
Electrical System	Batter	12 Volt
	Alternator	55 Amp
	Starter Motor	12 Volt, 2.0 kW
Dimensions & Weight	Total weight	2310 kg
	Wheel base	2100 mm
	Overall length	3720 mm
	Overall width	1965 mm
	Ground clearance	420 mm
Other	Turning radius with brakes	2.9 m
	Deck design	Flat Deck
Factory Fitted Options	Fuel Tank Capacity	65 Liters
	Auxiliary Control Valve	
	Reverse PTO (RPTO)	
	2WD Adjustable axle	
	T - TOT variant for Harvesters	

Calculated according to our criteria. The actual capacity you achieve may be different.
The specifications, information, and appearance of the machines herein are subject to change without notice.

Plough



TOT



Super Seeder



Trolly



Quality you can trust on

Kubota received the Deming Prize which is the highest proof of recognition of major advances in quality improvement. Kubota has also received the ISO9001 Certification which is the international standard of quality management systems, the ISO14001 Certification which is the international standards related to environment management, and the OSHAS 18001 Certification which is the international assessment series of occupational health and safety systems.




ISO9001 Certification



The Deming Prize



ISO14001 Certification



OSHAS 18001 Certification



Escorts Kubota Limited

15/5, Mathura Road, Faridabad-121003

Toll Free : 1800 309 1694



Escorts Kubota Limited

MU

MU5502
REMARKABLE ENGINE
REMARKABLE PERFORMANCE



*Disclaimer: A per Japan's Journal GYOKAI, Kubota ranks No.1 (Agt Machinery) for the year 2021 in turnover



E-CDIS Engine



4 Valves System



Balancer Shaft



Synchro Gear
12+4 Speed

*50 HP category, Ability to run most of 55HP implements *T&C Apply

Kubota V2403-M-DI-TE3 Engine Performance with Fuel Efficiency

Excellent Engine Set-up

Same LEGENDARY V2403 Engine is in MU5502

Powerful &
effective
combustion

Less fuel
consumption

Environment
friendly
emission

Low
vibration &
low noise



e-CDIS Technology

Eco-Central Direct
Injection system
for less fuel
consumption



4 Valves System

Better
combustion and
more power



Balancer Shaft

Less
vibration &
low noise



Synchro Gear 12+4 Speed

12F [1.8 to 30.8 kmph]
4R [5.1 to 14 kmph]


MU5502

The **MU5502** is a high performance tractor with better fuel efficiency & reliability leading to high productivity.

Performance



Main
Transmission
Synchronmesh



Independent
PTO with
STD
ECO / RPTO*



High hydraulic
lift capacity
1,800 kgf and 2,100 kgf
(at lift point)



Double acting power
steering with variable
front axle

Comfort




Suspended pedals
improves operator's
comfort




Larger seat with
better suspension,
adjustable &
comfortable for long
operating hours



LED back light
meter panel for easy
operations even at
night with all
safety signs



Flat deck with
rubber mat
for comfortable
operation



Front opening hood
easy to open with
the touch of a knob




Best in class
brake lock



Accessible PTO
speed change lever



Luxurious
accelerator pedal




Telescopic stabilizer
for easy setting


Reliability



5 Fin cerametallic
double clutch 25%
more durability



Clutch fixing
lock for better
clutch reliability



Planetary drive for
better traction



Reliable oil
immersed brakes



World top class
high quality
Japanese NOK
oil seals