Machine Learning Algorithms

Cheatsheet

1. Data Handling & Preprocessing

Pandas / IO

```
df = pd.read_csv("<path>")
df.head() / df.info() / df.describe() / df.columns / df.shape / df.
➥ dtypes
df.value_counts(<normalize=True>)  # Target value counts <or
➥ percentages>
df = df.drop_duplicates().reset_index(drop=True)
df.drop(columns=[<col_list>], inplace=<True/False>)
```

Feature Type Identification / Selection

```
# Select numeric columns
num_colmn = df.select_dtypes(
    include=['int64', 'float64']
).columns

# binary columns
binary_cols = [col for col in df.columns if df[col].nunique() == 2]
```

Nulls & Masks

```
any(df["col"].isna())
any(df["col"].isnull())
mask = df["col"].isna()
df["col"].isnull().sum()
```

Fill / Impute

```
df["col"].fillna(value=<value>, inplace=<True/False>)
from sklearn.impute import SimpleImputer
imp = SimpleImputer(missing_values=np.nan,    strategy=<"mean"/"median
➥ "/"most_frequent">)
X = imp.fit_transform(X)
```

Outlier Analysis and Removal

```
Q1 = <df>[<col>].quantile(0.25)
Q3 = <df>[<col>].quantile(0.75)
IQR = Q3 - Q1
lower_bound = Q1 - 1.5 * IQR
upper_bound = Q3 + 1.5 * IQR
<df> = <df>[(<df>[<col>] >= lower_bound) & (<df>[<col>] <= upper_bound
➥ )]
```

Descriptive

```
df["col"].mean(), df["col"].median(), df["col"].mode(), df["col"].std
➥ (), df["col"].quantile(<k>)
```

Transformations

```
trans = np.log1p(df["col"])  # if data is not normal
orig = np.expm1(trans)  # inverse log1p
df["col"] = np.where(<condition>, <true_val>, <false_val>)
```

Scaling & Encoding

```
from sklearn.preprocessing import StandardScaler, MinMaxScaler
from sklearn.preprocessing import MaxAbsScaler, RobustScaler
X_std = StandardScaler().fit_transform(X)  # normal
X_min = MinMaxScaler().fit_transform(X)  # bounded
X_maxabs = MaxAbsScaler().fit_transform(X)  # sparse_data

from sklearn.preprocessing import PolynomialFeatures
X_poly = PolynomialFeatures(
    degree=<d>, include_bias=<True/False>
).fit_transform(X)
X_robust = RobustScaler().fit_transform(X)  # outliers(Extreme)

from sklearn.preprocessing import LabelBinarizer  # for target
lb = LabelBinarizer(
    neg_label=<0>, pos_label=<1>, sparse_output=<False>
)
y_bin = lb.fit_transform(y)  # multiclass: same output as one-hot
y_inv = lb.inverse_transform(y_bin)

from sklearn.preprocessing import OrdinalEncoder, OneHotEncoder,
➥ LabelEncoder
X_le = LabelEncoder().fit_transform(X_cat)
X_ord = OrdinalEncoder().fit_transform(X_cat)
X_ord = OrdinalEncoder(categories=<categories_list>).fit_transform(
➥ X_cat)
X_oh = OneHotEncoder(
    handle_unknown=<"ignore"/"error">
).fit_transform(X_cat).toarray()
```

Polynomial Regression

```
from sklearn.preprocessing import PolynomialFeatures
from sklearn.linear_model import LinearRegression
from sklearn.pipeline import make_pipeline

# Polynomial Regression = PolynomialFeatures + LinearRegression
poly_reg = make_pipeline(
    PolynomialFeatures(degree=<d>, include_bias=False),
    LinearRegression()
)
poly_reg.fit(X_train, y_train)
y_pred = poly_reg.predict(X_test)
```

Split

```
from sklearn.model_selection import train_test_split
X_train, X_test, y_train, y_test = train_test_split(
    X, y, test_size=<float(from 0 to 1)>, random_state=<int>, stratify
➥ =<y_or_None>  # test_size: 0=no test, 1=100% test
)
```

2. Supervised Learning Models (Syntactic)

Pipeline

```
from sklearn.pipeline import make_pipeline
pipe = make_pipeline(<step1>, <step2>, ...)
```

```
# Example steps: impute -> scale -> classify
pipe = make_pipeline(
    SimpleImputer(strategy="median"),
    StandardScaler(),
    LogisticRegression()
)
```

Linear & Logistic

```
from sklearn.linear_model import LinearRegression, Ridge, Lasso,
➥ LogisticRegression
LinearRegression()
Ridge(alpha=<alpha>)
Lasso(alpha=<alpha>)
LogisticRegression(
    penalty=<"l1"/"l2"/"elasticnet"/"none">,
    C=<float>,
    solver=<"liblinear"/"saga"/"lbfgs">,
    l1_ratio=<float_or_None>,
    random_state=<int>
)
```

```
# Example: linear regression
lin_reg = LinearRegression()
lin_reg.fit(X_train, y_train)
y_pred = lin_reg.predict(X_test)
lin_reg.coef_, lin_reg.intercept_
```

Decision Tree

```
from sklearn.tree import DecisionTreeClassifier, DecisionTreeRegressor
DecisionTreeClassifier(
    criterion=<"gini"/"entropy">,
    max_depth=<int_or_None>,
    min_samples_split=<int>,
    min_samples_leaf=<int>,
    random_state=<int>
)
DecisionTreeRegressor(
    criterion=<"squared_error"/"friedman_mse"/"absolute_error">,
    max_depth=<int_or_None>,
    min_samples_split=<int>,
    random_state=<int>
)
```

Naive Bayes, KNN, SVM

```
from sklearn.naive_bayes import GaussianNB, MultinomialNB
from sklearn.svm import SVC, SVR
GaussianNB()  # no scaling needed
MultinomialNB()  # non-negative inputs only
BernoulliNB()
KNeighborsClassifier(n_neighbors=<int>,
                     algorithm=<"auto"/"ball_tree"/"kd_tree">)  #
➥ needs scaling
SVC(kernel=<"linear"/"poly"/"rbf"/"sigmoid">,
    C=<float>, degree=<int>, gamma=<"scale"/"auto">,
    probability=<True/False>, random_state=<int>)  # needs scaling;
➥ probability=True for predict_proba
SVR(
    kernel=<"linear"/"poly"/"rbf"/"sigmoid">,
    C=<float>,
    degree=<int>,           # for 'poly' kernel
    gamma=<"scale"/"auto">,  # kernel coefficient
    epsilon=<float>         # tolerance margin in regression
)
```

Bagging & RandomForest

```
from sklearn.ensemble import (BaggingClassifier, BaggingRegressor,
                              RandomForestClassifier,
➥ RandomForestRegressor)
BaggingClassifier(estimator=<est>, n_estimators=<int>, max_samples=<
➥ float>,
                  max_features=<float>, random_state=<int>)
RandomForestClassifier(n_estimators=<int>, criterion=<"gini"/"entropy"
➥ >,
                       max_depth=<int_or_None>, min_samples_split=<int
➥ >,
                       max_features=<"sqrt"/"log2"/<float>>,
➥ random_state=<int>)
BaggingRegressor(...)  # same params as BaggingClassifier
RandomForestRegressor(n_estimators=<int>, criterion=<"squared_error"/"
➥ absolute_error"/"friedman_mse"/"poisson">,
                      max_depth=<int_or_None>, min_samples_split=<int
➥ >,
                      max_features=<1.0/"sqrt"/"log2"/<float>>,
➥ random_state=<int>)  # default max_features=1.0
```

Boosting

```
from sklearn.ensemble import (AdaBoostClassifier, AdaBoostRegressor,
                              GradientBoostingClassifier,
➥ GradientBoostingRegressor)
from xgboost import XGBClassifier, XGBRegressor

AdaBoostClassifier(
    estimator=DecisionTreeClassifier(...),
    n_estimators=<int>, learning_rate=<float>, random_state=<int>
)
AdaBoostRegressor(
    estimator=DecisionTreeRegressor(...),
    n_estimators=<int>, learning_rate=<float>,
    loss=<"linear"/"square"/"exponential">, random_state=<int>
)

GradientBoostingClassifier(
    n_estimators=<int>, learning_rate=<float>, max_depth=<int>,
    min_samples_split=<int>, min_samples_leaf=<int>,
    subsample=<float>, max_features=<"sqrt"/"log2">, random_state=<int
➥ >
)
GradientBoostingRegressor(
    loss=<"squared_error"/"absolute_error"/"huber"/"quantile">,
    alpha=<float>,  # huber / quantile only
    n_estimators=<int>, learning_rate=<float>, max_depth=<int>,
    min_samples_split=<int>, min_samples_leaf=<int>,
    subsample=<float>, max_features=<"sqrt"/"log2">, random_state=<int
➥ >
)

XGBClassifier(
    use_label_encoder=<False/True>, eval_metric=<"logloss">,
    n_estimators=<int>, max_depth=<int>, learning_rate=<float>,
    subsample=<float>, random_state=<int>
)
XGBRegressor(
    objective=<"reg:squarederror"/"reg:absoluteerror">,
    eval_metric=<"rmse"/"mae">,  # no use_label_encoder
    n_estimators=<int>, max_depth=<int>, learning_rate=<float>,
    subsample=<float>, random_state=<int>
)
```

Stacking

```
from sklearn.ensemble import StackingClassifier, StackingRegressor
StackingClassifier(
    estimators=[("<n>", <estimator>), ...],
    final_estimator=<estimator>, cv=<int>, n_jobs=<int>
)
StackingRegressor(
    estimators=[("<n>", <estimator>), ...],
    final_estimator=<regressor>, cv=<int>, n_jobs=<int>
)
```

General

```
model.fit(<X_train>, <y_train>)
y_pred = model.predict(<X_test>)
y_proba = model.predict_proba(<X_test>)[:, <class_index>]
score = model.score(<X_test>, <y_test>)
```

3. Unsupervised Learning Models (Syntactic)

K Means

```
from sklearn.cluster import KMeans
kmeans = KMeans(
    n_clusters=<int>, random_state=<int>
)
kmeans.fit(<X>)
wcss = kmeans.inertia_
labels = kmeans.labels_
centers = kmeans.cluster_centers_

from sklearn.metrics import silhouette_score
sil = silhouette_score(<X>, labels)  # -1 to 1, higher is better
```

4. Validation & Hyperparam Search

K-Fold & CV

```
from sklearn.model_selection import (KFold, cross_val_score,
➥ cross_validate,
                                     StratifiedKFold)
KFold(n_splits=<int>, shuffle=<True/False>, random_state=<int>)
StratifiedKFold(
    n_splits=<int>,
    shuffle=<True/False>,
    random_state=<int>
)
```

```
cross_val_score(estimator=<model>,
                X=<X>, y=<y>,
                cv=<int_or_KFold>, scoring=<metric>,
                return_train_score=<True/False>)
```

Grid / Randomized Search

```
from sklearn.model_selection import GridSearchCV, RandomizedSearchCV
search = GridSearchCV(estimator=<model>,
                      param_grid={<param>: [<values>], ...},
                      cv=<int_or_KFold>,
                      scoring=<metric>,
                      n_jobs=<int>)
search = RandomizedSearchCV(estimator=<model>,
                            param_distributions={<param>: [<values>],
➥ ...},
                            n_iter=<int>, cv=<int>, scoring=<metric>,
➥ n_jobs=<int>)
search.best_estimator_
search.cv_results_
search.best_score_
search.best_params_
```

Minimal example (tune KNN with GridSearchCV):

```
from sklearn.model_selection import GridSearchCV
from sklearn.neighbors import KNeighborsClassifier

search = GridSearchCV(
    estimator=KNeighborsClassifier(),
    param_grid={"n_neighbors": [3, 5, 7]},
    cv=5, scoring="accuracy", n_jobs=-1
)
search.fit(X_train, y_train)
print(search.best_params_, search.best_score_)
y_pred = search.best_estimator_.predict(X_test)
```

Minimal example (same KNN with RandomizedSearchCV):

```
from sklearn.model_selection import RandomizedSearchCV
from sklearn.neighbors import KNeighborsClassifier

search = RandomizedSearchCV(
    estimator=KNeighborsClassifier(),
    param_distributions={"n_neighbors": range(1, 10),
                         "algorithm": ["kd_tree", "ball_tree"]},
    n_iter=5, cv=5, scoring="accuracy", n_jobs=-1, random_state=42
)
search.fit(X_train, y_train)
print(search.best_params_, search.best_score_)
y_pred = search.best_estimator_.predict(X_test)
```

5. Metrics & Visualization

Note: y_test = y_true

Classification Metrics

```
from sklearn.metrics import (
    accuracy_score, precision_score, recall_score, f1_score,
    confusion_matrix, classification_report, roc_auc_score,
    roc_curve, average_precision_score
)
accuracy_score(<y_true>, <y_pred>)
precision_score(<y_true>, <y_pred>,
                average=<"binary"/"micro"/"macro"/"weighted">)
recall_score(<y_true>, <y_pred>)
f1_score(<y_true>, <y_pred>)
confusion_matrix(<y_true>, <y_pred>)
classification_report(<y_true>, <y_pred>)
```

Probabilistic / ROC

```
y_proba = model.predict_proba(<X_test>)[:, <class_index>]
fpr, tpr, thr = roc_curve(<y_true>, <y_proba>)
auc = roc_auc_score(<y_true>, <y_proba>)
```

Regression Metrics

```
from sklearn.metrics import r2_score, mean_squared_error,
➥ mean_absolute_error
r2_score(<y_true>, <y_pred>)
adjusted_r2 = 1 - (1 - r2)*(n - 1)/(n - p - 1)
mean_squared_error(<y_true>, <y_pred>)
mean_absolute_error(<y_true>, <y_pred>)
```

Clustering Metrics

```
from sklearn.metrics import (
    silhouette_score,
    calinski_harabasz_score,
    davies_bouldin_score,
    adjusted_rand_score,
    normalized_mutual_info_score
)
silhouette_score(<X>, <labels>)
calinski_harabasz_score(<X>, <labels>)
davies_bouldin_score(<X>, <labels>)
adjusted_rand_score(<y_true>, <labels>)
normalized_mutual_info_score(<y_true>, <labels>)
```

Minimal example:

```
from sklearn.cluster import KMeans
from sklearn.metrics import silhouette_score
labels = KMeans(n_clusters=3, random_state=42).fit_predict(X)
print(silhouette_score(X, labels))
```

Visualization (Syntactic)

```
# ================ Confusion Matrix ================
sns.heatmap(
    <conf_matrix>,
    annot=<True/False>,
    fmt="<fmt>",
    cmap="<cmap>",
    xticklabels=<labels>,
    yticklabels=<labels>
)
from sklearn.metrics import ConfusionMatrixDisplay
ConfusionMatrixDisplay.from_predictions(y_true, y_pred)

# ================ ROC Curve ================
from sklearn.metrics import roc_curve
fpr, tpr, thr = roc_curve(<y_true>, <y_score>)
plt.plot(fpr, tpr)
plt.plot([0,1], [0,1], linestyle="<ls>")  # "-" solid, "--" dashed,
➥ "-." dash-dot, ":" dotted
from sklearn.metrics import RocCurveDisplay
RocCurveDisplay.from_predictions(y_true, y_score)

# ================ Precision-Recall Curve ================
from sklearn.metrics import PrecisionRecallDisplay
PrecisionRecallDisplay.from_predictions(y_true, y_score)

# ================ Regression & Scatter ================
sns.regplot(
    x=<y_true>,
    y=<y_pred>,
    ci=<int_or_None>
)
sns.scatterplot(
    x=<x>,
    y=<y>,
    hue=<col_or_None>
)

# ================ Feature Importance ================
plt.bar(<feature_names>, <coef_or_importance>)
plt.barh(<feature_names>, <importance>)

# ================ Subplots ================
fig, axes = plt.subplots(
    nrows=<int>,
    ncols=<int>,
    figsize=(<width>, <height_per_row> * nrows)
)

# ================ Histograms & Boxplots ================
plt.hist(
```

```
    <data>,
    bins=<int>,
    color="<color>",
    edgecolor="<color>"
)
sns.histplot(
    data=<DataFrame>,
    x=<column>,
    bins=<int>,
    color="<color>",
    edgecolor="<color>",
    ax=<axes[i]>
)
sns.boxplot(
    data=<DataFrame>,
    x=<column>,
    ax=<axes[i]>
)

# ================= Classification / Clustering Scatter
➥ =================
sns.scatterplot(
    x=<1d_X>,
    y=<1d_Y>,
    hue=<labels>,
    palette="<deep/tab10/coolwarm>",
    legend="<full/brief/False>",
    s=<int>
)
sns.scatterplot(
    x=X[:,0],
    y=X[:,1],
    hue=labels
)

# ================= Learning / Validation Curves =================
plt.plot(train_sizes, train_scores.mean(axis=1))
plt.plot(train_sizes, val_scores.mean(axis=1))
plt.plot(param_range, train_scores.mean(axis=1))
plt.plot(param_range, val_scores.mean(axis=1))

# ================= Dimensionality Reduction =================
plt.scatter(X_pca[:,0], X_pca[:,1], c=y)
plt.scatter(X_tsne[:,0], X_tsne[:,1], c=y)

# ================= Error / Residual Analysis =================
residuals = y_true - y_pred
plt.scatter(y_pred, residuals)
plt.axhline(0, color="<color>", linestyle="<style>")
sns.kdeplot(residuals)
plt.plot(y_true, y_pred, 'o')
plt.plot(
    [min(y_true), max(y_true)],
    [min(y_true), max(y_true)]
)

# ================= Training Dynamics =================
plt.plot(history.history["loss"])
plt.plot(history.history["val_loss"])
```

6. Principal Component Analysis

```
from sklearn.decomposition import PCA
pca = PCA(
    n_components=<float_or_int>,  # e.g., 0.95 or 2
    random_state=<int>
)
X_train_pca = pca.fit_transform(X_train)
X_test_pca = pca.transform(X_test)
pca.explained_variance_ratio_
pca.singular_values_
```

7. Statistical Significance Test

```
from scipy.stats import friedmanchisquare, f_oneway

model_scores = [
    [<score1>, <score2>, ...],  # Model 1
    [<score1>, <score2>, ...],  # Model 2
    ...                         # Model k
]

# Friedman Test (non-parametric)
friedman_stat, friedman_p = friedmanchisquare(*model_scores)

# One-way ANOVA Test (parametric)
anova_stat, anova_p = f_oneway(*model_scores)

if friedman_p < 0.05:
    print("Significant difference among models | proceed with post-hoc
➥  test")
else:
    print("No significant difference | all models perform similarly")

if anova_p < 0.05:
    print("At least one model differs significantly")
else:
    print("No significant difference detected")
```

```
from scipy.stats import ttest_rel, ttest_ind, wilcoxon

# Paired t-test (parametric)
paired_stat, paired_p = ttest_rel(model1_scores, model2_scores)

# Independent t-test (parametric)
ind_stat, ind_p = ttest_ind(model1_scores, model2_scores, equal_var=
➥ False)

# Wilcoxon signed-rank test (non-parametric, paired)
wilcoxon_stat, wilcoxon_p = wilcoxon(model1_scores, model2_scores)

if paired_p < 0.05:
    print("Paired t-test: Significant difference")
else:
    print("Paired t-test: No significant difference")

if ind_p < 0.05:
    print("Independent t-test: Significant difference")
else:
    print("Independent t-test: No significant difference")

if wilcoxon_p < 0.05:
    print("Wilcoxon: Significant difference")
else:
    print("Wilcoxon: No significant difference")
```

8. Available Metric Strings (sklearn)

```
# Classification:
"accuracy", "precision", "recall", "f1",
"f1_micro", "f1_macro", "f1_weighted",
"precision_micro", "precision_macro", "precision_weighted",
"recall_micro", "recall_macro", "recall_weighted",
"roc_auc", "average_precision"

# Regression:
"r2",
"neg_mean_squared_error",
"neg_root_mean_squared_error",
"neg_mean_absolute_error",
"neg_median_absolute_error",
"explained_variance"
```

9. Miscellaneous (NumPy & Pandas)

```
# NumPy
np.sqrt(<x>), np.exp(<x>), np.log(<x>)
np.log1p(<x>), np.expm1(<x>)
np.mean(<x>), np.median(<x>), np.std(<x>), np.var(<x>)
np.max(<x>), np.min(<x>), np.argmax(<x>), np.argmin(<x>)
np.unique(<x>), np.dot(<a>,<b>)
np.linalg.inv(<A>), np.linalg.det(<A>)
np.corrcoef(<x>,<y>)
np.linspace(<start>,<stop>,<num>), np.arange(<start>,<stop>,<step>)
np.random.rand(<n>), np.random.randn(<n>), np.random.seed(<int>)
np.percentile(<data>,<q>)

# Pandas quick
df.head(<n>), df.tail(<n>), df.sample(<n>)
df.isnull().sum(), df.dropna(axis=<0_or_1>)
df.groupby(<cols>).agg({<col>: <func>})
```

Parameter Grids

KNN

- n_neighbors: range(1, 10)
- algorithm: "kd_tree" or "ball_tree"

SVM

- 'C': [0.1, 1, 10]
- gamma: 'scale', 'auto' (only for rbf / poly / sigmoid)
- degree: 2, 3 (only for poly)

Decision Tree

- 'max_depth': [None, 3, 5, 7, 10]
- 'min_samples_split': [2, 5, 10]
- 'min_samples_leaf': [1, 2, 4]
- 'criterion': ['gini', 'entropy']

AdaBoost

- 'n_estimators': [50, 100, 200]
- 'learning_rate': [0.01, 0.1, 1]
- 'estimator': [DecisionTreeClassifier(max_depth=1, random_state=42), DecisionTreeClassifier(max_depth=2, random_state=42)]

Gradient Boosting

- 'n_estimators': [50, 100, 200]
- 'learning_rate': [0.01, 0.1, 0.2]
- 'max_depth': [1, 3, 5]
- 'subsample': [0.8, 1.0]

XGBoost

- 'n_estimators': [50, 100, 200]
- 'learning_rate': [0.01, 0.1, 0.2]
- 'max_depth': [3, 5, 7]
- 'gamma': [0, 0.1, 0.3]
- 'subsample': [0.8, 1.0]
- 'colsample_bytree': [0.8, 1.0]

Random Forest

- 'n_estimators': [50, 100, 200]
- 'max_depth': [None, 5, 10]
- 'criterion': ['gini', 'entropy']
- 'max_features': ['sqrt', 'log2']
- 'min_samples_split': [2, 5, 10]

Grid Search Template

```
grid_search = GridSearchCV(
    estimator=dt,
    param_grid=param_grid,
    cv=5,                # 5-fold cross validation
    scoring='accuracy',  # Metric to optimize
    n_jobs=-1            # Use all CPU cores
)
grid_search.fit(x_train, y_train)
best_model = grid_search.best_estimator_
y_pred = best_model.predict(x_test)
print("best parameters :", grid_search.best_params_)
print("best score :", grid_search.best_score_)
dtaccuracy = accuracy_score(y_test, y_pred)

results_df = pd.DataFrame(grid_search.cv_results_)
best_idx = grid_search.best_index_
print("\nFold-wise accuracy for best parameters:")
print(results_df.loc[best_idx, [c for c in results_df.columns if
                                c.startswith('split')]])
```

Post-hoc Testing

```
model_means = [np.mean(scores) for scores in model_scores]
best_index = np.argmax(model_means)  # or np.argmin if lower is better
print(f"Best model: Model {best_index + 1} with mean score = {
➥ model_means[best_index]:.4f}")
```