

• .NET Core :-

Nuget Package Manager

↳ Microsoft. Data. SqlClient

↓

ADO.NET Connected Architecture.

↳ Developer opens and closes

Db connection manually.

SqlConnection Cn → establish connection
with Db using connectionString

Data Source = Server =	Initial Catalog = Database =	Integrated Security = User Name =, Password =
---------------------------	---------------------------------	--

SqlCommand cmd $\Rightarrow$ new SqlCommand

("Select Query - " / "constraints")

Con. Open();

Factory Method.

IDataReader reader = cmd.ExecuteReader()

SqlDataReader
while (reader.Read()) ^{0, 1, 2, 3} 1 / false

(int) reader ["Id"] $\rightarrow$

	0	Emp	1	2
		Id	Name	Address
row[0]	0	1	HJ	NYC
1	1	2	JH	LA

Cuit
 D = n
 Data Base

row [0] is collection of 3 columns.

row [0][1] → Name Column Value = HJ

row[0]["Name"]

Database

class DataSet

Emp
DataTable

Id	name	Addr
1	KS	NYC
2	TH	LA
3	PP	London

class DataRow

class DataColumn

Cust

Dept

RAM

m/c

.NET

POCO
DbContent

Select

List < Emp >

Emp

RAM

Table [Emp] ✓

Id	Name	Address
1	KS	NYC
2	TH	LA
3	PP	London

Database

m/c
buffer

ADO.NET

Connected

Architecture

SqlConnection
Open()

Close()

Select =

Insert

Update

Delete

Disconnected
Architecture

SqlConnection

SqlDataAdapter

↓

SelectQuery

DataSet / DataTable

DataTable dt
Columns.
Rows.

DataColumn col1 = ("Id", type(int))
col2 = ("Name", type(str))
col3 = ("Address", type(str))

dt. columns. Add(col1, col2, col3)

DataRow row = dt.NewRow();

[0:Id, 1:Name, 2:Address]

row["Id"] = Convert.ToInt32
 (order["Id"])

dt.Rows.Add(row);

th	0	1	2
*	Id	Name	Address
r0			
r1			
r2			

↑
int
↓
Pkey
↑
str
↓
str

DataTable dt = "Emp"

Id	Name	Addr
1	KD	NY
2	TK	LA
3	IM	Pu
4	Ron	Ron

3

1

SqlCommandBuilder
and create
Insert Query

Observe
Collection

recor-
add.

Insert into
Emp values
(4, 'Ron', 'Ron')

1		
2		
3		
4		

-NET
Coll.