



API User Guide

Version 1.0



Table of Contents

API Listing	4
Our List of API includes the following APIs with relevant details:.....	4
Authorization	4
E-COM API Listing	5
Authentication	5
Booking – Create.....	6
Booking – Create Cost Center Code	13
Booking – Cancel.....	14
Booking – Payment Invoice	15
Booking – Reverse.....	17
Booking – Get CN Update	18
CN Print	18
Inquiry – Cost Center Inquiry	19
Payment – Status	21
Payment – Detail.....	22
Setup – Area Code	24
Setup – Block Code	26
Setup – Country List.....	27
Setup – City list by Country	28
Setup – Route List	29
Setup – Delivery Status List	31
Tracking	32
Status Codes	34



Overview:

To test the complete set of product APIs & get better understanding of TCS API integration visit, please visit:
<https://ociconnect.tcscourier.com/ecom/index.html>

Available APIs:

Check the list of available APIs at: <https://ociconnect.tcscourier.com/ecom/index.html>

Sandbox Access:

Below is the link for UAT and production portals.

<https://devconnect.tcscourier.com/ecom/index.html>

Production Access:

If you need production access, you must proceed with the successful UAT phase. Please note that production access approval/setup will take at least three working days.

<https://ociconnect.tcscourier.com/ecom/index.html>



API Listing

Our List of API includes the following APIs with relevant details:

Authorization

API Name	Authorization																																			
Description	To get bearer token to access authorized APIs																																			
Sandbox/Developer Link	https://devconnect.tcscourier.com/auth/api/auth																																			
Production Link	https://ociconnect.tcscourier.com/auth/api/auth																																			
API Method	GET																																			
API Body	<table><tr><th>S No.</th><th>Parameter</th><th>Mandatory</th><th>Data Type</th><th>Remarks</th></tr><tr><td>1</td><td>clientId</td><td>Yes</td><td>Number</td><td>To be provided by TCS</td></tr><tr><td>2</td><td>clientsecret</td><td>Yes</td><td>String</td><td>To be provided by TCS</td></tr><tr><td colspan="5">Response Parameters</td></tr><tr><td>1</td><td>accesstoken</td><td>Yes</td><td>String</td><td></td></tr><tr><td>2</td><td>expiry</td><td>Yes</td><td>Date</td><td>Token expiry date and time</td></tr><tr><td>3</td><td>userinformation</td><td>No</td><td>String</td><td></td></tr></table>	S No.	Parameter	Mandatory	Data Type	Remarks	1	clientId	Yes	Number	To be provided by TCS	2	clientsecret	Yes	String	To be provided by TCS	Response Parameters					1	accesstoken	Yes	String		2	expiry	Yes	Date	Token expiry date and time	3	userinformation	No	String	
S No.	Parameter	Mandatory	Data Type	Remarks																																
1	clientId	Yes	Number	To be provided by TCS																																
2	clientsecret	Yes	String	To be provided by TCS																																
Response Parameters																																				
1	accesstoken	Yes	String																																	
2	expiry	Yes	Date	Token expiry date and time																																
3	userinformation	No	String																																	
JSON Body Request/Payload	<pre>{ "clientId": "205659575", "clientsecret": "YWxuYXNlZWJkYWlyeWZvb2RAdGNzYm9va==" }</pre>																																			
API Success Response	<pre>{ "result": { "accessToken": "eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXZWl0eWZvb2RAdGNzYm9va==", "expiry": "2027-01-04T05:08:47Z", "userInformation": null }, "status": true, "code": "0200" }</pre>																																			
Failure Response	<pre>{ "result": null, "status": false, "code": "401" }</pre>																																			



E-COM API Listing

Authentication

API Name	Authentication																																							
Description	To obtain access token and gain access to permitted APIs, utilize this API.																																							
Sandbox/Developer Link	https://devconnect.tcscourier.com/ecom/api/authentication/token																																							
Production Link	https://ociconnect.tcscourier.com/ecom/api/authentication/token																																							
API Method	GET																																							
Access Token	Provided in Authentication API																																							
API Body	<table><tr><th>S No.</th><th>Parameter</th><th>Mandatory</th><th>Data Type</th><th>Remarks</th></tr><tr><td>1</td><td>username</td><td>Yes</td><td>String</td><td>To be provided by TCS</td></tr><tr><td>2</td><td>password</td><td>Yes</td><td>String</td><td>To be provided by TCS</td></tr><tr><td colspan="5">Response Parameters</td></tr><tr><td>1</td><td>accesstoken</td><td>Yes</td><td>String</td><td></td></tr><tr><td>2</td><td>expiry</td><td>Yes</td><td>Date</td><td>Token expiry date & time</td></tr><tr><td>3</td><td>message</td><td>No</td><td>String</td><td></td></tr></table>					S No.	Parameter	Mandatory	Data Type	Remarks	1	username	Yes	String	To be provided by TCS	2	password	Yes	String	To be provided by TCS	Response Parameters					1	accesstoken	Yes	String		2	expiry	Yes	Date	Token expiry date & time	3	message	No	String	
	S No.	Parameter	Mandatory	Data Type	Remarks																																			
	1	username	Yes	String	To be provided by TCS																																			
	2	password	Yes	String	To be provided by TCS																																			
	Response Parameters																																							
	1	accesstoken	Yes	String																																				
	2	expiry	Yes	Date	Token expiry date & time																																			
	3	message	No	String																																				
JSON Body Request/Payload	{ "username": "abc", "password": "123" }																																							
API Success Response	{ "accesstoken": "jcgwsU85g+loIFikVpysWUQ/0sycayn1fOKUHbanhNc4Hix21+9FtBgTNT+17xcw8hCA/m0WK Wvj1WdkCRRamFiwoEIcst9yGRPksWtz1YzAeo2sIQBv6vbf8H2yFRSc4bD4oCpQznmOuzRLumY Gj0B15qJnVczoG1WHo=", "expiry": "2027-06-08T09:01:25.0704875Z", "message": "success", "traceid": "f6a5843c-e60a-40d7-8cf1-607d26d8a4f2" }																																							
Failure Response	{ "result": null, "status": false, "code": "401" }																																							



Booking – Create

API Name	Create Booking																																																																					
Description	To schedule and confirm new shipments.																																																																					
Sandbox/Developer Link	https://devconnect.tcscourier.com/ecom/api/booking/create																																																																					
Production Link	https://ociconnect.tcscourier.com/ecom/api/booking/create																																																																					
API Method	POST																																																																					
Bearer Token	Provided in Authorization API																																																																					
API Body	<table><tr><th>S.No.</th><th>Parameter</th><th>Date Type</th><th>Mandatory</th><th>Remarks</th></tr><tr><td>1</td><td>accesstoken</td><td>String</td><td>Yes</td><td>Provided by TCS</td></tr><tr><td>2</td><td>consignmentno</td><td>Number</td><td>No</td><td>Not mapped</td></tr><tr><td colspan="5">Shipper Info</td></tr><tr><td>1</td><td>tcsaccount</td><td>String (12)</td><td>Yes</td><td>Provided by TCS Max Length: 12 Min Length: 3</td></tr><tr><td>2</td><td>shippername</td><td>String (50)</td><td>Yes</td><td>Max Length: 50 Min Length: 3</td></tr><tr><td>3</td><td>address1</td><td>String (120)</td><td>Yes</td><td>Max Length: 120 Min Length: 3</td></tr><tr><td>4</td><td>address2</td><td>String (120)</td><td>No</td><td>Max Length: 120 Min Length: 3</td></tr><tr><td>5</td><td>address3</td><td>String (120)</td><td>No</td><td>Max Length: 120 Min Length: 3</td></tr><tr><td>6</td><td>Zip</td><td>String (6)</td><td>No</td><td>Max Length: 6 Min Length: 3</td></tr><tr><td>7</td><td>countrycode</td><td>String (2)</td><td>Yes</td><td>Max Length: 2 Min Length: 2</td></tr><tr><td>8</td><td>countryname</td><td>String (50)</td><td>Yes</td><td>Max Length: 50 Min Length: 3</td></tr><tr><td>9</td><td>citycode</td><td>String (5)</td><td>No</td><td>Max Length: 5</td></tr></table>					S.No.	Parameter	Date Type	Mandatory	Remarks	1	accesstoken	String	Yes	Provided by TCS	2	consignmentno	Number	No	Not mapped	Shipper Info					1	tcsaccount	String (12)	Yes	Provided by TCS Max Length: 12 Min Length: 3	2	shippername	String (50)	Yes	Max Length: 50 Min Length: 3	3	address1	String (120)	Yes	Max Length: 120 Min Length: 3	4	address2	String (120)	No	Max Length: 120 Min Length: 3	5	address3	String (120)	No	Max Length: 120 Min Length: 3	6	Zip	String (6)	No	Max Length: 6 Min Length: 3	7	countrycode	String (2)	Yes	Max Length: 2 Min Length: 2	8	countryname	String (50)	Yes	Max Length: 50 Min Length: 3	9	citycode	String (5)	No	Max Length: 5
	S.No.	Parameter	Date Type	Mandatory	Remarks																																																																	
	1	accesstoken	String	Yes	Provided by TCS																																																																	
	2	consignmentno	Number	No	Not mapped																																																																	
	Shipper Info																																																																					
	1	tcsaccount	String (12)	Yes	Provided by TCS Max Length: 12 Min Length: 3																																																																	
	2	shippername	String (50)	Yes	Max Length: 50 Min Length: 3																																																																	
	3	address1	String (120)	Yes	Max Length: 120 Min Length: 3																																																																	
	4	address2	String (120)	No	Max Length: 120 Min Length: 3																																																																	
	5	address3	String (120)	No	Max Length: 120 Min Length: 3																																																																	
	6	Zip	String (6)	No	Max Length: 6 Min Length: 3																																																																	
	7	countrycode	String (2)	Yes	Max Length: 2 Min Length: 2																																																																	
	8	countryname	String (50)	Yes	Max Length: 50 Min Length: 3																																																																	
	9	citycode	String (5)	No	Max Length: 5																																																																	



				Min Length: 0
	10	cityname	String (50)	Yes Max Length: 50 Min Length: 3
	11	mobile	Number (11)	Yes Like (0300xxxxxxx) Max Length: 11 Min Length: 11
	Consignee Info			
	1	consignee code	String (10)	No Max Length: 10 Min Length: 2
	2	firstname	String (50)	Yes Max Length: 50 Min Length: 3
	3	middlename	String (50)	Yes Max Length: 50 Min Length: 3
	4	lastname	String (50)	No Max Length: 50 Min Length: 3
	5	address1	String (120)	Yes Max Length: 120 Min Length: 3
	6	address2	String (120)	No Max Length: 120 Min Length: 3
	7	address3	String (120)	No Max Length: 120 Min Length: 3
	8	zip	String (6)	No Max Length: 6 Min Length: 0
	9	countrycode	String (2)	Yes Max Length: 2 Min Length: 2
	10	countryname	String (50)	Yes Max Length: 50 Min Length: 3
	11	citycode	String (5)	No Max Length: 5 Min Length: 3



API User Guide
Version 1.0

	12	cityname	String (50)	Yes	Max Length: 50 Min Length: 3
	13	Email	String (50)	No	Max Length: 50 Min Length: 3
	14	areacode	String (5)	No	Max Length: 5 Min Length: 3
	15	areaname	String (50)	No	Max Length: 50 Min Length: 3
	16	blockcode	String (5)	No	Max Length: 5 Min Length: 3
	17	blockname	String (50)	No	Max Length: 50 Min Length: 3
	18	lat	String (50)	No	Max Length: 50 Min Length: 3
	19	lng	String (50)	No	Max Length: 50 Min Length: 3
	20	landmark	String (200)	No	Max Length: 200 Min Length: 0
	21	mobile	Number (11)	Yes	Like (0300xxxxxxx) Max Length: 11 Min Length: 11
	Vendor Info				
	1	name	String (50)	No	Max Length: 50 Min Length: 1
	2	address1	String (120)	No	Max Length: 120 Min Length: 3
	3	address2	String (120)	No	Max Length: 120 Min Length: 3
	4	address3	String (120)	No	Max Length: 120



API User Guide
Version 1.0

					Min Length: 3
	5	citycode	String (5)	No	Max Length: 5 Min Length: 3
	6	cityname	String (50)	No	Max Length: 50 Min Length: 3
	7	mobile	Number (11)	No	Like (0300xxxxxxx) Max Length: 11 Min Length: 11
	Shipment Info				
	1	costcentercode	String (20)	Yes	Max Length: 20 Min Length: 2
	2	referenceno	String (50)	No	Max Length: 50 Min Length: 3
	3	contentdesc	String (50)	No	Max Length: 999 Min Length: 3
	4	servicecode	String (6)	Yes	Max Length: 6 Min Length: 1
	5	parametertype	String (50)	No	Max Length: 50 Min Length: 1
	6	shipmentdate	String (20)	No	DD-MM-YYYY Max Length: 20 Min Length: 1
	7	shippingtype	String	No	Maximum: 10 Minimum: 0
	8	currency	String (5)	Yes	PKR, USD and so on Max Length: 5 Min Length: 3
	9	codamount	Number (int32)	Yes	maximum: 250000 minimum: 0



API User Guide
Version 1.0

	10	declaredvalue	Number (int32)	No	maximum: 250000 minimum: 0
	11	insuredvalue	Number (int32)	No	maximum: 250000 minimum: 0
	12	transactiontype	String	No	Maximum: 10 Minimum: 0
	13	dsflag	String (50)	No	Max Length: 50 Min Length: 0
	14	carrierslug	String (50)	No	Max Length: 50 Min Length: 0
	15	weightinkg	Number (double)	Yes	Minimum weight is 0.5
	16	pieces	Number (int32)	Yes	maximum: 2147483647 minimum: 1
	17	remarks	String (500)	No	Max Length: 500 Min Length: 3
	18	fragile	Boolean	Yes	Value should be true or false
	SKU				
	1	description	String (50)	No	Max Length: 200 Min Length: 3
	2	quantity	Number(int32)	Yes	Quantity should be greater than or equals to 1.
	3	weight	Number(double)	Yes	Minimum weight is 0.5
	4	uom	String	No	
	5	unitprice	Number(int32)	Yes	maximum: 250000 minimum: 1
	6	declaredvalue	Number(int32)	No	maximum: 250000 minimum: 0
	7	insuredvalue	Number(int32)	No	maximum: 250000 minimum: 0
	Response Parameters				



S. No.	Response	Remarks
1	Consignment #	To be provided by TCS
2	Response Code	Response code based on provided information
3	Status	True or False
4	Message	API response
5	Request Time	
6	Response Time	

JSON Body Request/Payload	
	<pre> { "accesstoken": "", "consignmentno": "", "shipperinfo": { "tcsaccount": "04011K1", "shippername": "Test", "address1": "Test address 1", "address2": "Test address 2", "address3": "Test address 3", "zip": "75800", "countrycode": "PK", "countryname": "Pakistan", "citycode": "KHI", "cityname": "Karachi", "mobile": "03451234567" }, "consigneeinfo": { "consigneeinfo": { "consigneeinfo": { "consigneecode": "C103", "firstname": "First name", "middlename": "Middle name", "lastname": "Last name", "address1": "Test address 1", "address2": "Test address 2", "address3": "Test address 3", "zip": "75800", "countrycode": "PK", "countryname": "Pakistan", "citycode": "KHI", "cityname": "Karachi", "email": "test@test.com", "areacode": "KHI00001", "areaname": "Gulshan", "blockcode": "", "blockname": "Gulshan block 6 PECHS", "lat": "24.920733", "lng": "67.088162", "landmark": "Baloch Hospital", } } } } </pre>



	<pre> "mobile": "03451234567" }, "vendorinfo": { "name": "Test Vendor", "address1": "Test address 1", "address2": "Test address 2", "address3": "Test address 3", "citycode": "KHI", "cityname": "Karachi", "mobile": "03451234567" }, "shipmentinfo": { "costcentercode": "Test-01", "referenceno": "123456789", "contentdesc": "Cost center description", "servicecode": "0", "parametertype": "Parameter Type", "shipmentdate": "28/08/2023 01:04:02", "shippingtype": "", "currency": "PKR", "codamount": 250, "declaredvalue": null, "insuredvalue": null, "transactiontype": "", "dsflag": "", "carrierslug": "", "weightinkg": 0.5, "pieces": 1, "fragile": false, "remarks": "Test remarks", "skus": [{ "description": "SKU description", "quantity": 1, "weight": 0.5, "uom": "KG", "unitprice": 250, "declaredvalue": null, "insuredvalue": null }] } } }</pre>
API Success Response	<pre>{ "response": "SUCCESS", "consignmentNo": "99210301520", "code": "200", "status": true, }</pre>



	<pre>"message": "success", "requestTime": "07:27:43", "responseTime": "07:27:44" }</pre>
Failure Response	<pre>{ "error": [{ "errorname": "error description" }], "message": "Summary of error", "traceid": "00-b5059f8935daf8f3d75e-3d58b17af9ab812-00" } OR { "code": 401, "message": "Invalid Bearer token. Mismatch configuration.", "status": "Unauthorized" }</pre>

Booking – Create Cost Center Code

API Name	Create Cost Center Code																																																																
Description	To generate and assign cost center codes for bookings.																																																																
Sandbox/Developer Link	https://devconnect.tcscourier.com/ecom/api/booking/createcostcentercode																																																																
Production Link	https://ociconnect.tcscourier.com/ecom/api/booking/createcostcentercode																																																																
API Method	POST																																																																
Bearer Token	Provided in Authorization API																																																																
API Body	<table><tr><th>S No.</th><th>Parameter</th><th>Mandatory</th><th>Data Type</th><th>Remarks</th></tr><tr><td>1</td><td>costcentercitname</td><td>Yes</td><td>String</td><td>To be provided by TCS</td></tr><tr><td>2</td><td>costcentercode</td><td>Yes</td><td>String</td><td></td></tr><tr><td>3</td><td>costcentername</td><td>Yes</td><td>String</td><td></td></tr><tr><td>4</td><td>pickupaddress</td><td>Yes</td><td>String</td><td></td></tr><tr><td>5</td><td>returnaddress</td><td>Yes</td><td>String</td><td></td></tr><tr><td>6</td><td>islabelprint</td><td>Yes</td><td>String</td><td></td></tr><tr><td>7</td><td>accountNumber</td><td>Yes</td><td>String</td><td></td></tr><tr><td>8</td><td>phoneNumber</td><td>No</td><td>String</td><td></td></tr><tr><td>9</td><td>email</td><td>No</td><td>String</td><td></td></tr><tr><td colspan="5">Response Parameters</td></tr><tr><td>1</td><td>accesstoken</td><td>String (400)</td><td>Yes</td><td></td></tr></table>					S No.	Parameter	Mandatory	Data Type	Remarks	1	costcentercitname	Yes	String	To be provided by TCS	2	costcentercode	Yes	String		3	costcentername	Yes	String		4	pickupaddress	Yes	String		5	returnaddress	Yes	String		6	islabelprint	Yes	String		7	accountNumber	Yes	String		8	phoneNumber	No	String		9	email	No	String		Response Parameters					1	accesstoken	String (400)	Yes	
	S No.	Parameter	Mandatory	Data Type	Remarks																																																												
	1	costcentercitname	Yes	String	To be provided by TCS																																																												
	2	costcentercode	Yes	String																																																													
	3	costcentername	Yes	String																																																													
	4	pickupaddress	Yes	String																																																													
	5	returnaddress	Yes	String																																																													
	6	islabelprint	Yes	String																																																													
	7	accountNumber	Yes	String																																																													
	8	phoneNumber	No	String																																																													
	9	email	No	String																																																													
	Response Parameters																																																																
	1	accesstoken	String (400)	Yes																																																													



JSON Body Request/Payload	<pre>{ "costcentercityname": "KARACHI", "costcentercode": "9211", "costcentername": "Kathryn Poole1", "pickupaddress": "KHI Airport", "returnaddress": "KHI Airport", "islabelprint": "yes", "accountNumber": "04011K1", "phoneNumber": "32122457457", "email": "test@abc.com", "accesstoken": "" }</pre>
API Success Response	<pre>{ "message": "SUCCESS", "costcentercode": "9211", "traceid": "49a5e1e7-2f47-430e-9443-8227acba134c" }</pre>
Failure Response	<pre>{ "message": "FAILURE: Cost Center Already Exists", "costcentercode": null, "traceid": "0b131f86-ee51-4a11-abdc-4266e08b65ab" }</pre>

Booking – Cancel

API Name	Cancel Booking																								
Description	To cancel an existing booking in TCS system																								
Sandbox/Developer Link	https://devconnect.tcscourier.com/ecom/api/booking/cancel																								
Production Link	https://ociconnect.tcscourier.com/ecom/api/booking/cancel																								
API Method	POST																								
Bearer Token	Provided in Authorization API																								
API Body	<table><tr><th>S No.</th><th>Parameter</th><th>Mandatory</th><th>Data Type</th><th>Remarks</th></tr><tr><td>1</td><td>ConsignmentNumber</td><td>Yes</td><td>Number</td><td>To be provided by Customer</td></tr><tr><td colspan="5">Response Parameters</td></tr><tr><td>1</td><td>accesstoken</td><td>String (400)</td><td>Yes</td><td></td></tr></table>					S No.	Parameter	Mandatory	Data Type	Remarks	1	ConsignmentNumber	Yes	Number	To be provided by Customer	Response Parameters					1	accesstoken	String (400)	Yes	
	S No.	Parameter	Mandatory	Data Type	Remarks																				
	1	ConsignmentNumber	Yes	Number	To be provided by Customer																				
	Response Parameters																								
1	accesstoken	String (400)	Yes																						
JSON Body Request/Payload	{ "consignmentNumber": "173000008151", "accesstoken": "" }																								



API Success Response	<pre>{ "message": "SUCCESS", "traceid": "294d5e4f-913c-45a4-bf90-e00993157c0b" }</pre>
Failure Response	<pre>{ "message": "Failure: No Record Founds", "traceid": "e291bead-5a51-4669-87eb-6f65535da994" }</pre>

Booking – Payment Invoice

API Name	Payment Invoice																								
Description	To generate and retrieve payment invoices against bookings																								
Sandbox/Developer Link	https://devconnect.tcscourier.com/ecom/api/booking/paymentinvoice																								
Production Link	https://ociconnect.tcscourier.com/ecom/api/booking/paymentinvoice																								
API Method	GET																								
Bearer Token	Provided in Authorization API																								
API Body	<table><tr><th>S No.</th><th>Parameter</th><th>Mandatory</th><th>Data Type</th><th>Remarks</th></tr><tr><td>1</td><td>Invoiceno</td><td>Yes</td><td>Number</td><td>To be provided by TCS</td></tr><tr><td colspan="5">Response Parameters</td></tr><tr><td>1</td><td>accesstoken</td><td>String (400)</td><td>Yes</td><td></td></tr></table>					S No.	Parameter	Mandatory	Data Type	Remarks	1	Invoiceno	Yes	Number	To be provided by TCS	Response Parameters					1	accesstoken	String (400)	Yes	
	S No.	Parameter	Mandatory	Data Type	Remarks																				
	1	Invoiceno	Yes	Number	To be provided by TCS																				
	Response Parameters																								
1	accesstoken	String (400)	Yes																						
JSON Body Request/Payload	{ " invoiceno ": "543777", " accesstoken ": "" }																								
API Success Response	{ "message": "SUCCESS", "traceid": "94a05367-5a0d-44e1-8dd1-d2ba01b344cd", "data": [{ "cnsg_no": "779412314605", "cust_ref": "Internet 570372", "bkg_dat": "2024-08-07T00:00:00", "consignee": "Muhib Ali", "orgn": "LHE", "dstn": "HSL", "wtt_bkg": 2, "paymentperiod": "08 Aug to 14 Aug 2024", "status": "Return To Origin", }] }																								



	<pre>"codamount": 2057, "courier_charges": 116, "gst": 18.56, "cus_no": "882161", "invoice": "LHEGEW888257" }, { "cmsg_no": "779412315161", "cust_ref": "Internet 571197", "bkg_dat": "2024-08-07T00:00:00", "consignee": "Khalid Bashir", "orgn": "LHE", "dstn": "LHE", "wtt_bkg": 0.5, "paymentperiod": "08_Aug_to_14_Aug_2024", "status": "Delivered", "codamount": 0, "courier_charges": 83, "gst": 13.28, "cus_no": "882161", "invoice": "LHEGEW888257" }, { "cmsg_no": "779412315162", "cust_ref": "Internet 571299", "bkg_dat": "2024-08-07T00:00:00", "consignee": "Marism Shahid", "orgn": "LHE", "dstn": "LHE", "wtt_bkg": 1, "paymentperiod": "08_Aug_to_14_Aug_2024", "status": "Delivered", "codamount": 2559, "courier_charges": 83, "gst": 13.28, "cus_no": "882161", "invoice": "LHEGEW888257" }]</pre>
Failure Response	<pre>{ "code": "Unauthorized", "message": "Invalid access token", "status": 401 }</pre>



Booking – Reverse

API Name	Reverse																														
Description	To book a reverse pickup for your shipments.																														
Sandbox/Developer Link	https://devconnect.tcscourier.com/ecom/api/booking/reverse																														
Production Link	https://ociconnect.tcscourier.com/ecom/api/booking/reverse																														
API Method	POST																														
Bearer Token	Provided in Authorization API																														
API Body	<table><tr><th>S No.</th><th>Parameter</th><th>Mandatory</th><th>Data Type</th><th>Remarks</th></tr><tr><td>1</td><td>costcentercode</td><td>No</td><td>String</td><td>To be provided by Customer</td></tr><tr><td>2</td><td>consignmentno</td><td>Yes</td><td>String</td><td>To be provided by Customer</td></tr><tr><td>3</td><td>consigneemobileno</td><td>No</td><td>String</td><td>-</td></tr><tr><td colspan="5">Response Parameters</td></tr><tr><td>1</td><td>accesstoken</td><td>Yes</td><td>String</td><td></td></tr></table>	S No.	Parameter	Mandatory	Data Type	Remarks	1	costcentercode	No	String	To be provided by Customer	2	consignmentno	Yes	String	To be provided by Customer	3	consigneemobileno	No	String	-	Response Parameters					1	accesstoken	Yes	String	
S No.	Parameter	Mandatory	Data Type	Remarks																											
1	costcentercode	No	String	To be provided by Customer																											
2	consignmentno	Yes	String	To be provided by Customer																											
3	consigneemobileno	No	String	-																											
Response Parameters																															
1	accesstoken	Yes	String																												
JSON Body Request/Payload	<pre>{ "costcentercode": "", "consignmentno": "99555303992", "consigneemobno": "", "accesstoken": "" }</pre>																														
API Success Response	<pre>{ "message": "SUCCESS", "status": "true", "accesstoken": "4563d2ejhfberbfkejfbkejrfb322dhdjdjjdf2532ggfjffj325djffj6" }</pre>																														
Failure Response	<pre>{ "code": 401, "message": "Invalid Bearer token. Mismatch configuration. " "status": "Unauthorized" }</pre>																														



Booking – Get CN Update

API Name	Get CN Update																													
Description	To retrieves the latest update on the status of a consignment note (CN) based on the provided CN Number.																													
Sandbox/Developer Link	https://devconnect.tcscourier.com/ecom/api/booking/getcnupdate																													
Production Link	https://ociconnect.tcscourier.com/ecom/api/booking/getcnupdate																													
API Method	GET																													
Bearer Token	Provided in Authorization API																													
API Body	<table><tr><th>S No.</th><th>Parameter</th><th>Mandatory</th><th>Data Type</th><th>Remarks</th></tr><tr><td>1</td><td>ID</td><td>Yes</td><td>String</td><td>To be provided</td></tr><tr><td>2</td><td>Flag</td><td>Yes</td><td>Number</td><td>To be provided</td></tr><tr><td colspan="5">Response Parameters</td></tr><tr><td>1</td><td>accesstoken</td><td>Yes</td><td>String (400)</td><td></td></tr></table>					S No.	Parameter	Mandatory	Data Type	Remarks	1	ID	Yes	String	To be provided	2	Flag	Yes	Number	To be provided	Response Parameters					1	accesstoken	Yes	String (400)	
	S No.	Parameter	Mandatory	Data Type	Remarks																									
	1	ID	Yes	String	To be provided																									
	2	Flag	Yes	Number	To be provided																									
	Response Parameters																													
1	accesstoken	Yes	String (400)																											
JSON Body Request/Payload	{ "ID": "779416038409", "flag": "2" }																													
API Success Response	{ "MESSAGE": "MSG01- CN 779416038409 Succesfully Updated ", "status": "true", "traceid": "2ac10ba8-5679-4bb2-8a9a-407e37ea7647" }																													
Failure Response	{ "MESSAGE": "ERR01-No Data Found against 779416038410", "status": "true", "traceid": "5354d4d5-4800-4ae8-a9b1-070daae8c7f8" }																													

CN Print

API Name	CN print
Description	To facilitate all your CN printing needs efficiently and effectively.
Sandbox/Developer Link	https://devconnect.tcscourier.com/ecom/api/print/label
Production Link	https://ociconnect.tcscourier.com/ecom/api/print/label
API Method	GET
Bearer Token	Provided in Authorization API



API User Guide Version 1.0

API Body	S No.					Parameter	Mandatory	Data Type	Remarks
	1	consignmentno	Yes	String	To be provided				
	2	shipperdetail	Yes	Dropdown	To be provided				
	Response Parameters								
	1	accesstoken	Yes	String (400)					
JSON Body Request/Payload	{ "consignmentno": "99555303992", "shipperdetail": "true", "accesstoken": "" }								
API Success Response	A PDF file will be available for downloading as per below sample:  779412322995.pdf								
Failure Response	{ "message": "CN not found", "url": "", "traceid": "6e621297-3881-40c1-b611-d03717827690" }								

Inquiry – Cost Center Inquiry

API Name	Cost Center Inquiry
Description	To fetch cost center details against customer account Number
Production Link	https://devconnect.tcscourier.com/ecom/inquiry/costcenterinquiry
Sandbox/Developer Link	https://ociconnect.tcscourier.com/ecom/inquiry/costcenterinquiry
API Method	GET
Bearer Token	Provided in Authorization API



API User Guide Version 1.0

API Body	S.No.	Parameter	Data Type	Mandatory	Remarks
	1	accesstoken	String (400)	Yes	Generated through provided Envio credentials
	2	customerno	Number (20)	Yes	TCS account Number
	Response Parameters				
	1	costcentercode	Number (20)	Yes	
	2	costcentercity	String (30)	Yes	
	3	costcentername	String (50)	Yes	
	4	phoneno	Number (11)	No	
	5	email	String (50)	No	
	6	pickupaddress	String (120)	Yes	
	7	returnaddress	String (120)	Yes	
	8	printonlabel	String (1)	Yes	Yes -> Y No -> N
JSON Body Request/Payload	<pre>{ "accessToken": "eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9eyJjbGlnbnRpZCI6IjI1NTYxMDgxNyIsInNlcnZpY2VzIjoimZcwLDM3MSIsIm", "customerno": "217698" }</pre>				
API Success Response	<pre>{ "detail": [{ "costcentercode": "001 - LHR", "costcentercity": "LAHORE", "costcentername": "Dubuy LHR", "phoneno": "03447274889", "email": "info@dubuypk.com", "pickupaddress": " AGRICS TOWN RAIWIND ROAD LAHORE ,", "returnaddress": " AGRICS TOWN RAIWIND ROAD LAHORE ,", "printonlabel": "Y" }, { "costcentercode": "002 - KHI", "costcentercity": "LAHORE", "costcentername": "Dubuy KHI", "phoneno": "03447274889", "email": "info@dubuypk.com", "pickupaddress": " AGRICS TOWN RAIWIND ROAD LAHORE ,", "returnaddress": " AGRICS TOWN RAIWIND ROAD LAHORE ,", "printonlabel": "Y" }] }</pre>				



	<pre>"phoneno": "03112313616", "email": "info@dubuy.pk.com", "pickupaddress": "Lasbella Garden Karachi", "returnaddress": "Lasbella Garden Karachi", "printonlabel": "Y" }, { "costcentercode": "003 - GUJ", "costcentercity": "LAHORE", "costcentername": "Sharif Fabrics Gujranwala", "phoneno": "03237466222", "email": "info@dubuy.pk.com", "pickupaddress": "M sharif 276 A model town back side of Jinnah hospital band Gali Gujranwala", "returnaddress": "M sharif 276 A model town back side of Jinnah hospital band Gali Gujranwala", "printonlabel": "Y" }], "message": "success", "traceid": "15f62e2d-bccf-44ae-9928-63996b4bcc22" }</pre>
Failure Response	<pre>{ "code": "Unauthorized", "message": "Invalid access token", "status": 401 }</pre>

Payment – Status

API Name	Payment Status																			
Description	To retrieve the current status of a payment transaction.																			
Sandbox/Developer Link	https://devconnect.tcscourier.com/ecom/api/Payment/status																			
Production Link	https://ociconnect.tcscourier.com/ecom/api/Payment/status																			
API Method	GET																			
Bearer Token	Provided in Authorization API																			
API Body																				
	<table><tr><th>S No.</th><th>Parameter</th><th>Mandatory</th><th>Data Type</th><th>Remarks</th></tr><tr><td>1</td><td>customerno</td><td>Yes</td><td>Number</td><td>To be provided by Shipper</td></tr><tr><td>2</td><td>consignmentno</td><td>Yes</td><td>Number</td><td>To be provided by Shipper</td></tr></table>					S No.	Parameter	Mandatory	Data Type	Remarks	1	customerno	Yes	Number	To be provided by Shipper	2	consignmentno	Yes	Number	To be provided by Shipper
	S No.	Parameter	Mandatory	Data Type	Remarks															
1	customerno	Yes	Number	To be provided by Shipper																
2	consignmentno	Yes	Number	To be provided by Shipper																
JSON Body Request/Payload	{ "customerno": "1234" "consignmentno": "779412323079" }																			



API Success Response	<pre>{ "detail": [{ "booking date": "09/09/2024", "cn by courier": "779412323079", "cn status": "RO", "order no": "Internet 591139", "payment status": "N", "amount paid": 0, "parcel weight": 0.5, "city": "TMK", "delivery charges": 116, "delivery date": "16/09/2024", "payment date": null }], "message": "SUCCESS", "status": "true", "traceid": "7cc65dfc-8b8b-4186-9259-aae6ba9f7d66" }</pre>
Failure Response	<pre>{ "detail": null, "message": "Invalid CN", "status": "true", "traceid": "3a52a19c-84cc-4416-b7f9-b05d38051eb4" }</pre>

Payment – Detail

API Name	Payment Detail				
Description	To retrieve detailed information about a specific payment transaction.				
Sandbox/Developer Link	https://devconnect.tcscourier.com/ecom/api/Payment/detail				
Production Link	https://ociconnect.tcscourier.com/ecom/api/Payment/detail				
API Method	GET				
Bearer Token	Provided in Authorization API				
API Body	S. No.	Parameter	Mandatory	Data Type	Remarks
	1	accesstoken	Yes	String (400)	To be provided by Customer
	2	customerno	Yes	Number	To be provided by Customer
	3	fromdate	Yes	Number	-
	4	todate	Yes	Number	-



JSON Body Request/Payload	<pre>{ "accesstoken": "" "customerno": "123456" "fromdate": "2024-09-08" "todate": "2024-09-14" }</pre>
API Success Response	<pre>{ "detail": [{ "booking date": "09/09/2024", "cn by courier": "779412322995", "cn status": "OK", "order no": "Internet 591128", "payment status": "N", "amount paid": 0, "parcel weight": 1, "city": "KHI", "delivery charges": 118, "delivery date": "10/09/2024", "payment date": null }, { "booking date": "09/09/2024", "cn by courier": "779412323054", "cn status": "OK", "order no": "Internet 590823", "payment status": "N", "amount paid": 0, "parcel weight": 2, "city": "SLT", "delivery charges": 174, "delivery date": "13/09/2024", "payment date": null }, { "booking date": "09/09/2024", "cn by courier": "779412323079", "cn status": "RO", "order no": "Internet 591139", "payment status": "N", "amount paid": 0, "parcel weight": 0.5, "city": "TMK", "delivery charges": 116, "delivery date": "16/09/2024", "payment date": null }] }</pre>



	<pre>}], "message": "SUCCESS", "status": "true", "traceid": "7cc65dfc-8b8b-4186-9259-aae6ba9f7d66" }</pre>
Failure Response	<pre>{ "code": 401, "message": "Invalid Bearer token. Mismatch configuration.", "status": "Unauthorized" }</pre>

Setup – Area Code

API Name	Area code																			
Description	To retrieve area codes by area description																			
Sandbox/Developer Link	https://devconnect.tcscourier.com/ecom/api/setup/areacode																			
Production Link	https://ociconnect.tcscourier.com/ecom/api/setup/areacode																			
API Method	GET																			
Bearer Token	Provided in Authorization API																			
API Body	<table><tr><th>S No.</th><th>Parameter</th><th>Mandatory</th><th>Data Type</th><th>Remarks</th></tr><tr><td>1</td><td>citycode</td><td>No</td><td>String</td><td>To be provided by TCS</td></tr><tr><td>2</td><td>area</td><td>No</td><td>String</td><td>To be provided by TCS</td></tr></table>					S No.	Parameter	Mandatory	Data Type	Remarks	1	citycode	No	String	To be provided by TCS	2	area	No	String	To be provided by TCS
S No.	Parameter	Mandatory	Data Type	Remarks																
1	citycode	No	String	To be provided by TCS																
2	area	No	String	To be provided by TCS																
JSON Body Request/Payload	<pre>{ "citycode": "KHI", "area": "" }</pre>																			
API Success Response	<pre>{ "message": "SUCCESS", "count": "9", "data": [{ "srl": 1, "areaid": 163, "citycode": "HSL", "areacode": "R80302402", "areaname": "Jamalpur" }, { "srl": 2,</pre>																			


```
"areaaid": 164,  
"citycode": "JMP",  
"areacode": "R80302762",  
"areaname": "Jampur"  
},  
{  
  "srl": 3,  
  "areaaid": 165,  
  "citycode": "PEW",  
  "areacode": "RPK5773",  
  "areaname": "Jamrud - Khyber Agency"  
},  
{  
  "srl": 4,  
  "areaaid": 166,  
  "citycode": "JND",  
  "areacode": "R80302688",  
  "areaname": "Jand"  
},  
{  
  "srl": 5,  
  "areaaid": 167,  
  "citycode": "QML",  
  "areacode": "R80302947",  
  "areaname": "Jandala"  
},  
{  
  "srl": 6,  
  "areaaid": 168,  
  "citycode": "NRL",  
  "areacode": "R80302434",  
  "areaname": "Jassar"  
},  
{  
  "srl": 7,  
  "areaaid": 169,  
  "citycode": "NOW",  
  "areacode": "R80302362",  
  "areaname": "Jehangira"  
},  
{  
  "srl": 8,  
  "areaaid": 170,  
  "citycode": "HZD",  
  "areacode": "R80302556",  
  "areaname": "Jhairanwala"  
},
```



	<pre>{ "srl": 9, "areaid": 171, "citycode": "SGD", "areacode": "R80306616", "areaname": "Jhal Chakian" }, "traceid": "83351973-9924-4133-ab3-007ead38e62f" }</pre>
Failure Response	<pre>{ "code": 401, "message": "Invalid Bearer token. Mismatch configuration.", "status": "Unauthorized" }</pre>

Setup – Block Code

API Name	Block code															
Description	To retrieve block code by block description															
Sandbox/Developer Link	https://devconnect.tcscourier.com/ecom/api/setup/blockcode															
Production Link	https://ociconnect.tcscourier.com/ecom/api/setup/blockcode															
API Method	GET															
Bearer Token	Provided in Authorization API															
API Body	<table><tr><th>S No.</th><th>Parameter</th><th>Mandatory</th><th>Data Type</th><th>Remarks</th></tr><tr><td>1</td><td>area</td><td>Yes</td><td>String</td><td>To be provided by TCS</td></tr><tr><td>2</td><td>blockcode</td><td>No</td><td>String</td><td>To be provided by TCS</td></tr></table>	S No.	Parameter	Mandatory	Data Type	Remarks	1	area	Yes	String	To be provided by TCS	2	blockcode	No	String	To be provided by TCS
S No.	Parameter	Mandatory	Data Type	Remarks												
1	area	Yes	String	To be provided by TCS												
2	blockcode	No	String	To be provided by TCS												
JSON Body Request/Payload	<pre>{ "area": "R80306631", "blockcode": "" }</pre>															
API Success Response	<pre>{ "message": "SUCCESS", "count": "2", "data": [{ "srl": 1, "blockid": 19396, "citycode": "LHE", "areaid": 593,</pre>															



	<pre>"areacode": "R80306631", "blockcode": "R80306632", "blockname": "Abdul Karim Road" }, { "srl": 2, "blockid": 19397, "citycode": "LHE", "areaid": 593, "areacode": "R80306631", "blockcode": "R80306633", "blockname": "Shaheen Complex" }], "traceid": "ef12bf80-9cd9-46f1-a060-c3b73c4f011e" }</pre>
Failure Response	<pre>{ "code": 401, "message": "Invalid Bearer token. Mismatch configuration.", "status": "Unauthorized" }</pre>

Setup – Country List

API Name	Country list
Description	To retrieve a list of countries for setup using the Country List API.
Sandbox/Developer Link	https://devconnect.tcscourier.com/ecom/api/setup/countrylist
Production Link	https://ociconnect.tcscourier.com/ecom/api/setup/countrylist
API Method	GET
Bearer Token	Provided in Authorization API
API Body	This API runs without any input parameters
JSON Body Request/Payload	N/A
API Success Response	<pre>{ "message": "SUCCESS", "data": [{ "countrycode": "PK", "countryname": "PAKISTAN" }] }</pre>



	<pre> }, { "countrycode": "DXB", "countryname": "UAE" }], "traceid": "20aeb-72fc-4b21-92c8-8abc5eb163b9" }</pre>
Failure Response	<pre>{ "result": null, "status": false, "code": "401" }</pre>

Setup – City list by Country

API Name	City list by Country														
Description	To retrieve a list of cities for a specified country using the CityListByCountry API.														
Sandbox/Developer Link	https://devconnect.tcscourier.com/ecom/api/setup/citylistbycountry														
Production Link	https://ociconnect.tcscourier.com/ecom/api/setup/citylistbycountry														
API Method	GET														
Bearer Token	Provided in Authorization API														
API Body	<table><tr><th>S No.</th><th>Parameter</th><th>Mandatory</th><th>Data Type</th><th>Remarks</th></tr><tr><td>1</td><td>countrycode</td><td>Yes</td><td>String</td><td>To be provided by TCS</td></tr></table>					S No.	Parameter	Mandatory	Data Type	Remarks	1	countrycode	Yes	String	To be provided by TCS
S No.	Parameter	Mandatory	Data Type	Remarks											
1	countrycode	Yes	String	To be provided by TCS											
JSON Body Request/Payload	<pre>{ "countrycode": ["PK"] }</pre>														
API Success Response	<pre>{ "message": "SUCCESS", "data": [{ "citycode": "TAL", "cityname": "TALL" }, { "citycode": "TDJ", "cityname": "TANDO JAM" }, { </pre>														



	<pre> "citycode": "TOP", "cityname": "TOPI" }], "traceid": "e52914aa-1f71-4a0a-b899-b4edd7361b72" } }</pre>
Failure Response	<pre>{ "result": null, "status": false, "code": "401" }</pre>

Setup – Route List

API Name	Route list														
Description	To fetch or set up a list of routes for a specified system or module, The request can include various filtering or sorting parameters to customize the output based on the route list requirements.														
Sandbox/Developer Link	https://devconnect.tcscourier.com/ecom/api/setup/routelist/														
Production Link	https://ociconnect.tcscourier.com/ecom/api/setup/routelist/														
API Method	GET														
Bearer Token	Provided in Authorization API														
API Body	<table><tr><th>S No.</th><th>Parameter</th><th>Mandatory</th><th>Data Type</th><th>Remarks</th></tr><tr><td>1</td><td>countrycode</td><td>Yes</td><td>String</td><td>To be provided by Customer</td></tr></table>					S No.	Parameter	Mandatory	Data Type	Remarks	1	countrycode	Yes	String	To be provided by Customer
S No.	Parameter	Mandatory	Data Type	Remarks											
1	countrycode	Yes	String	To be provided by Customer											
JSON Body Request/Payload	<pre>{ "countrycode": "SKT", }</pre>														
API Success Response	<pre>{ "message": "SUCCESS", "data": [{ "stA_NO": "SKT", "routeE_CODE": "X24118", "routeE_TYPE": "COCO", "exP_NAME": "Khurrianwala Express Center", "address": "TCS Express Center Shop No. 707 Khilot No. 1029 Khrrianwals Shahkot", "contactT_NUMBER": "3169992870", "areA_NO": "FSD", }] }</pre>														



	<pre>"latitude": "31.496388", "longitude": "73.269244", "flaG_HAZIR": "N", "flaG_EC": "Y" }, { "stA_NO": "SKT", "route_CODE": "X24203", "route_TYPE": "Franchise", "exP_NAME": "Shahkot Express Center", "address": "TCS Express Center Opposite Govt. Elementary School No. 3 Nankana Road Shahkot ", "contact_NUMBER": "3169992870", "areA_NO": "FSD", "latitude": "31.575158", "longitude": "73.483265", "flaG_HAZIR": "N", "flaG_EC": "Y" }, { "stA_NO": "SKT", "route_CODE": "X24404", "route_TYPE": "Shop in Shop", "exP_NAME": "Adda Jhol ", "address": "TCS Express Center Bismillah Market Sheikhpura Faisalabad ", "contact_NUMBER": "3169992870", "areA_NO": "FSD", "latitude": "31.522127", "longitude": "73.371926", "flaG_HAZIR": "N", "flaG_EC": "Y" } }, "status": "true", "traceid": "21291a14-8232-4e5b-a24b-de90a0b13d0f" }</pre>
Failure Response	<pre>{ "code": 401, "Message": "Invalid.", "status": "Unauthorized" }</pre>



Setup – Delivery Status List

API Name	Delivery Status List
Description	To fetch available tracking status for orders
Production Link	https://devconnect.tcscourier.com/ecom/setup/deliverystatuslist
Sandbox/Developer Link	https://ociconnect.tcscourier.com/ecom/setup/deliverystatuslist
API Method	GET
Bearer Token	Provided in Authorization API
API Body	This API runs without any input parameters
JSON Body Request/Payload	N/A
API Success Response	<pre>{ "detail": [{ "statusCode": "DBC", "description": "Delay Beyond Our Control" }, { "statusCode": "DFC", "description": "Delay due to Flight Cancelled" }, { "statusCode": "DAE", "description": "Delay due To Airline Handling Error" }, { "statusCode": "DFM", "description": "Delay due To Force Majeure" }], "message": "SUCCESS", "traceid": "7c9dbc4b-5edb-457f-9343-7e89e422025c" }</pre>
Failure Response	<pre>{ "code": "Unauthorized", "message": "Invalid access token", "status": 401 }</pre>



Tracking

API Name	Tracking														
Descriptio	To efficiently monitor and manage tracking needs.														
Sandbox/Developer Link	https://devconnect.tcscourier.com/tracking/api/Tracking/GetDynamicTrackDetail														
Production Link	https://ociconnect.tcscourier.com/tracking/api/Tracking/GetDynamicTrackDetail														
API Method	GET														
Bearer Token	Provided in Authorization API														
API Body	<table><tr><th>S No.</th><th>Parameter</th><th>Mandatory</th><th>Data Type</th><th>Remarks</th></tr><tr><td>1</td><td>consignee</td><td>Yes</td><td>String</td><td>TCS CN Number</td></tr></table>					S No.	Parameter	Mandatory	Data Type	Remarks	1	consignee	Yes	String	TCS CN Number
S No.	Parameter	Mandatory	Data Type	Remarks											
1	consignee	Yes	String	TCS CN Number											
JSON Body Request/Payload	{ "consignee": ["779412326902"] }														
API Success Response	{ "shipmentinfo": [{ "consignmentno": "779412326902", "bookingdate": "Oct 14, 2024", "shipper": "Imrooz Haider", "consignee": "Imrooz Haider", "origin": "LAHORE", "origincountry": "PAK", "destination": "BAGH", "destinationcountry": "PAK", "referenceno": "NA" }], "deliveryinfo": [{ "consignmentno": "779412326902", "station": "BAGH", "datetime": "Thursday Oct 17, 2024 12:58", "recievedby": "IMROOZ", "status": "Delivered", "code": "OK", "allowshow": "Y" }, { "consignmentno": "779412326902", "station": "BAGH", "datetime": "Wednesday Oct 16, 2024 11:58", "recievedby": null, "status": "Awaiting Receiver Collection", }] }														



	<pre> "code": "SC", "allowshow": "Y" },], "checkpoints": [{ "consignmentno": "779412326902", "datetime": "Thursday Oct 17, 2024 12:58", "recievedby": "IMROOZ", "status": "Shipment Delivered" }, { "consignmentno": "779412326902", "datetime": "Thursday Oct 17, 2024 09:35", "recievedby": null, "status": "Out For Delivery" }, { "consignmentno": "779412326902", "datetime": "Wednesday Oct 16, 2024 10:52", "recievedby": "BAGH", "status": "Arrived at TCS Facility" }, { "consignmentno": "779412326902", "datetime": "Monday Oct 14, 2024 23:19", "recievedby": "LAHORE", "status": "Arrived at TCS Facility" }], "shipmentsummary": "Current Status: DELIVERED\nDelivered On: Thursday Oct 17, 2024 12:58\nSigned By: Imrooz", "message": "SUCCESS", "traceid": "111c95db-9d3b-4b6d-8509-6b116fd372a5" }</pre>
Failure Response	<pre>{ "shipmentinfo": null, "deliveryinfo": null, "checkpoints": null, "shipmentsummary": "No Data Found/Invalid CN", "message": "FAIL", "traceid": "8aded596-4811-408d-b4f7-7481d0602a75" }</pre>



Status Codes

Status Code	Description
200	OK
201	Created
400	Bad request
401	Authentication failure
403	Forbidden
404	Resource not found
405	Method Not Allowed
500	Internal Server Error
501	Not Implemented
503	Service Unavailable