

Running Two Tomcat Instances on Different Ports

This document explains how to run two separate Apache Tomcat instances on different ports on a Linux server.

1. Clone Existing Tomcat Installation

Create a second Tomcat instance by copying the existing directory:

```
cp -r /opt/tomcat8 /opt/tomcat2
```

2. Configure Ports for Second Tomcat

Edit the `server.xml` file:

```
vi /opt/tomcat2/conf/server.xml
```

Update the following ports to avoid conflict with Tomcat1:

Shutdown Port

```
<Server port="8006" shutdown="SHUTDOWN">
```

HTTP Connector Port

```
<Connector port="8081" protocol="HTTP/1.1"/>
```

AJP Connector Port

```
<Connector port="8010" protocol="AJP/1.3"/>
```

3. Set Permissions

Make scripts executable:

```
chmod +x /opt/tomcat2/bin/*.sh
```

4. Configure Environment Variables (Important)

Edit startup script:

```
vi /opt/tomcat2/bin/startup.sh
```

Add:

```
export CATALINA_HOME=/opt/tomcat2  
export CATALINA_BASE=/opt/tomcat2
```

(Optional but recommended)

Edit shutdown script:

```
vi /opt/tomcat2/bin/shutdown.sh
```

Add:

```
export CATALINA_HOME=/opt/tomcat2  
export CATALINA_BASE=/opt/tomcat2
```

5. Start & Stop Tomcat

Start Tomcat2

```
/opt/tomcat2/bin/startup.sh
```

Stop Tomcat2

```
/opt/tomcat2/bin/shutdown.sh
```

6. Troubleshooting (If Port 8081 Not Coming Up)

Check logs:

```
tail -50 /opt/tomcat2/logs/catalina.out
```

Check running ports:

```
ss -tulnp | grep 8081  
ss -tulnp | grep java
```

Check specific PID:

```
ss -tulnp | grep <PID>
```

7. Common Issues

Issue: Tomcat not starting on port 8081

- Port already in use
- Wrong `CATALINA_BASE`
- Permission issues
- Logs not showing deployment errors

Fix Steps

- Verify port availability
- Ensure correct environment variables
- Restart service

8. Validation

After startup, verify:

```
ss -tulnp | grep 8081
```

Expected output should show Java process listening on port 8081.

End of Document