


# Day 14 : Securing Web API




# Authentication

- Is the process of determining the user's identity
- In ASP.NET Core, authentication is handled by *IAuthenticationService*
- Authentication Service uses registered handlers to complete authentication related actions such as
  - Authenticating the user
  - Responding when an unauthenticated user tries to access a restricted resource
- Registered Authentication handlers and their configuration options are called ***Schemes***

# Basic Authentication

- Simplest technique for enforcing access
- Built into HTTP Protocol
- Allows browsers or other agents to request access using credentials consisting of username and password
- Doesn't require cookies, session identifiers or login pages
- Authentication scheme checks the Authorization header in HTTP requests



# Implementing Basic Authentication

- Can be implemented using
  - Middleware
  - Attribute

```
public class BasicAuthAttribute : TypeFilterAttribute
{
    public BasicAuthAttribute(string realm = @"My Realm") : base(typeof(BasicAuthFilter))
    {
        Arguments = new object[] { realm };
    }
}
```

```
[BasicAuth] // You can optionally provide a specific realm --> [BasicAuth("my-realm")]
public IEnumerable<int> BasicAuth()
{
    _logger.LogInformation("basic auth");
    var rng = new Random();
    return Enumerable.Range(1, 10).Select(x => rng.Next(0, 100));
}
```


# Bearer Authentication

- Is an HTTP authentication scheme that involves security tokens called ***Bearer Tokens***
- Is also known as token authentication
- Bearer token is a cryptic string usually generated by the server in response to the login request
- Client must send this token in the authorization header in the format
  - Authorization: Bearer <token>


# JWT (JSON Web Token)

- Is an open standard, self defined and compact mechanism for securely transmitting information using JSON Object
- The information can be verified and trusted because its digitally signed
- Can be signed using a secret or a public-private key pair
- Usage Scenarios
  - Authorization
  - Information Exchange

# JWT Structure




# JWT Authentication Flow





# JWT Authentication Flow




# Debugging JWT Token using jwt.io


The image is a screenshot of the JWT.io website. At the top, there is a navigation bar with the JWT logo on the left, followed by links for 'Debugger', 'Libraries', 'Introduction', 'Ask', and 'Get a T-shirt!'. On the right side of the navigation bar, it says 'Crafted by' followed by the Auth0 logo and 'Auth0'. The main content area is split into two columns. The left column is titled 'Encoded' and has a sub-label 'PASTE A TOKEN HERE'. It contains a long string of characters representing an encoded JWT token. The right column is titled 'Decoded' and has a sub-label 'EDIT THE PAYLOAD AND SECRET'. It is divided into three sections: 'HEADER: ALGORITHM & TOKEN TYPE' showing a JSON object with 'typ' as 'JWT' and 'alg' as 'HS256'; 'PAYLOAD: DATA' showing a JSON object with various claims like 'iss', 'iat', 'exp', 'aud', 'sub', 'Email', and 'role'; and 'VERIFY SIGNATURE' showing the HMACSHA256 algorithm and a checkbox for 'secret base64 encoded'.

# Implementing JWT Auth in ASP.NET Core

```
services.AddAuthentication(x =>
{
    x.DefaultAuthenticateScheme = JwtBearerDefaults.AuthenticationScheme;
    x.DefaultChallengeScheme = JwtBearerDefaults.AuthenticationScheme;
})
.AddJwtBearer(x =>
{
    x.RequireHttpsMetadata = false;
    x.SaveToken = true;
    x.TokenValidationParameters = new TokenValidationParameters
    {
        ValidateIssuerSigningKey = true,
        IssuerSigningKey = new SymmetricSecurityKey(Encoding.ASCII.GetBytes(_configuration["Jwt:Key"])),
        ValidateIssuer = false,
        ValidateAudience = false,
    };
});
```



# Authorization




# Authorization in JWT

- Authorization based on Roles is supported out of the box
- As long as the bearer token contains elements for roles, the middleware infers from it and performs authorization checks
- Access to Controller or Action Methods can be restricted using [Authorize] attribute

```
[HttpGet]
[Authorize(Roles = "Read")]
0 references | Amal Dev, 4 days ago | 1 author, 1 change
public ActionResult<List<EmployeeEntity>> Get()
{
    return _empRepo.EmployeeList();
}


[HttpGet]
[Route("{id}")]
[Authorize(Roles = "Read,Exclusive")]
0 references | 0 changes | 0 authors, 0 changes
public ActionResult<EmployeeEntity> GetEmployee([FromRoute] int Id)
{
    return _empRepo.GetEmployeeDetails(Id);
}
```

# Custom Authorization Policies

- Custom Authorization is implemented through custom requirements and handlers
  - Building Blocks
    - Requirement
    - Requirement Handler
    - Pre-Configured Policy
- 


# Implement a requirement

```
public class MinimumExperienceRequirement : IAuthorizationRequirement
{
    public MinimumExperienceRequirement(int years)
    {
        ExpInYears = years;
    }
    protected int ExpInYears { get; set; }
}
```



# Adding a Policy Handler


```
public class MinimumExperienceHandler : AuthorizationHandler<MinimumExperience>
{
    protected override Task HandleRequirementAsync(AuthorizationContext context, MinimumExperience requirement)
    {
        if (!context.User.HasClaim(c => c.Type == ClaimTypes.YearsOfExp))
        {
            return Task.CompletedTask;
        }
        var expInYears = Convert.ToDateTime(context.User.FindFirst(c => c.Type == ClaimTypes.YearsOfExp).Value);
        if (expInYears >= 3)
        {
            context.Succeed(requirement);
        }
        return Task.CompletedTask;
    }
}
```






# Register Policy

```
public void ConfigureServices(IServiceCollection services)
{
    services.AddMvc();
    services.AddAuthorization(options =>
    {
        options.AddPolicy("CustomPolicy", policy =>
            policy.Requirements.Add(new MinimumExperience(10)));
    });
}
```



# Applying Policy

```
[Authorize(Policy="CustomPolicy")]  
public class SampleController : Controller  
{  
    //Write your code here...  
}
```



# Thanks for joining!

