



Day 9 : ASP.NET Core Web API – DI, Middleware, Routing



What is Dependency Injection(DI)

- Is a design pattern
- Allows the creation of dependent objects outside of a class and provides those objects to a class through different ways
- Involves three components



Dependency Injection(DI)

- ASP.NET Core is designed from scratch to support DI
- Come with a DI container out of the box
- Dependencies managed by the container are called ***Services***
- Two types of Services are there
 - Framework Services
 - Application Services

Configuring DI

- Install the framework NuGet package

Install-Package Microsoft.Extensions.DependencyInjection

- Register your dependencies in Startup.cs

```
public void ConfigureServices(IServiceCollection services)
{
    services.AddScoped<ISecurityService, SecurityService>();
    services.AddSingleton<ICachingService, CachingService>();
}
```

- Usage

```
private readonly ICachingService _cachingService;

public DefaultController(ICachingService cachingService)
{
    _cachingService = cachingService;
}
```

DI – Service Lifetimes

- DI Container allows you to control the lifetime of registered services
- Three types of lifetimes are available
 - Singleton – Creates only one instance
 - Transient - Creates an instance each time it is requested from the container
 - Scoped – Instances are created once per client request(HTTP Request)

DI – Accessing Service instance

```
public class Startup
{
    // ...code ...

    public void ConfigureServices(IServiceCollection services)
    {
        services.AddControllers();

        services.AddScoped<Interfaces.IOrderSender, HttpOrderSender>();
        services.AddScoped<Interfaces.IOrderManager, OrderManager>();
    }

    // ...code ...
}
```

Built-in DI Container - Limitations

- Features not supported
 - Property Injection
 - Injection based on name
 - Child Containers
 - Custom lifetime management
 - Convention-based registration

Built-in DI Container – Third Party Support

- Autofac
- Dryloc
- Grace
- LightInject
- Lamar
- Stashbox
- Unity

DI – Using Third Party Providers


```
public IServiceProvider ConfigureServices(IServiceCollection services)
{
    // Add framework services.
    // Configure third-party DI container
    // return container-specific IServiceProvider implementation
}
```

```
public class Startup {
    public IServiceProvider ConfigureServices(IServiceCollection services) {
        // setup the Autofac container
        var builder = new ContainerBuilder();
        builder.Populate(services);
        builder.RegisterType<ArticleService>().As<IArticleService>();
        var container = builder.Build();
        // return the IServiceProvider implementation
        return new AutofacServiceProvider(container);
    }
}
```


Middleware

- Is a piece of logic or code, that's assembled into an app pipeline to handle requests and responses.
- Each component:
 - Chooses whether to pass the request to the next component in the pipeline.
 - Can perform work before and after the next component in the pipeline.
- Each component in the request pipeline is responsible for invoking the next component in the pipeline or short-circuiting the pipeline
- When a middleware short-circuits, it's called a terminal middleware because it prevents further middleware from processing the request.


Middleware



Middleware – Execution Order



Middleware – Execution Order



Middleware - Configuration

```
public void Configure(IApplicationBuilder app, IWebHostEnvironment env)
{
    if (env.IsDevelopment())
    {
        app.UseDeveloperExceptionPage();
        app.UseDatabaseErrorPage();
    }
    else
    {
        app.UseExceptionHandler("/Error");
        app.UseHsts();
    }

    app.UseHttpsRedirection();
    app.UseStaticFiles();
    app.UseCookiePolicy();
    app.UseRouting();
    app.UseAuthentication();
    app.UseAuthorization();
    app.UseSession();

    app.UseEndpoints(endpoints =>
    {
        endpoints.MapRazorPages();
    });
}
```


Map, Run & Use methods

- `app.Use()`
 - used to allow the request delegate to pass the request to the next middleware in the pipeline.
- `app.Map()`
 - branch the request pipeline with the mentioned URL
- `app.Run()`
 - will be used to end the pipeline registrations and acts as a final step

Routing

- Routing is responsible for matching incoming HTTP requests to the endpoints
- Endpoints are application's unit of request handling code
 - Are defined in the app and configured when app starts
 - Matching process extracts values from the URL and provides it for the request processing
- Uses two middlewares, UseRouting & UseEndpoints
 - UseRouting – adds route matching to the middleware pipeline
 - UseEndpoints – adds the endpoint execution to the middleware pipeline

Routing - Flow




```
public void Configure(IApplicationBuilder app, IWebHostEn
{
    if (env.IsDevelopment())
    {
        app.UseDeveloperExceptionPage();
    }


    app.UseRouting();

    app.UseEndpoints(endpoints =>
    {
        endpoints.MapGet("/", async context =>
        {
            await context.Response.WriteAsync("Hello World");
        });
    });
}
```


Endpoints



- Before



- After



Thanks for joining!

