

F-SECURE LABS

<<<

NEWS FROM THE LAB - Monday, June 23, 2014

>>>

[ARCHIVES](#) | [SEARCH](#)

[Havex Hunts For ICS/SCADA Systems](#)

Posted by Daavid @ 14:46 GMT

During the past year, we've been keeping a close eye on the Havex malware family and the group behind it. Havex is known to be used in targeted attacks against different industry sectors, and it was [earlier reported](#) to have specific interest in the energy sector.

The main components of Havex are a general purpose Remote Access Trojan (RAT) and a server written in PHP. The name "Havex" is clearly visible in the server source code:

```
define("PATH_BLOCKFILE", "block.tmp");
define("PATH_LOGFILE", "testlog.php");
define("DATATAG_START", "<html><head><meta http-equiv='CACHE-CONTROL' "
    "content='NO-CACHE'></head><body>No data!<!--havex");
define("DATATAG_END", "havex--></body></head>");
define("NODATA", "<html><head><meta http-equiv='CACHE-CONTROL' "
    "content='NO-CACHE'></head><body>Sorry, no data corresponding your request."
    "<!--havexhavex--></body></html>");
define("ANSWERTAG_START", "<xdata d='%s' u='%s'>");
define("ANSWERTAG_END", "</xdata>\n");
define("FILE_OUTPUT_BLOCK_SIZE", 16384);
```

During the spring of 2014, we noticed that Havex took a specific interest in Industrial Control Systems (ICS) and the group behind it uses an innovative trojan horse approach to compromise victims. The attackers have trojanized software available for download from ICS/SCADA manufacturer websites in an attempt to infect the computers where the software is installed to.

We gathered and analyzed 88 variants of the Havex RAT used to gain access to, and harvest data from, networks and machines of interest. This analysis included investigation of 146 command and control (C&C) servers contacted by the variants, which in turn involved tracing around 1500 IP addresses in an attempt to identify victims.

The attackers use compromised websites, mainly blogs, as C&C servers. Here are some examples of command and control servers used:

```
abainternationaltoursandtravel.com
adultfriendgermany.com
africancranesafaris.com
alexvernigor.com
al-mashkoor.com
alpikaclub.com
antibioticsdrugstore.com
arsch-anus.com
artem.sataev.com
artsepid.com
ask.az
atampy.com
aziaone.com
```

We also identified an additional component used by the attackers that includes code to harvest data from infected machines used in ICS/SCADA systems. This indicates that the attackers are not just interested in compromising the networks of companies they are interested in, but are also motivated in having control of the ICS/SCADA systems in those organizations. The source of this motivation is unclear to us.

Trojanized Software as an Infection Vector

The Havex RAT is distributed at least through following channels:

- Spam email
- Exploit kits
- Trojanized installers planted on compromised vendor sites

The spam and exploit kit channels are fairly straightforward distribution mechanisms and we won't analyze them in more detail here.

Of more interest is the third channel, which could be considered a form of "watering-hole attack", as the attackers chose to compromise an intermediary target - the ICS vendor site - in order to gain access to the actual targets.

It appears the attackers abuse vulnerabilities in the software used to run the websites to break in and replace legitimate software installers available for download to customers.

Our research uncovered three software vendor sites that were compromised in this manner. The software installers available on the sites were trojanized to include the Havex RAT. We suspect more similar cases exist but have not been identified yet.

Based on the content of their websites, all three companies are involved in development of applications and appliances for use in industrial applications. These organizations are based in Germany, Switzerland and Belgium. Two of them are suppliers of remote management software for ICS systems and the third develops high-precision industrial cameras and related software.

As an example, we can see the partial results of dynamic analysis for one of the trojanized installers:

```
Created processes
C:\WINDOWS\system32\rundll32.exe C:\DOCUME~1\<USER>~1\LOCALS~1\Temp\mbcheck.dll,RunDllEntry (successful)
C:\DOCUME~1\<USER>~1\LOCALS~1\Temp\mbcheck.exe C:\DOCUME~1\<USER>~1\LOCALS~1\Temp\mbcheck.exe " (successful)
```

The normal, clean installer does not include a file called "mbcheck.dll". This file is actually the Havex malware. The trojanized software installer will drop and execute this file as a part of the normal installation. The user is left with a

working system, but the attacker now has a backdoor to access and control the computer.

Target Organizations

We were able to locate some of the infected systems and identify the organization affected by the samples analyzed in this report by tracing the IP addresses communicating to the C&C servers used by the Havex RAT.

All of these entities are associated in some way with the development or use of industrial applications or machines. The majority of the victims are located in Europe, though at the time of writing at least one company in California was also observed sending data to the C&C servers. Of the European-based organizations, two are major educational institutions in France that are known for technology-related research; two are German industrial application or machine producers; one is a French industrial machine producer; and one is a Russian construction company that appears to specialize in structural engineering.

ICS/SCADA Sniffer

Our analysis of Havex sample codes also uncovered its "ICS/SCADA sniffing" behavior. The C&C server will instruct infected computers to download and execute further components, and one of these components appeared very interesting. While analyzing this component, we noticed that it enumerates the local area network and looks for connected resources and servers:

```
scan_LAN      proc near                                ; CODE XREF: scan_LAN4+13E↓p
push         ebp
push         edi
mov         edi, [esi]
xor         ebp, ebp
push         ebp
push         offset asc_10030D58 ; "*****"
call        write_to_file2
mov         edi, [esi]
push         ebp ; int
push         offset aStartFinging_1 ; "Start finging of LAN hosts...\n"
call        write_to_file
add         esp, 10h
push         ebp ; lpNetResource
push         ebp ; int
mov         ecx, esi
call        recursive_WNetEnumResourceW
mov         edi, [esi]
test        al, al
jnz         short loc_10001427
push         ebp ; int
push         offset aFindingWasFaul ; "Finding was fault. Unexpective error\n"
call        write_to_file
```

We then noticed that it uses Microsoft Component Object Model (COM) interfaces (CoInitializeEx, CoCreateInstanceEx) to connect to specific services:

```

mov     eax, [esp+98h+var_78]
add     esp, 0Ch
push    edi                ; dwCoInit
push    edi                ; pvReserved
mov     [esp+94h+pServerInfo.pwszName], eax
mov     [esp+94h+pResults.pIID], offset gIOPCServerList2 ; {9dd0b56c-ad9e-43ee-8305-487f3188bf7a}
mov     [esp+94h+pResults.pItf], edi
mov     [esp+94h+pResults.hr], edi
call    ds:CoInitializeEx
lea     eax, [esp+8Ch+pResults]
push    eax                ; pResults
xor     ebx, ebx
inc     ebx
push    ebx                ; dwCount
lea     eax, [esp+94h+pServerInfo]
push    eax                ; pServerInfo
push    17h                ; dwClsCtx
push    edi                ; punkOuter
push    offset gIOPCServerList ; {13486D51-4821-11D2-A494-3CB306C10000}
mov     [esp+0A4h+var_4], edi
call    ds:CoCreateInstanceEx

```

To identify which services the sample is interested in, we can simply search for the identifiers seen above, which tell us what kind of interfaces are being used. A bit of googling gives us these names:

- **9DD0B56C-AD9E-43EE-8305-487F3188BF7A** = IID_IOPCServerList2
- **13486D51-4821-11D2-A494-3CB306C10000** = CLSID_OPCServerList

Note the mention of "OPCServer" in the names. There are more hints pointing in the same direction -- the strings found in the executable also make several references to "OPC":

Address	Length	Type	String
[S] .rdata:1003CD0	00000050	unic...	Programm was started at %02i:%02i:%02i\n
[S] .rdata:1003D20	00000006	unic...	a+
[S] .rdata:1003D28	0000002C	unic...	%02i:%02i:%02i.%04i:
[S] .rdata:1003D58	00000098	unic...	*****\n
[S] .rdata:1003DF0	0000003E	unic...	Start finging of LAN hosts...\n
[S] .rdata:1003E30	0000004C	unic...	Finding was fault. Unexpective error\n
[S] .rdata:1003E7C	00000038	unic...	Was found %i hosts in LAN:\n
[S] .rdata:1003EB4	00000028	unic...	Hosts was't found.\n
[S] .rdata:1003EDC	00000022	unic...	\t\t\t\t\t%02i) [%s]\n
[S] .rdata:1003F00	00000042	unic...	Start finging of OPC Servers...\n
[S] .rdata:1003F44	00000036	unic...	Was found %i OPC Servers.\n
[S] .rdata:1003F80	00000054	unic...	\t\t\t%02i) [%s\\%s]\n\t\t\t\t\tCLSID: %s\n
[S] .rdata:1003FD8	0000006E	unic...	\t\t\t\t\tUserType: %s\n\t\t\t\t\tVerIndProgID: %s\n
[S] .rdata:10031048	00000038	unic...	\t\t\t\t\tOPC version support: %s\n
[S] .rdata:10031080	00000054	unic...	OPC Servers not found. Programm finished\n

It turns out that OPC stands for [OLE for Process Control](#), and it's a standard way for Windows applications to interact with process control hardware. Using OPC, the malware component gathers any details about connected devices and sends them back to the C&C for the attackers to analyze. It appears that this component is used as a tool for intelligence gathering. So far, we have not seen any payloads that attempt to control the connected hardware.

Summary

The attackers behind Havex are conducting industrial espionage using a clever method. Trojanizing ICS/SCADA software installers is an effective method in gaining access to target systems, potentially even including critical infrastructure.

The method of using compromised servers as C&C's is typical for this group. The group doesn't always manage the C&C's in a professional manner, revealing lack of experience in operations. We managed to monitor infected computers connecting to the servers and identify victims from several industry sectors.

The additional payload used to gather details about ICS/SCADA hardware connected to infected devices shows the attackers have direct interest in controlling such environments. This is a pattern that is not commonly observed today.

SHA-1 hashes of the samples discussed:

```
7f249736efc0c31c44e96fb72c1efcc028857ac7  
1c90ecf995a70af8f1d15e9c355b075b4800b4de  
db8ed2922ba5f81a4d25edb7331ea8c0f0f349ae  
efe9462bfa3564fe031b5ff0f2e4f8db8ef22882
```

F-Secure detects this threat as **Backdoor:W32/Havex.A**.

Post by — [Daavid](#) and [Antti](#)