



SR. NO	01	02
TAG NO	STK - 401/402/403	STK - 405
TITLE	CONC.(85%) H3PO4 TANK	10% HCL TANK
TYPE	VERTICAL CYLINDRICAL WITH 15 DEG. CONICAL TOP & FLAT BOTTOM.	VERTICAL CYLINDRICAL WITH 15 DEG. CONICAL TOP & FLAT BOTTOM.
SIZE (MM)	1500 mm ID X 2500 mm VERTICAL SHELL HEIGHT	1700 mm ID X 2750 mm VERTICAL SHELL HEIGHT
CAPACITY	3.5 KL	5 KL
DENSITY (KG/M3)	1800	1060
PROCESS FLUID	85% H3PO4	10% HCL
DESIGN PRESSURE	(+500 mm WC	(+500 mm WC
OP.PRESSURE	ATM	ATM
HYDRAULIC TEST PRESSURE	FULL OF WATER	FULL OF WATER
DESIGN TEMP	100 DEG C	100 DEG C
OPERATING TEMP	30-60 DEG C	30-60 DEG C
M.O.C	FRP (SUPER VINYL ESTER - INDIAN)	FRP (SUPER VINYL ESTER - INDIAN)
GASKET	SOFT PTFE	SOFT PTFE
NUT BOLTS	IS 1367 CL 4.0 & 4.6 WITH CADMIUM PASSIVATED	IS 1367 CL 4.0 & 4.6 WITH CADMIUM PASSIVATED
THICKNESS		
SHELL	9 mm FRP at Bottom Reducing to 6 mm FRP at Top (With 1 .no stiffeners)	10 mm FRP at Bottom Reducing to 7 mm FRP at Top (With 1 .no stiffeners)
TOP	6 mm FRP (With stiffeners)	7 mm FRP (With stiffeners)
BOTTOM	14 mm FRP (CENTRE TO END REDUCING) (1:100 SLOPE BOTTOM)	16 mm FRP (CENTRE TO END REDUCING) (1:100 SLOPE BOTTOM)
DESIGN STANDARD	BS 4994 & GEP	BS 4994 & GEP
NOZZLES	AS PER YOUR SPECIFICATION DRG.SHEET	AS PER YOUR SPECIFICATION DRG.SHEET
FLANGE STD.	ANSI B 16.5 150#	ANSI B 16.5 150#
SUPPORT	NIL, SELF SUPPORTED (CLIENT TO PROVIDE RUBBER PADDING OR FINE SLURRY AT THE BOTTOM AT THE TIME OF INSTALLATION)	NIL, SELF SUPPORTED (CLIENT TO PROVIDE RUBBER PADDING OR FINE SLURRY AT THE BOTTOM AT THE TIME OF INSTALLATION)
ACCESSORIES	NAME PLATE LIFTING LUGS & HOLDOWN LUGS, 1 NOS EARTHING WITH GRAPHITE ROD	NAME PLATE LIFTING LUGS & HOLDOWN LUGS, LADDER & RAILING. (MS EPOXY PAINTED), 1 NOS EARTHING WITH GRAPHITE ROD
INTERNALS	GOOSE NECK.	GOOSE NECK & 80NB DIP PIPE
COMMISSIONING SPARES	200% (2 SETS) OF GASKET, 10% (MIN 4 Nos) OF BOLTS & NUTS FOR BLIND FLANGES & MANHOLES ONLY.	200% (2 SETS) OF GASKET, 10% (MIN 4 Nos) OF BOLTS & NUTS FOR BLIND FLANGES & MANHOLES ONLY.
EXCLUSION	COMMON PLATFORMS, LEVEL INDICATOR / LEVEL TRANSMITTER, LEVEL SWITCH, THERMOWELL, RUBBER PADDING AT BOTTOM, SUPPORT STURCURE, ANY TYPE OF INSULATION.	COMMON PLATFORMS, LEVEL INDICATOR / LEVEL TRANSMITTER, LEVEL SWITCH, THERMOWELL, RUBBER PADDING AT BOTTOM, SUPPORT STURCURE, ANY TYPE OF INSULATION.
UNIT RATE FOR EACH QTY (EX WORKS)	Rs. 2,79,500	Rs. 3,50,500
QTY (NOS)	3	1
TOTAL (EX WORKS)	Rs. 8,38,500	Rs. 3,50,500

NOTE :	EXTRA PRICE FOR MS STRUCTURE WILL BE RS 150/- PER KG.
	MATERIAL SUITABILITY TO BE CHECKED AT YOUR END.



03	04	05
STK - 406	STK - 101/201/202	STK - 403
ACIDIC CONDENSATE TANK	SPENT H3PO4 TANK	CONC.(85%) H3PO4 TANK
VERTICAL CYLINDRICAL WITH 15 DEG. CONICAL TOP & FLAT BOTTOM.	VERTICAL CYLINDRICAL WITH 15 DEG. CONICAL TOP & FLAT BOTTOM.	VERTICAL CYLINDRICAL WITH 15 DEG. CONICAL TOP & FLAT BOTTOM.
1700 mm ID X 2750 mm VERTICAL SHELL HEIGHT	2200 mm ID X 3750 mm VERTICAL SHELL HEIGHT	3000 mm ID X 5000 mm VERTICAL SHELL HEIGHT
5 KL	14 KL	30 KL
1100	1250	1800
ACIDIC CONDENSATE	SPENT H3PO4	85% H3PO4
(+)500 mm WC	(+)500 mm WC	(+)500 mm WC
ATM	ATM	ATM
FULL OF WATER	FULL OF WATER	FULL OF WATER
100 DEG C	100 DEG C	100 DEG C
30-60 DEG C	30-60 DEG C	30-60 DEG C
FRP (SUPER VINYL ESTER - INDIAN)	FRP (SUPER VINYL ESTER - INDIAN)	FRP (SUPER VINYL ESTER - INDIAN)
SOFT PTFE	SOFT PTFE	SOFT PTFE
IS 1367 CL 4.0 & 4.6 WITH CADMIUM PASSIVATED	IS 1367 CL 4.0 & 4.6 WITH CADMIUM PASSIVATED	IS 1367 CL 4.0 & 4.6 WITH CADMIUM PASSIVATED
10 mm FRP at Bottom Reducing to 7 mm FRP at Top (With 1 .no stiffeners)	11 mm FRP at Bottom Reducing to 8 mm FRP at Top (With 2 .no stiffeners)	21 mm FRP at Bottom Reducing to 18 mm FRP at Top (With 3.no stiffeners)
7 mm FRP (With stiffeners)	8 mm FRP (With stiffeners)	18 mm FRP (With stiffeners)
16 mm FRP (CENTRE TO END REDUCING) (1:100 SLOPE BOTTOM)	19 mm FRP (CENTRE TO END REDUCING) (1:100 SLOPE BOTTOM)	28 mm FRP (CENTRE TO END REDUCING) (1:100 SLOPE BOTTOM)
BS 4994 & GEP	BS 4994 & GEP	BS 4994 & GEP
AS PER YOUR SPECIFICATION DRG.SHEET	AS PER YOUR SPECIFICATION DRG.SHEET	AS PER YOUR SPECIFICATION DRG.SHEET
ANSI B 16.5 150#	ANSI B 16.5 150#	ANSI B 16.5 150#
NIL, SELF SUPPORTED (CLIENT TO PROVIDE RUBBER PADDING OR FINE SLURRY AT THE BOTTOM AT THE TIME OF INSTALLATION)	NIL, SELF SUPPORTED (CLIENT TO PROVIDE RUBBER PADDING OR FINE SLURRY AT THE BOTTOM AT THE TIME OF INSTALLATION)	NIL, SELF SUPPORTED (CLIENT TO PROVIDE RUBBER PADDING OR FINE SLURRY AT THE BOTTOM AT THE TIME OF INSTALLATION)
NAME PLATE LIFTING LUGS & HOLDOWN LUGS, LADDER & RAILING. (MS EPOXY PAINTED), 1 NOS EARTHING WITH GRAPHITE ROD	NAME PLATE LIFTING LUGS & HOLDOWN LUGS, LADDER & RAILING. (MS EPOXY PAINTED), 1 NOS EARTHING WITH GRAPHITE ROD	NAME PLATE LIFTING LUGS & HOLDOWN LUGS, LADDER & RAILING. (MS EPOXY PAINTED), 1 NOS EARTHING WITH GRAPHITE ROD
GOOSE NECK & 80NB DIP PIPE	GOOSE NECK & 80NB DIP PIPE	--
200% (2 SETS) OF GASKET, 10% (MIN 4 Nos) OF BOLTS & NUTS FOR BLIND FLANGES & MANHOLES ONLY.	200% (2 SETS) OF GASKET, 10% (MIN 4 Nos) OF BOLTS & NUTS FOR BLIND FLANGES & MANHOLES ONLY.	200% (2 SETS) OF GASKET, 10% (MIN 4 Nos) OF BOLTS & NUTS FOR BLIND FLANGES & MANHOLES ONLY.
COMMON PLATFORMS, LEVEL INDICATOR / LEVEL TRANSMITTER, LEVEL SWITCH, THERMOWELL, RUBBER PADDING AT BOTTOM, SUPPORT STURCURE, ANY TYPE OF INSULATION.	COMMON PLATFORMS, LEVEL INDICATOR / LEVEL TRANSMITTER, LEVEL SWITCH, THERMOWELL, RUBBER PADDING AT BOTTOM, SUPPORT STURCURE, ANY TYPE OF INSULATION.	COMMON PLATFORMS, LEVEL INDICATOR / LEVEL TRANSMITTER, LEVEL SWITCH, THERMOWELL, RUBBER PADDING AT BOTTOM, SUPPORT STURCURE, ANY TYPE OF INSULATION.
Rs. 3,42,000	Rs. 5,65,000	Rs. 16,74,000
1	3	1
Rs. 3,42,000	Rs. 16,95,000	Rs. 16,74,000

NOTE :	EXTRA PRICE FOR MS STRUCTURE WILL BE RS 150/- PER KG.
	MATERIAL SUITABILITY TO BE CHECKED AT YOUR END.