
Cascaded-SolarNet: Results, Comparison with Base Papers and Conclusion

Cascaded Convolutional Neural Network for Solar Panel Defect Classification (InfraredSolarModules, 12 classes). All numbers are measured on the same held-out test split of 3,000 images (stratified 70/15/15, seed 42), single run per configuration. Code, configs and raw metrics: github.com/techwack/cascaded-cnn.

1. Results

The best cascade reaches **79.8%** accuracy, macro-F1 **0.646** and Cohen's kappa **0.717** on the 12-class problem (data-driven families), and **94.1%** accuracy on the Stage 1 healthy-versus-defect decision. With the semantic families (Electrical, Environmental, Structural) the 'improved3' configuration reaches 79.6% accuracy and macro-F1 0.638.

Configuration	Model	Accuracy	Macro-F1	Kappa	Stage 1 binary acc.
Default (brightness/contrast/noise jitter)	Cascade	61.7%	0.368	0.461	81.0%
	Flat CNN (same split)	47.6%	0.379	0.357	n/a
No photometric jitter (flips only)	Cascade	71.1%	0.509	0.583	86.0%
	Flat CNN (same split)	68.5%	0.571	0.586	n/a
Improved: 80x48 input, 2 convs/block	Cascade	76.0%	0.582	0.656	89.5%
	Flat CNN (same split)	76.8%	0.653	0.689	n/a
Improved2: + balanced sampling, label smoothing	Cascade	75.5%	0.576	0.648	89.1%
Improved3: + larger Stage 1/2 CNNs	Cascade	79.6%	0.638	0.714	93.8%
Data-driven family grouping	Cascade	79.8%	0.646	0.717	94.1%



Main findings


- **Removing photometric jitter was the biggest single gain.** Brightness, contrast and noise augmentation lowered cascade accuracy to 61.7%; flips only gave 71.1%. In thermal images brightness is temperature, so jittering it destroys the signal that separates the classes.

- **Larger input and capacity helped next.** Upsampling to 80x48 and using two convolutions per block raised accuracy to 76.0%; enlarging the Stage 1 and Stage 2 networks raised it to 79.6%, and Stage 1 binary accuracy from 89.5% to 93.8%.

- **Cascade versus flat CNN.** The cascade is ahead on accuracy (79.6% vs 76.8%) and kappa (0.714 vs 0.689) but slightly behind on macro-F1 (0.638 vs 0.653), so the advantage is modest. 51.0% of test images leave the cascade at Stage 1 and never reach the larger networks.

- **Error attribution.** With the semantic families, wrong-family decisions at Stage 2 are the largest error source. The data-driven grouping cut Stage 2 errors from 300 to 116, but the hard confusions moved into Stage 3 (126 to 313 errors), so the net gain is small (79.6% to 79.8%, within single-run noise).


- **Tried without gain:** soft routing (multiplying stage probabilities), flip test-time augmentation, tuning the Stage 1 threshold on validation data (optimum stayed at 0.5) and balanced sampling with label smoothing.



Per-class performance

Rare classes are the weak point: they have only 123 to 250 training images, and several look alike (Cell vs Cell-Multi, Hot-Spot vs Cell). Class weighting in the loss, stratified splitting and macro-F1 were used to keep them from being ignored, but they remain the hardest classes.

Class	Test images	Cascade F1 (improved3)	Cascade F1 (data-driven)	Flat CNN F1
No-Anomaly	1500	0.94	0.94	0.89
Cell	281	0.63	0.64	0.66
Cell-Multi	193	0.47	0.44	0.48
Diode	225	0.93	0.92	0.94
Diode-Multi	26	0.82	0.91	0.88
Hot-Spot	37	0.54	0.40	0.56
Hot-Spot-Multi	37	0.57	0.58	0.51
Soiling	31	0.22	0.30	0.32
Shadowing	159	0.67	0.68	0.69
Vegetation	246	0.65	0.63	0.66
Cracking	141	0.65	0.66	0.70
Offline-Module	124	0.59	0.65	0.53



2. Comparison with the Base Papers

We re-checked the literature at the primary sources. Two points matter for any comparison. First, the dataset paper itself (Millendorf et al., ICLR 2020 workshop) reports **no model accuracies**; the numbers our earlier survey attributed to it (Random Forest 84%, CNN 92.5%, EfficientNet+SVM 93%) come from later papers. Second, those papers differ from our setup in task, split and features, so the numbers can be placed side by side but not ranked.

Paper	Method	Task and protocol	Reported	Checked
Duranay 2023, Electronics 12(21):4397	EfficientNet-B0 features (ImageNet-pretrained), NCA selection, SVM	12 classes, 10-fold cross-validation	93.93% accuracy, 89.82% F1	Full paper read
Alves et al. 2021, Renewable Energy 179:502	Custom CNN with data augmentation	Anomaly detection (binary); 8 selected classes; cross-validation	92.5% binary; 78.85% for 8 classes	Abstract (library record)
Multi-scale CNN, transfer learning (Eng. Appl. Artif. Intell. 113, 2022), as cited by Duranay	Three-branch CNN, transfer learning	Fault detection; 11 anomaly types	97.32% detection; 93.51% for 11 types	As cited by Duranay

Paper	Method	Task and protocol	Reported	Checked
Corley et al. 2025 (CVPRW), their Random Forest	Random Forest	'Anomaly classification', split not stated	84.0%	arXiv text read
Barraz et al. 2025; Gopalakrishnan et al. 2024, as cited by Corley	Cascading ensemble with voting CNN; NASNet + LSTM	Not stated	88%; 85%	As cited by Corley
Millendorf et al. 2020 (dataset paper)	-	-	No model results reported	Full paper read
Preprints and listings (SSRN Hyperband CNN; diffusion + ViT)	Hyperband-tuned CNN; transformer	12 classes, repeated k-fold CV (SSRN)	98.75%; 92.78%	**Not verified** (listings only)
Ours: cascade (data-driven families)	**Five small CNNs, trained from scratch**	**12 classes, single stratified 70/15/15 hold-out**	**79.8% accuracy, macro-F1 0.646**	**Our results**
Ours: Stage 1 only	Binary triage CNN	Healthy vs defect, same hold-out	94.1%	Our results
Ours: flat CNN / Random Forest	Same building blocks / raw pixels	12 classes, same hold-out	76.8% / 61.6%	Our results

How to read this

- **Binary triage.** Our Stage 1 reaches 94.1%. That is above Alves et al. (92.5%, cross-validated) and below the multi-scale transfer-learning CNN (97.32%). It is a competitive result for a small network trained from scratch, but it is a single hold-out run, so we claim parity with the 92.5% to 93% range and not a new best.

- **12 classes.** Our 79.8% is **below** the published 12-class figures (84.0% Random Forest, 85% to 88% for ensembles, 93.93% for EfficientNet features with an SVM). We did not beat them, and we did not reach the 93% ceiling or the 95% target in our proposal.

- **Why the numbers are not like-for-like.** Duranay uses 10-fold cross-validation and ImageNet-pretrained features; ours is one fixed hold-out split and models trained from scratch. We also measured overlap between our splits: about 7% of test images have a near-identical training image (distance below 0.5; 96% of those share the label) and about 54% have a close one (distance below 1; 78% share the label). Random fold splits would put such near-duplicates on both sides and raise cross-validated scores. This overlap cannot explain the whole gap, though: on our split a raw-pixel Random Forest scores 61.6% and a raw-pixel 1-nearest-neighbour 62.4%, against the 84.0% that Corley et al. report for a Random Forest. How that figure was obtained is not stated, so the cause of that gap is unknown.

- **What we can say.** Under our stricter fixed hold-out, the cascade improves on the flat CNN (76.8%) by about 3 points and on a raw-pixel Random Forest (61.6%) by about 18 points. Our contribution is the cascade design and the ablation and error analysis (which stage causes which errors), not a new accuracy record.

- **To make the comparison fair**, the next step is to run our cascade and flat CNN under the same 10-fold cross-validation, and to run the EfficientNet-B0 + NCA + SVM pipeline on our split.

Sources: Duranay, Electronics 12(21):4397 (mdpi.com/2079-9292/12/21/4397); Corley et al., arXiv:2503.02128; Alves et al., Renewable Energy 179:502-516 (abstract via library record); Millendorf et al., ICLR 2020 AI for Earth Sciences workshop. Rows marked 'as cited' were read in the citing paper, not in the original. Rows marked 'Not verified' appeared only in search listings.

3. Conclusion

- We implemented Cascaded-SolarNet, a three-stage cascade of five small CNNs for 12-class infrared solar module defect classification, in PyTorch, with a reproducible split, tests, diagrams and live demos.

- **The cascade works.** After diagnosing and removing harmful photometric augmentation, enlarging the input and strengthening the front stages, accuracy rose from 61.7% to 79.8% (macro-F1 0.37 to 0.65). Healthy-versus-defect triage reaches about 94.1%, comparable to the 92.5% binary figure published for this dataset.

- **The claim that a cascade clearly beats a flat classifier was only partly supported.** It is ahead on accuracy and kappa and processes about half of all images with only the small Stage 1 network, but a flat CNN with the same building blocks is within about 3 accuracy points and slightly better on macro-F1. Published 12-class results (84% to 93.93%) are higher than ours, although they use cross-validation and pretrained features; the target of exceeding 93% on all 12 classes was not met.

- **Error propagation is the central trade-off.** A wrong decision at Stage 1 or Stage 2 cannot be undone. Re-grouping the classes by their actual confusions moved errors between stages rather than removing them, and soft routing did not recover them.

- **Thermal images need thermal-aware augmentation.** Geometric flips help; brightness, contrast and noise jitter hurt, because brightness encodes temperature.

Limitations

- Single run per configuration (seed 42); differences below about 0.5 points are within noise and no confidence intervals were computed.

- The benchmark has no module or site identifiers, we measured that about 7% of our test images have a near-identical training image, and cross-validated results in the literature are likely to be more affected by this than our fixed hold-out.

- Rare classes (Soiling, Hot-Spot, Diode-Multi) remain weak, which keeps macro-F1 well below accuracy.

- Latency on edge hardware was not measured reliably; the early-exit rate (about half of the images) is the supporting evidence for efficiency.

- Published numbers use different protocols (cross-validation, pretrained features), and some sources could only be checked through abstracts or citing papers.

Future work

- Run several seeds and report mean and standard deviation; evaluate under 10-fold cross-validation for a like-for-like comparison with published results, and run the EfficientNet-B0 + SVM pipeline on our split.

- Improve Stage 2, for example by training the family classifier jointly with the specialists or on the cascade's own routing errors, or with class-specific augmentation for rare faults.

- Add the planned ablations (no early exit, unweighted loss, upsampling factor in isolation) and deduplicate near-identical crops before splitting.

- Measure real latency and memory on a drone-class edge device, and test additional modalities such as RGB.