

My eyes tend to light up when faced against filters though. A filter means the parameter we are testing is vulnerable to XSS, but the developer has created a filter to prevent any malicious HTML. This is one of the main reasons I also spend a lot of time looking for XSS when first starting on a new program because if they are filtering certain payloads, **it can give you a feel for the overall security of their site**. Remember, XSS is the easiest bug type to prevent against, so why are they creating a filter? And what else have they created filters around (think SSRF.. filtering just internal IP addresses? Perhaps they forgot about <http://169.254.169.254/latest/meta-data> - chances are, they did!).

Process for testing for XSS & filtering:

Step One: Testing different encoding and checking for any weird behaviour

Finding out what payloads are allowed on the parameter we are testing and how the website reflects/handles it. Can I input the most basic `<h2>`, ``, `<table>` without any filtering and it's reflected as HTML? Are they filtering malicious HTML? If it's reflected as `<` or `%3C` then I will test for double encoding `%253C` and `%26lt;` to see how it handles those types of encoding. Some interesting encodings to try can be found on <https://d3adend.org/xss/ghettoBypass>. This step is about finding out what's allowed and isn't & how they handle our payload. For example if `<script>` was reflected as `<script>`, but `%26lt;script%26gt;` was reflected as `<script>`, then I know I am onto a bypass and I can begin to understand how they are handling encodings (which will help me in later bugs maybe!). If not matter what you try you always see `<script>` or `%3Cscript%3E` then the parameter in question may not be vulnerable.