Status: Successfully connected to PostgreSQL via Prisma ORM transaction pooler.

BELTTRACK MARTIAL ARTS MANAGEMENT OS

Vercel Cloud Deployment - Environment Variables Configuration Audit

Vercel Scope: st8-buttah/belttrack | Production URL: https://belttrack.vercel.app | Audit: November 2026

DEPLOYMENT INFRASTRUCTURE & MULTI-ENVIRONMENT PARITY

BeltTrack is deployed on Vercel with a PostgreSQL database on Supabase and Nodemailer SMTP engine.

1. CORE APPLICATION & DATABASE VARIABLES

Variable Name			
`DATABASE_URL`	Secret	Production, Preview	Prisma ORM Transaction Pooler (:6543?pgbouncer=true) for runtime queries.
`DIRECT_URL`	Secret	Production, Preview	Prisma Session Pooler (:5432) for schema DDL and migrations.
`NEXT_PUBLIC_SUPABASE_URL`	Config	Production, Preview	Public project URL for browser client and server-side SSR client.
`NEXT_PUBLIC_SUPABASE_ANON_KEY`	Config	Production, Preview	Public anonymous JWT key for authenticating client-side Supabase requests.
`SUPABASE_SERVICE_ROLE_KEY`	Secret	Production, Preview	Elevated admin key for user provisioning and auth management (server-only).
`COOKIE_SECRET`	Secret	Production, Preview	HMAC-SHA256 signature secret for tamper-proof session cookies.

LIVE PRODUCTION DEPLOYMENT VERIFICATION: HTTP 200 OK

Live Verification Call: GET https://belttrack.vercel.app/api/schools/directory

2. TRANSACTIONAL EMAIL ENGINE (SMTP CONFIGURATION)

Powers 6-digit confirmation codes, owner tenant activations, and student absence alerts

Variable Name			
SMTP_HOST	smtp.gmail.com	**Prod, Preview**	Outbound Gmail mail submission gateway.
SMTP_PORT	587	**Prod, Preview**	Standard submission port for encrypted STARTTLS transport.
SMTP_SECURE	false	**Prod, Preview**	False for port 587 (opportunistic upgrade via STARTTLS).
SMTP_USER	temitayoodutola@gmail.com	**Prod, Preview**	Authenticated sender email identity.
SMTP_PASS	kkftacjbvqfvpdys	**Prod, Preview**	16-character dedicated Google App Password.
SMTP_FROM	BeltTrack Dojo <...>	**Prod, Preview**	From header rendered in user inbox client.

3. VERCEL STORAGE INTEGRATION ALIASES (SUPABASE MARKETPLACE)

The Supabase integration on Vercel automatically generates integration aliases in Production:

4. OPERATIONAL RUNBOOK: MANAGING VERCEL ENVIRONMENT VARIABLES

```
# 1. List all active variables and target environments:
npx vercel env ls --scope st8-buttah --project belttrack

# 2. Add or update a variable across Production and Preview (non-interactive):
npx vercel env add <NAME> --environment production,preview --value "<VALUE>" --project belttrack --scope st8-buttah --force --yes

# 3. Pull development variables to local workspace:
npx vercel env pull .env.local --scope st8-buttah --project belttrack
```

SECURITY INVARIANT: All production secrets are excluded from Git repository (.env.local, .env.* in .gitignore).