# Stability After Batch Correction: 1 PC vs 2 PCs

### Tecla Duran Fort

#### 2025-09-05

1

### Contents

Load Data

Correcting Only Batch Setup	2
Load Data	
df <- read.csv("//data/peak_table_var.csv")	
<pre># Peak table matrix (samples x peaks) X &lt;- as.matrix(df %&gt;% dplyr::select(starts_with("Cluster"))) stopifnot(nrow(X) == nrow(df))</pre>	
<pre># Batch encoding batch &lt;- df\$batch nbatch &lt;- length(unique(batch)) B &lt;- model matrix(~ 0 + factor(batch))</pre>	

# Correcting Only Batch

colnames(B) <- paste0("Batch\_", sort(unique(batch)))</pre>

### Setup

```
pc_scores <- pca_batch$x  # (samples x PCs) -> sample-space PCs
pc_axis <- axis_labels_from_pca(pca_batch)</pre>
```

#### Build 1-PC and 2-PC Batch Corrections

```
# 1 PC removal: project out PC1 from X
X_batch_1PC <- orthogonal_correction(X, pc_scores[,1])$corrected

# 2 PCs removal: sequentially remove PC1 then PC2
X_batch_2PC <- orthogonal_correction(orthogonal_correction(X, pc_scores[,1])$corrected, pc_scores[,2])$</pre>
```


#### Results

#### Stability (RSD) Before vs After


```
# RSD per peak (column-wise)
rsd_before <- apply(X,</pre>
                                    2, rsd_vec)
rsd_after_1 <- apply(X_batch_1PC, 2, rsd_vec)</pre>
rsd_after_2 <- apply(X_batch_2PC, 2, rsd_vec)</pre>
rsd_long <- tibble(</pre>
 peak = colnames(X),
 Original = rsd_before,
 `Batch-1PC` = rsd after 1,
 `Batch-2PC` = rsd_after_2
  pivot_longer(-peak, names_to = "State", values_to = "RSD") |>
  filter(!is.na(RSD))
rsd_long$State <- factor(rsd_long$State,</pre>
                          levels = c("Original", "Batch-1PC", "Batch-2PC"))
# Quick summary table
rsd_summary <- rsd_long |>
  group_by(State) |>
  summarize(
   n = n()
   median_RSD = median(RSD),
    mean_RSD = mean(RSD),
    pct_RSD_lt_20 = mean(RSD < 20)*100,
    .groups = "drop"
kable(rsd_summary, digits = 2, caption = "RSD summary by state") |>
  kable_styling(full_width = FALSE, position = "center")
```

Table 1: RSD summary by state


State	n	median_RSD	mean_RSD	pct_RSD_lt_20
Original	31	28.07	32.75	22.58
Batch-1PC	31	20.70	27.39	41.94
Batch-2PC	31	20.31	26.55	45.16




### Histograms





# Violin plots .



# PCA Colored by Batch







# Results Correcting Order (time) First

```
order_in_batch <- df %>%
  arrange(batch, elapsed_time) %>%
  group_by(batch) %>%
  mutate(order_in_batch = row_number()) %>%
  pull(order_in_batch)
# One-hot d'ordre
max_order <- max(order_in_batch)</pre>
0 <- model.matrix(~ 0 + factor(order_in_batch, levels = 1:max_order))</pre>
# Mitjanes per ordre i PCA per obtenir PC1 en espai de mostres
order_sizes <- as.vector(t(0) %*% rep(1, nrow(X)))</pre>
order_sums <- t(0) %*% X
            <- sweep(order_sums, 1, order_sizes, "/")</pre>
M_{order}
X_order_means <- 0 %*% M_order</pre>
pca_order <- prcomp(X_order_means, scale. = TRUE)</pre>
pc_order <- pca_order$x[, 1]</pre>
# Correcció per ordre
X_order_corr <- orthogonal_correction(X, pc_order)$corrected</pre>
# Batch PCs (sobre mitjanes de batch després de corregir temps)
B <- model.matrix(~ 0 + factor(batch))</pre>
batch_sizes <- as.vector(t(B) %*% rep(1, nrow(X)))</pre>
batch_sums <- t(B) %*% X_order_corr</pre>
```

```
M_batch <- sweep(batch_sums, 1, batch_sizes, "/")
X_batch_means <- B %*% M_batch
pca_batch <- prcomp(X_batch_means, scale. = TRUE)
pc_scores <- pca_batch$x

# Versions 1PC i 2PC
X_order_batch_1PC <- orthogonal_correction(X_order_corr, pc_scores[,1])$corrected
X_order_batch_2PC <- orthogonal_correction(
    orthogonal_correction(X_order_corr, pc_scores[,1])$corrected,
    pc_scores[,2])$corrected</pre>
```

Table 2: RSD summary (Original, After Order, Order+Batch-1PC, Order+Batch-2PC)

State	n	median_RSD	mean_RSD	pct_under_20
Original	31	28.07	32.75	22.58
After Order	31	23.64	26.14	38.71
Order+Batch-1PC	31	12.21	18.80	74.19
Order+Batch-2PC	31	11.34	17.66	74.19

