

Session 6 Report: Production Manual, Sustainability, and Life Cycle

Sofía Pons Carmona
Eduardo Cárdenas Herrera

5.1 Production Overview


The manufacturing execution framework for the **UNBROKEN Skate Wrap** is governed by a **hybrid industrialized-artisanal operational strategy**. This strategy bridges advanced, high-modulus protective textile engineering with traditional manual fabrication techniques. Transitioning directly from high-fidelity 3D digital visualization and cardboard volumetric prototyping, this manual establishes the standard operating procedures required to scale the design into low-to-medium volume mass production.



The primary production objective is twofold: ensuring structural compliance with international mechanical protection regulations while honoring the anti-establishment, DIY aesthetic values of the skateboarding subculture. By enforcing rigorous quality thresholds, the manufacturing line yields a specialized "legitimate tool" that avoids the clean, glossy signifiers of corporate luxury fashion. Instead, it delivers high-performance, street-ready utility that natively integrates into the skater's everyday urban routine.

5.2 Production Flow

The industrial scaling workflow maps out six highly specialized, sequential operational blocks designed to minimize material waste and optimize structural integrity:



- 1. Material Sourcing & Surface Modification:** Procurement of advanced protective textiles, followed by localized high-energy ultraviolet (UV) photochemical surface grafting to increase the interfacial bonding properties of chemically inert fibers like Ultra-High Molecular Weight Polyethylene (UHMWPE).
- 2. Primary Fabrication:** Precision automated die-cutting or laser cutting of textile sheets, followed by computerized lockstitch joining of the high-tensile outer shell boundaries and the inner soft-goods tool compartments.
- 3. Specialized Coating Application:** Target deployment of fluid barrier films onto internal compartments to isolate melting waxes and hydrocarbon oils from the rest of the chassis.
- 4. Artisanal Integration:** Hand-processing, manual bending, and structural split-weaving of raw rattan fitrit borders alongside local traditional textile components (such as Batik or Tenun sheets).
- 5. Final Assembly:** Structural synthesis and multi-layer lockstitch marriage of all independent panels into the centralized, flat 85 cm layout.
- 6. Quality Validation:** Empirically testing batch samples against rigorous mechanical stress parameters under international standards (EN388 and ISO 13997).



5.3 Assembly Sequence

To maintain dimensional stability and prevent alignment errors across the flexible textile layers, assembly technicians must strictly execute operations in the following sequence:

- **Step 1: Polymeric Barrier Lamination:** Liquid Polyurethane (PU) or eco-friendly Thermoplastic Polyurethane (TPU) matrices are applied directly to the interior faces of the denim/nylon tool pockets via a specialized knife-over-roll coating technique. This creates an absolute, continuous liquid barrier that guarantees fluid-tight isolation before any structural sewing occurs.
- **Step 2: Internal Organizer Tray Component Stitching:** Industrial computerized lockstitch machinery maps out and sews the texturized tool slots and heavy-gauge elastic retention loops onto the face of the internal tray canvas. This pre-assembly ensures that the metal tools will remain securely trapped under high kinetic vibration.
- **Step 3: Artisanal Frame Border Integration:** Master artisans manually treat, heat-bend, and split-weave raw rattan fitrit structural trims into the specialized exterior margins of the soft tray assembly. This provides structural silhouette memory and flexible framing without relying on rigid, unyielding plastics.
- **Step 4: Load-Bearing Strap Anchoring:** High-tensile, reinforced nylon webbing straps are aligned with maximum stress vectors on the main outer shell. They are anchored using dense, computerized machine bar-tack sewing patterns with bonded synthetic threads to withstand the weight of suspended boards.
- **Step 5: Final Multi-Layer Structural Marriage:** The sacrificial outer layer fabric (Aramid 1414 / UHMWPE) is placed facedown, aligned with the internal high-density closed-cell EVA or PU padding foam core (*busa*), and capped by the pre-assembled internal organizer tray. The stack is joined around its perimeter using a continuous heavy-duty structural lockstitch.
- **Step 6: Functional Hardware Installation:** High-impact Polyoxymethylene (POM / Acetal) side-release buckles and ladderlock tension sliders are threaded onto the terminal ends of the 64 cm transport webbing to finalize the wrap tightening mechanism.

5.4 Tools and Manufacturing Processes

- **Computerized Lockstitch Sewing Machines:** Heavy-duty programmable textile stitchers utilized for continuous, high-precision joining of high-denier synthetics and heavyweight denim.




- **Industrial Bar-Tack Stitching Machinery:** Specialized high-density automated stitching setups required to execute reinforcement grid blocks at maximum load-bearing tension anchors (such as webbing-to-shell bonds).



- **Polymer Knife-Over-Roll Coating Arrays:** Industrial machinery that controls a precision scraping blade to spread uniform, ultra-thin layers of liquid PU or TPU across woven sheets, creating reliable waterproof barriers.



- **Photochemical UV Irradiation Chambers:** High-energy ultraviolet light exposure setups used to alter the surface energy of chemically inert, ultra-slippery synthetic fibers like UHMWPE, drastically improving mechanical interlocking with backing adhesives.



- **Artisanal Manual Bending and Splitting Arrays:** Traditional hand-tools (steaming tubes, precision splitting blades) utilized to process raw rattan into low-profile, flexible framing boundaries.



- **Radio Frequency (RF) Dielectric Welding:** A candidate manufacturing process under evaluation for closing polymer seams without pierce-holes, optimizing fluid-tight containment cells (**requires compatibility testing**).



5.5 Quality Control Checklist

[] CRITERION 01: ABRASION RESISTANCE

- Standard: EN388 Level 4 Minimum (Mechanical Risk).
- Verification: Does the sacrificial outer shell withstand prolonged abrasive testing against standard 80-grit silicon carbide?

[] CRITERION 02: CUT & PIERCING PROTECTION

- Standard: ISO 13997 Level Certification.
- Verification: Does the integrated fiber matrix effectively prevent perforation from internal sharp screwdrivers or external skate truck metal corners?

[] CRITERION 03: CHEMICAL ISOLATION

- Standard: Absolute Fluid Containment.
- Verification: Are the laminated wax pockets 100% airtight, displaying zero organic solvent migration or grease weeping under high temperatures?

[] CRITERION 04: STRUCTURAL INTEGRITY

- Standard: Load-Bearing Stress Thresholds.
- Verification: Do the machine bar-tack webbing anchors withstand the calculated mechanical load of a heavy standard deck under high-speed commuting conditions? (*requires measurement*)

[] CRITERION 05: ERGONOMIC PROFILE

- Standard: Anthropometric Survey Limits.
- Verification: Are the final manufactured suspension straps cut and sewn to an exact finished length of 64 cm?

[] CRITERION 06: CMF PALETTE COMPLIANCE

- Standard: "Identity, Edge & Expression" Moodboard Guidelines.
- Verification: Are all visible textile surfaces finished with strictly Matte, Raw, and Rugged treatments, discarding all glossy or delicate consumer-fashion finishes?

5.6 Maintenance Instructions

To maximize product life within abusive, highly destructive urban environments, end-users must observe basic care guidelines:

- **Cleaning and Fabric Washing:** The high-performance outer textiles, internal denim canvas, and internal padding core are fully washable. Hand-washing with cold water and mild neutral detergents is highly recommended to protect the internal polymer coatings from cracking or delamination. Machine washing and high-heat tumble dryers must be avoided.
- **Hardware Integrity Callout:** Users must periodically inspect the POM side-release and ladderlock buckles for micro-fractures, stress whitening, or physical chips, especially after accidental impact drops onto urban concrete or asphalt.
- **Storage Optimization:** When not in active transport or workstation mode, the empty system should be folded into its ultra-compact shape and stored in a cool, dry environment. Prolonged storage in high-humidity zones or direct, continuous sunlight must be avoided to prevent the thermal oxidative degradation of synthetic webbing matrices and PU barrier films.



5.7 Repair and Replacement Strategy

To respect and foster the DIY subcultural values of the global skate community, the product architecture avoids built-in obsolescence by emphasizing visible repairability:

- **Replaceable Internal Tray:** The internal tool organizer tray is designed as a modular, field-replaceable sub-assembly. If specialized elastic tool loops experience tearing from tool friction, the modular tray panel can be removed and swapped out without compromising the outer protective shell.
- **Sacrificial Shell Philosophy:** The outer fiber matrix is engineered from its inception as a sacrificial layer. Surface micro-fraying and scratch accumulation are expected technical milestones under constant exposure to board lija, functioning as visible evidence of street-ready durability.

- **Open Source Potential:** If the sourcing of advanced technical textiles like Kevlar® or UHMWPE triggers severe cost escalation that limits market reach, the brand can deploy official sewing patterns, technical blueprints, and step-by-step material alternatives online as an open-source project. This empowers price-sensitive skaters to construct or patch their own wraps using scrap materials, strengthening community engagement.

5.8 Sustainability Strategy

- **Eco-Friendly Polymer Alternatives:** The design eliminates toxic, rigid PVC coatings containing hazardous phthalate plasticizers (such as DOP). Instead, it uses **Thermoplastic Polyurethane (TPU)** or **Ethylene-Vinyl Acetate (EVA)** films, ensuring highly effective fluid containment without toxic manufacturing byproducts.
- **Localized Sourcing and Carbon Reduction:** By incorporating regional natural fibers—such as raw rattan frames and vegetable-dyed traditional Batik or Tenun cotton weaves—the manufacturing plan reduces reliance on long-distance chemical shipping, decreases the total carbon footprint, and directly supports traditional artisanal workshops.
- **Upcycled Material Integrations:** The technical pipeline is currently investigating the integration of vulcanized waste rubber harvested from recycled automotive tires. These sheets could serve as extreme-wear corner patches, capitalizing on an abundant urban waste stream (**requires empirical evidence**).
- **Longevity as a Sustainable Weapon:** By shifting from standard low-cost materials to dense, cut-resistant fibers (EN388 compliance), the product's useful lifecycle is drastically extended. This curbs the rapid disposal-and-replacement cycles common with generic canvas backpacks.



5.9 Product Life Cycle

The product's life-cycle trajectory maps closely onto established trend sports equipment diffusion models:

- **Innovation & Refinement Phase (Current):** Engineering optimization of dual-function mechanics, finalizing material matrices, establishing industrial tolerances, and prototyping sample iterations.
- **Subcultural Expansion Phase (Near-Term):** Controlled market entry driven by grassroots word-of-mouth validation and active endorsements from respected local professional skaters (Max Barrera, Itzel Granados). This avoids broad commercial advertising to establish authenticity in local skate shops.
- **Market Maturity Phase (Long-Term):** Diffusion into the broader urban commuter market as a baseline, highly recognized action-sport accessory. Production processes normalize, scaling up manufacturing volumes through reliable OEM factory channels.
- **End-Of-Life Management (EOL):** Addressing long-term material breakdown. Synthetic polymers (nylon, PU matrices) will eventually go through natural thermal oxidative degradation and embrittlement. The brand's EOL framework aims to reclaim old shells to downcycle the dense fibers into industrial insulation or reinforcement fillings.

5.10 Basic Norms and References



- **EN388 (European Standard for Protective Gloves against Mechanical Risks):** Adopted to evaluate performance metrics for textile abrasion cycles, blade cut resistance, tear strength, and puncture vulnerability under rigorous friction.



- **EN420 (General Requirements for Protective Gear):** Governs fundamental product safety parameters, ergonomic freedom of movement, breathability factors, and material chemical safety.

- **ISO 13997 (Mechanical Properties - Determination of Resistance to Cutting by Sharp Objects):** Utilized to evaluate protective textile face response under intense perpendicular pressure from sharp edges, ensuring tools or hardware do not perforate structural zones.



- **ASTM F-1790 (Standard Test Method for Measuring Cut Resistance of Materials):** North American technical benchmark employed to cross-reference and verify automated blade-testing performance on high-modulus protective fabrics.

Digital Transformation Suggestions

To enhance accessibility for both manufacturers and users, this content can be converted into the following digital formats:

1. **GitHub Pages (Developer/DIY Focus):** Host the "Production Manual" as a repository. This allows the DIY community to access **sewing patterns**, technical blueprints, and material lists as an "open source" project.
2. **Expo Go App Prototype (User Experience):** Develop a mobile tool where users can access the **online configurator** to personalize their wrap (Batik/Tenun patterns) and view **maintenance/repair tutorials**.
3. **Digital Dossier (Business/Partner Focus):** A high-resolution PDF or interactive microsite for **OEM partners and investors**, focusing on the data-driven technical reports, regulatory compliance (EN388), and the **BOM table**.
4. **Brand Website (Consumer Focus):** A site featuring **rugged lifestyle photography** of the Skate Wrap in motion, endorsements from pro skaters, and a direct link to the configurator.