



COMP4161: Advanced Topics in Software Verification

HOL

June Andronick, Christine Rizkallah, Miki Tanaka, Johannes Åman Pohjola
T3/2019

data61.csiro.au



Content



- Intro & motivation, getting started [1]
- Foundations & Principles
 - Lambda Calculus, natural deduction [1,2]
 - Higher Order Logic, Isar (part 1) [3^a]
 - Term rewriting [4]
- Proof & Specification Techniques
 - Inductively defined sets, rule induction [5]
 - Datatypes, recursion, induction, Isar (part 2) [6, 7^b]
 - Hoare logic, proofs about programs, invariants [8]
 - C verification [9]
 - Practice, questions, exam prep [10^c]

^aa1 due; ^ba2 due; ^ca3 due

Defining Higher Order Logic

What is Higher Order Logic?



→ Propositional Logic:

- no quantifiers
- all variables have type bool

What is Higher Order Logic?



→ Propositional Logic:

- no quantifiers
- all variables have type bool

→ First Order Logic:

- quantification over values, but not over functions and predicates,
- terms and formulas syntactically distinct

What is Higher Order Logic?



→ Propositional Logic:

- no quantifiers
- all variables have type bool

→ First Order Logic:

- quantification over values, but not over functions and predicates,
- terms and formulas syntactically distinct

→ Higher Order Logic:

- quantification over everything, including predicates
- consistency by types
- formula = term of type bool
- definition built on λ^{\rightarrow} with certain default types and constants

Defining Higher Order Logic



Default types:

Defining Higher Order Logic



Default types:

`bool`

Defining Higher Order Logic



Default types:

`bool` `_` \Rightarrow `_`

Defining Higher Order Logic



Default types:

bool $_ \Rightarrow _$ ind

Defining Higher Order Logic



Default types:

`bool` `_ \Rightarrow _` `ind`

- `bool` sometimes called *o*
- `\Rightarrow` sometimes called *fun*

Defining Higher Order Logic



Default types:

`bool` `_` \Rightarrow `_` `ind`

→ `bool` sometimes called *o*

→ \Rightarrow sometimes called *fun*

Default Constants:

Defining Higher Order Logic



Default types:

`bool` `_` \Rightarrow `_` `ind`

→ `bool` sometimes called `o`

→ \Rightarrow sometimes called `fun`

Default Constants:

\longrightarrow `::` `bool` \Rightarrow `bool` \Rightarrow `bool`

Defining Higher Order Logic



Default types:

`bool` `_ \Rightarrow _` `ind`

→ `bool` sometimes called `o`

→ `\Rightarrow` sometimes called `fun`

Default Constants:

`→` `::` `bool \Rightarrow bool \Rightarrow bool`
`=` `::` `$\alpha \Rightarrow \alpha \Rightarrow bool$`

Defining Higher Order Logic



Default types:

`bool` `_ \Rightarrow _` `ind`

→ **bool** sometimes called *o*

→ \Rightarrow sometimes called *fun*

Default Constants:

\longrightarrow	$::$	$bool \Rightarrow bool \Rightarrow bool$
$=$	$::$	$\alpha \Rightarrow \alpha \Rightarrow bool$
ϵ	$::$	$(\alpha \Rightarrow bool) \Rightarrow \alpha$

Higher Order Abstract Syntax



Problem: Define syntax for binders like \forall , \exists , ε

Higher Order Abstract Syntax



Problem: Define syntax for binders like \forall , \exists , ε

One approach: $\forall :: \text{var} \Rightarrow \text{term} \Rightarrow \text{bool}$

Drawback: need to think about substitution, α conversion again.

Higher Order Abstract Syntax



Problem: Define syntax for binders like \forall , \exists , ε

One approach: $\forall :: var \Rightarrow term \Rightarrow bool$

Drawback: need to think about substitution, α conversion again.

But: Already have binder, substitution, α conversion in meta logic

λ

Higher Order Abstract Syntax



Problem: Define syntax for binders like \forall , \exists , ε

One approach: $\forall :: \text{var} \Rightarrow \text{term} \Rightarrow \text{bool}$

Drawback: need to think about substitution, α conversion again.

But: Already have binder, substitution, α conversion in meta logic

λ

So: Use λ to encode all other binders.

Higher Order Abstract Syntax



Example:

$$\text{ALL} :: (\alpha \Rightarrow \text{bool}) \Rightarrow \text{bool}$$

HOAS

usual syntax

Higher Order Abstract Syntax



Example:

$$\text{ALL} :: (\alpha \Rightarrow \text{bool}) \Rightarrow \text{bool}$$

HOAS

usual syntax

ALL $(\lambda x. x = 2)$

Higher Order Abstract Syntax



Example:

$ALL :: (\alpha \Rightarrow bool) \Rightarrow bool$

HOAS

usual syntax

$ALL (\lambda x. x = 2)$

$\forall x. x = 2$

Higher Order Abstract Syntax



Example:

$$\text{ALL} :: (\alpha \Rightarrow \text{bool}) \Rightarrow \text{bool}$$

HOAS

usual syntax

ALL $(\lambda x. x = 2)$
ALL P

$\forall x. x = 2$

Higher Order Abstract Syntax



Example:

$$\text{ALL} :: (\alpha \Rightarrow \text{bool}) \Rightarrow \text{bool}$$

HOAS

usual syntax

ALL $(\lambda x. x = 2)$

$\forall x. x = 2$

ALL P

$\forall x. P\ x$

Higher Order Abstract Syntax



Example:

$$\text{ALL} :: (\alpha \Rightarrow \text{bool}) \Rightarrow \text{bool}$$

HOAS

usual syntax

ALL $(\lambda x. x = 2)$

$\forall x. x = 2$

ALL P

$\forall x. P \ x$

Isabelle can translate usual binder syntax into HOAS.

Side Track: Syntax Declarations in Isabelle



→ **mixfix:**

consts `drvbl :: ct \Rightarrow ct \Rightarrow fm \Rightarrow bool` (`"-, - \vdash -"`)

Legal syntax now: $\Gamma, \Pi \vdash F$

Side Track: Syntax Declarations in Isabelle



→ **mixfix:**

consts $\text{drvbl} :: ct \Rightarrow ct \Rightarrow fm \Rightarrow bool$ ("_, _ \vdash _")

Legal syntax now: $\Gamma, \Pi \vdash F$

→ **priorities:**

pattern can be annotated with priorities to indicate binding strength

Example: $\text{drvbl} :: ct \Rightarrow ct \Rightarrow fm \Rightarrow bool$ ("_, _ \vdash _" [30, 0, 20] 60)

Side Track: Syntax Declarations in Isabelle



→ **mixfix:**

consts $\text{drvbl} :: ct \Rightarrow ct \Rightarrow fm \Rightarrow bool$ ("_, _ \vdash _")

Legal syntax now: $\Gamma, \Pi \vdash F$

→ **priorities:**

pattern can be annotated with priorities to indicate binding strength

Example: $\text{drvbl} :: ct \Rightarrow ct \Rightarrow fm \Rightarrow bool$ ("_, _ \vdash _" [30, 0, 20] 60)

→ **infixl/infixr:** short form for left/right associative binary operators

Example: $\text{or} :: bool \Rightarrow bool \Rightarrow bool$ (infixr " \vee " 30)

Side Track: Syntax Declarations in Isabelle



→ **mixfix:**

consts $\text{drvbl} :: ct \Rightarrow ct \Rightarrow fm \Rightarrow bool$ ("_, _ \vdash _")

Legal syntax now: $\Gamma, \Pi \vdash F$

→ **priorities:**

pattern can be annotated with priorities to indicate binding strength

Example: $\text{drvbl} :: ct \Rightarrow ct \Rightarrow fm \Rightarrow bool$ ("_, _ \vdash _" [30, 0, 20] 60)

→ **infixl/infixr:** short form for left/right associative binary operators

Example: $\text{or} :: bool \Rightarrow bool \Rightarrow bool$ (infixr " \vee " 30)

→ **binders:** declaration must be of the form

$c :: (\tau_1 \Rightarrow \tau_2) \Rightarrow \tau_3$ (binder " B " $< p >$)

$B \ x. P$ translated into $c \ P$ (and vice versa)

Example $\text{ALL} :: (\alpha \Rightarrow bool) \Rightarrow bool$ (binder " \forall " 10)

Side Track: Syntax Declarations in Isabelle



→ **mixfix:**

consts $\text{drvbl} :: ct \Rightarrow ct \Rightarrow fm \Rightarrow bool$ ("_, _ \vdash _")

Legal syntax now: $\Gamma, \Pi \vdash F$

→ **priorities:**

pattern can be annotated with priorities to indicate binding strength

Example: $\text{drvbl} :: ct \Rightarrow ct \Rightarrow fm \Rightarrow bool$ ("_, _ \vdash _" [30, 0, 20] 60)

→ **infixl/infixr:** short form for left/right associative binary operators

Example: $\text{or} :: bool \Rightarrow bool \Rightarrow bool$ (infixr " \vee " 30)

→ **binders:** declaration must be of the form

$c :: (\tau_1 \Rightarrow \tau_2) \Rightarrow \tau_3$ (binder "B" < p >)

$B \ x. P$ translated into $c \ P$ (and vice versa)

Example $\text{ALL} :: (\alpha \Rightarrow bool) \Rightarrow bool$ (binder " \forall " 10)

More in Isabelle/Isar Reference Manual (7.2)

Back to HOL



Base: $bool, \Rightarrow, ind$ $=, \longrightarrow, \varepsilon$

And the rest is

Back to HOL



Base: $bool, \Rightarrow, ind \quad =, \longrightarrow, \varepsilon$

And the rest is definitions:

True \equiv

All P \equiv

Ex P \equiv

False \equiv

$\neg P$ \equiv

$P \wedge Q$ \equiv

$P \vee Q$ \equiv

If $P \times y$ \equiv

inj f \equiv

surj f \equiv

Back to HOL



Base: $bool, \Rightarrow, ind \quad =, \longrightarrow, \varepsilon$

And the rest is definitions:

$\text{True} \quad \equiv \quad (\lambda x :: bool. x) = (\lambda x. x)$

$\text{All } P \quad \equiv$

$\text{Ex } P \quad \equiv$

$\text{False} \quad \equiv$

$\neg P \quad \equiv$

$P \wedge Q \quad \equiv$

$P \vee Q \quad \equiv$

$\text{If } P \times y \quad \equiv$

$\text{inj } f \quad \equiv$

$\text{surj } f \quad \equiv$

Back to HOL



Base: $bool, \Rightarrow, ind \quad =, \longrightarrow, \varepsilon$

And the rest is definitions:

$\text{True} \quad \equiv \quad (\lambda x :: \text{bool}. x) = (\lambda x. x)$

$\text{All } P \quad \equiv \quad P = (\lambda x. \text{True})$

$\text{Ex } P \quad \equiv$

$\text{False} \quad \equiv$

$\neg P \quad \equiv$

$P \wedge Q \quad \equiv$

$P \vee Q \quad \equiv$

$\text{If } P \times y \quad \equiv$

$\text{inj } f \quad \equiv$

$\text{surj } f \quad \equiv$

Back to HOL



Base: $bool, \Rightarrow, ind \quad =, \longrightarrow, \varepsilon$

And the rest is definitions:

$\text{True} \quad \equiv \quad (\lambda x :: \text{bool}. x) = (\lambda x. x)$

$\text{All } P \quad \equiv \quad P = (\lambda x. \text{True})$

$\text{Ex } P \quad \equiv \quad \forall Q. (\forall x. P \ x \longrightarrow Q) \longrightarrow Q$

$\text{False} \quad \equiv \quad \forall P. P$

$\neg P \quad \equiv \quad P \longrightarrow \text{False}$

$P \wedge Q \quad \equiv \quad \forall R. (P \longrightarrow Q \longrightarrow R) \longrightarrow R$

$P \vee Q \quad \equiv \quad \forall R. (P \longrightarrow R) \longrightarrow (Q \longrightarrow R) \longrightarrow R$

$\text{If } P \ x \ y \quad \equiv \quad \text{SOME } z. (P = \text{True} \longrightarrow z = x) \wedge (P = \text{False} \longrightarrow z = y)$

$\text{inj } f \quad \equiv \quad \forall x \ y. f \ x = f \ y \longrightarrow x = y$

$\text{surj } f \quad \equiv \quad \forall y. \exists x. y = f \ x$

The Axioms of HOL



$$\frac{}{t = t} \text{ refl} \qquad \frac{s = t \quad P \ s}{P \ t} \text{ subst} \qquad \frac{\bigwedge x. f \ x = g \ x}{(\lambda x. f \ x) = (\lambda x. g \ x)} \text{ ext}$$

The Axioms of HOL



$$\begin{array}{lcl} \frac{}{t = t} \text{ refl} & \frac{s = t \quad P \ s}{P \ t} \text{ subst} & \frac{\bigwedge x. f \ x = g \ x}{(\lambda x. f \ x) = (\lambda x. g \ x)} \text{ ext} \\[1em] \frac{P \implies Q}{P \longrightarrow Q} \text{ impl} & \frac{P \longrightarrow Q \quad P}{Q} \text{ mp} & \end{array}$$

The Axioms of HOL

$$\begin{array}{c} \frac{}{t = t} \text{ refl} \qquad \frac{s = t \quad P \ s}{P \ t} \text{ subst} \qquad \frac{\bigwedge x. f \ x = g \ x}{(\lambda x. f \ x) = (\lambda x. g \ x)} \text{ ext} \\[10pt] \frac{P \implies Q}{P \longrightarrow Q} \text{ impl} \qquad \frac{P \longrightarrow Q \quad P}{Q} \text{ mp} \\[10pt] \frac{}{(P \longrightarrow Q) \longrightarrow (Q \longrightarrow P) \longrightarrow (P = Q)} \text{ iff} \end{array}$$

The Axioms of HOL

$$\begin{array}{c} \frac{}{t = t} \text{ refl} \qquad \frac{s = t \quad P \ s}{P \ t} \text{ subst} \qquad \frac{\bigwedge x. f \ x = g \ x}{(\lambda x. f \ x) = (\lambda x. g \ x)} \text{ ext} \\[10pt] \frac{P \implies Q}{P \longrightarrow Q} \text{ impl} \qquad \frac{P \longrightarrow Q \quad P}{Q} \text{ mp} \\[10pt] \frac{}{(P \longrightarrow Q) \longrightarrow (Q \longrightarrow P) \longrightarrow (P = Q)} \text{ iff} \\[10pt] \frac{}{P = \text{True} \vee P = \text{False}} \text{ True_or_False} \end{array}$$

The Axioms of HOL

$$\begin{array}{c} \frac{}{t = t} \text{ refl} \qquad \frac{s = t \quad P \ s}{P \ t} \text{ subst} \qquad \frac{\bigwedge x. f \ x = g \ x}{(\lambda x. f \ x) = (\lambda x. g \ x)} \text{ ext} \\[10pt] \frac{P \implies Q}{P \longrightarrow Q} \text{ impl} \qquad \frac{P \longrightarrow Q \quad P}{Q} \text{ mp} \\[10pt] \frac{}{(P \longrightarrow Q) \longrightarrow (Q \longrightarrow P) \longrightarrow (P = Q)} \text{ iff} \\[10pt] \frac{}{P = \text{True} \vee P = \text{False}} \text{ True_or_False} \\[10pt] \frac{P \ ?_x}{P \ (\text{SOME } x. P \ x)} \text{ someI} \end{array}$$

The Axioms of HOL

$$\begin{array}{c}
 \frac{}{t = t} \text{ refl} \qquad \frac{s = t \quad P \ s}{P \ t} \text{ subst} \qquad \frac{\bigwedge x. f \ x = g \ x}{(\lambda x. f \ x) = (\lambda x. g \ x)} \text{ ext} \\
 \\
 \frac{P \implies Q}{P \longrightarrow Q} \text{ impl} \qquad \frac{P \longrightarrow Q \quad P}{Q} \text{ mp} \\
 \\
 \frac{}{(P \longrightarrow Q) \longrightarrow (Q \longrightarrow P) \longrightarrow (P = Q)} \text{ iff} \\
 \\
 \frac{}{P = \text{True} \vee P = \text{False}} \text{ True_or_False} \\
 \\
 \frac{P \ ?_x}{P \ (\text{SOME } x. P \ x)} \text{ someI} \\
 \\
 \frac{}{\exists f :: \text{ind} \Rightarrow \text{ind. inj } f \wedge \neg \text{surj } f} \text{ infy}
 \end{array}$$

That's it.



- 3 basic constants
- 3 basic types
- 9 axioms

That's it.



- 3 basic constants
- 3 basic types
- 9 axioms

With this you can define and derive all the rest.

That's it.



- 3 basic constants
- 3 basic types
- 9 axioms

With this you can define and derive all the rest.

Isabelle knows 2 more axioms:

$$\frac{x = y}{x \equiv y} \text{ eq_reflection} \qquad \overline{(\text{THE } x. x = a) = a} \text{ the_eq_trivial}$$

Demo:

The Definitions in Isabelle

Deriving Proof Rules



In the following, we will

Deriving Proof Rules



In the following, we will

→ look at the definitions in more detail

Deriving Proof Rules



In the following, we will

- look at the definitions in more detail
- derive the traditional proof rules from the axioms in Isabelle

Deriving Proof Rules



In the following, we will

- look at the definitions in more detail
- derive the traditional proof rules from the axioms in Isabelle

Convenient for deriving rules: **named assumptions in lemmas**

```
lemma [name :]  
  assumes [name1 :] “< prop >1”  
  assumes [name2 :] “< prop >2”  
  ⋮  
  shows “< prop >”  < proof >
```

Deriving Proof Rules



In the following, we will

- look at the definitions in more detail
- derive the traditional proof rules from the axioms in Isabelle

Convenient for deriving rules: **named assumptions in lemmas**

```
lemma [name :]  
  assumes [name1 :] “< prop >1”  
  assumes [name2 :] “< prop >2”  
  ⋮  
  shows “< prop >”  < proof >
```

proves: $\llbracket \langle prop \rangle_1; \langle prop \rangle_2; \dots \rrbracket \implies \langle prop \rangle$

True



consts True :: *bool*

True $\equiv (\lambda x :: \textit{bool}. x) = (\lambda x. x)$

Intuition:

right hand side is always true

True



consts True :: *bool*

True $\equiv (\lambda x :: \textit{bool}. x) = (\lambda x. x)$

Intuition:

right hand side is always true

Proof Rules:

$\overline{\text{True}}$ TrueI

Proof:

$$\frac{(\lambda x :: \textit{bool}. x) = (\lambda x. x)}{\text{True}} \text{ refl } \text{unfold True_def}$$

Demo

Universal Quantifier

consts ALL :: $(\alpha \Rightarrow \text{bool}) \Rightarrow \text{bool}$
ALL $P \equiv P = (\lambda x. \text{True})$



Universal Quantifier



consts ALL :: $(\alpha \Rightarrow \text{bool}) \Rightarrow \text{bool}$
ALL $P \equiv P = (\lambda x. \text{True})$

Intuition:

→ ALL P is Higher Order Abstract Syntax for $\forall x. P\ x$.

Universal Quantifier



consts ALL :: $(\alpha \Rightarrow \text{bool}) \Rightarrow \text{bool}$
ALL $P \equiv P = (\lambda x. \text{True})$

Intuition:

- ALL P is Higher Order Abstract Syntax for $\forall x. P\ x$.
- P is a function that takes an x and yields a truth value.

Universal Quantifier



consts ALL :: $(\alpha \Rightarrow \text{bool}) \Rightarrow \text{bool}$
ALL $P \equiv P = (\lambda x. \text{True})$

Intuition:

- ALL P is Higher Order Abstract Syntax for $\forall x. P\ x$.
- P is a function that takes an x and yields a truth value.
- ALL P should be true iff P yields true for all x , i.e.
if it is equivalent to the function $\lambda x. \text{True}$.

Universal Quantifier



consts ALL :: $(\alpha \Rightarrow \text{bool}) \Rightarrow \text{bool}$
ALL $P \equiv P = (\lambda x. \text{True})$

Intuition:

- ALL P is Higher Order Abstract Syntax for $\forall x. P\ x$.
- P is a function that takes an x and yields a truth value.
- ALL P should be true iff P yields true for all x , i.e.
if it is equivalent to the function $\lambda x. \text{True}$.

Proof Rules:

$$\frac{\bigwedge x. P\ x}{\forall x. P\ x} \text{allI} \qquad \frac{\forall x. P\ x \quad P\ ?x \implies R}{R} \text{allE}$$

Proof: Isabelle Demo

False

consts False :: *bool*
False $\equiv \forall P.P$



False

consts False :: *bool*

False $\equiv \forall P.P$

Intuition:

Everything can be derived from *False*.



False



consts False :: *bool*

False $\equiv \forall P. P$

Intuition:

Everything can be derived from *False*.

Proof Rules:

$$\frac{\text{False}}{P} \text{ FalseE} \quad \frac{}{\text{True} \neq \text{False}}$$

Proof: Isabelle Demo

Negation



consts Not :: *bool* \Rightarrow *bool* (\neg -)
 $\neg P \equiv P \longrightarrow \text{False}$

Negation



consts Not :: *bool* \Rightarrow *bool* (\neg _)

$\neg P \equiv P \longrightarrow \text{False}$

Intuition:

Try $P = \text{True}$ and $P = \text{False}$ and the traditional truth table for \longrightarrow .

Negation



consts Not :: *bool* \Rightarrow *bool* (\neg _)

$\neg P \equiv P \longrightarrow \text{False}$

Intuition:

Try $P = \text{True}$ and $P = \text{False}$ and the traditional truth table for \longrightarrow .

Proof Rules:

$$\frac{A \implies \text{False}}{\neg A} \text{ notI} \qquad \frac{\neg A \quad A}{P} \text{ notE}$$

Proof: Isabelle Demo

Existential Quantifier



consts EX :: $(\alpha \Rightarrow \text{bool}) \Rightarrow \text{bool}$
EX $P \equiv \forall Q. (\forall x. P\ x \longrightarrow Q) \longrightarrow Q$

Existential Quantifier



consts $EX :: (\alpha \Rightarrow \text{bool}) \Rightarrow \text{bool}$
 $EX\ P \equiv \forall Q. (\forall x. P\ x \longrightarrow Q) \longrightarrow Q$

Intuition:

→ $EX\ P$ is HOAS for $\exists x. P\ x$. (like \forall)

Existential Quantifier



consts $EX :: (\alpha \Rightarrow \text{bool}) \Rightarrow \text{bool}$
 $EX\ P \equiv \forall Q. (\forall x. P\ x \longrightarrow Q) \longrightarrow Q$

Intuition:

- $EX\ P$ is HOAS for $\exists x. P\ x$. (like \forall)
- Right hand side is characterization of \exists with \forall and \longrightarrow

Existential Quantifier



consts $EX :: (\alpha \Rightarrow \text{bool}) \Rightarrow \text{bool}$
 $EX\ P \equiv \forall Q. (\forall x. P\ x \longrightarrow Q) \longrightarrow Q$

Intuition:

- $EX\ P$ is HOAS for $\exists x. P\ x$. (like \forall)
- Right hand side is characterization of \exists with \forall and \longrightarrow
- Note that inner \forall binds wide: $(\forall x. P\ x \longrightarrow Q)$

Existential Quantifier



consts EX :: $(\alpha \Rightarrow \text{bool}) \Rightarrow \text{bool}$

EX P $\equiv \forall Q. (\forall x. P\ x \longrightarrow Q) \longrightarrow Q$

Intuition:

- EX P is HOAS for $\exists x. P\ x$. (like \forall)
- Right hand side is characterization of \exists with \forall and \longrightarrow
- Note that inner \forall binds wide: $(\forall x. P\ x \longrightarrow Q)$
- Remember lemma from last time: $(\forall x. P\ x \longrightarrow Q) = ((\exists x. P\ x) \longrightarrow Q)$

Existential Quantifier



consts $EX :: (\alpha \Rightarrow \text{bool}) \Rightarrow \text{bool}$
 $EX\ P \equiv \forall Q. (\forall x. P\ x \longrightarrow Q) \longrightarrow Q$

Intuition:

- $EX\ P$ is HOAS for $\exists x. P\ x$. (like \forall)
- Right hand side is characterization of \exists with \forall and \longrightarrow
- Note that inner \forall binds wide: $(\forall x. P\ x \longrightarrow Q)$
- Remember lemma from last time: $(\forall x. P\ x \longrightarrow Q) = ((\exists x. P\ x) \longrightarrow Q)$

Proof Rules:

$$\frac{P\ ?_x}{\exists x. P\ x} \text{ exI} \qquad \frac{\exists x. P\ x \quad \bigwedge x. P\ x \Longrightarrow R}{R} \text{ exE}$$

Proof: Isabelle Demo

Conjunction



consts And $:: \text{bool} \Rightarrow \text{bool} \Rightarrow \text{bool} \ (_ \wedge _)$
 $P \wedge Q \equiv \forall R. (P \longrightarrow Q \longrightarrow R) \longrightarrow R$

Conjunction



consts And $:: \text{bool} \Rightarrow \text{bool} \Rightarrow \text{bool} \ (_ \wedge _)$
 $P \wedge Q \equiv \forall R. (P \longrightarrow Q \longrightarrow R) \longrightarrow R$

Intuition:

→ Mirrors proof rules for \wedge

Conjunction



consts And :: $bool \Rightarrow bool \Rightarrow bool$ ($_ \wedge _$)
 $P \wedge Q \equiv \forall R. (P \longrightarrow Q \longrightarrow R) \longrightarrow R$

Intuition:

- Mirrors proof rules for \wedge
- Try truth table for P , Q , and R

Conjunction



consts And $:: \text{bool} \Rightarrow \text{bool} \Rightarrow \text{bool} \ (_ \wedge _)$
 $P \wedge Q \equiv \forall R. (P \longrightarrow Q \longrightarrow R) \longrightarrow R$

Intuition:

- Mirrors proof rules for \wedge
- Try truth table for P , Q , and R

Proof Rules:

$$\frac{A \quad B}{A \wedge B} \text{ conjI} \qquad \frac{A \wedge B \quad \llbracket A; B \rrbracket \Longrightarrow C}{C} \text{ conjE}$$

Proof: Isabelle Demo

Disjunction



consts Or :: *bool* \Rightarrow *bool* \Rightarrow *bool* (*_* \vee *_*)

$P \vee Q \equiv \forall R. (P \longrightarrow R) \longrightarrow (Q \longrightarrow R) \longrightarrow R$

Disjunction



consts Or :: *bool* \Rightarrow *bool* \Rightarrow *bool* ($_ \vee _$)
 $P \vee Q \equiv \forall R. (P \longrightarrow R) \longrightarrow (Q \longrightarrow R) \longrightarrow R$

Intuition:

→ Mirrors proof rules for \vee (case distinction)

Disjunction



consts Or :: *bool* \Rightarrow *bool* \Rightarrow *bool* ($_ \vee _$)
 $P \vee Q \equiv \forall R. (P \longrightarrow R) \longrightarrow (Q \longrightarrow R) \longrightarrow R$

Intuition:

- Mirrors proof rules for \vee (case distinction)
- Try truth table for P , Q , and R

Disjunction



consts Or :: *bool* \Rightarrow *bool* \Rightarrow *bool* ($_ \vee _$)
 $P \vee Q \equiv \forall R. (P \longrightarrow R) \longrightarrow (Q \longrightarrow R) \longrightarrow R$

Intuition:

- Mirrors proof rules for \vee (case distinction)
- Try truth table for P , Q , and R

Proof Rules:

$$\frac{A}{A \vee B} \quad \frac{B}{A \vee B} \text{ disjI1/2} \qquad \frac{A \vee B \quad A \Longrightarrow C \quad B \Longrightarrow C}{C} \text{ disjE}$$

Proof: Isabelle Demo

If-Then-Else



consts If $:: \text{bool} \Rightarrow \alpha \Rightarrow \alpha \Rightarrow \alpha$ (if_ then _ else _)

If $P \times y \equiv \text{SOME } z. (P = \text{True} \longrightarrow z = x) \wedge (P = \text{False} \longrightarrow z = y)$

If-Then-Else



consts If :: $bool \Rightarrow \alpha \Rightarrow \alpha \Rightarrow \alpha$ (if_ then _ else _)

If $P \times y \equiv \text{SOME } z. (P = \text{True} \longrightarrow z = x) \wedge (P = \text{False} \longrightarrow z = y)$

Intuition:

→ for $P = \text{True}$, right hand side collapses to $\text{SOME } z. z = x$

If-Then-Else



consts If :: $bool \Rightarrow \alpha \Rightarrow \alpha \Rightarrow \alpha$ (if_ then _ else _)

If $P \times y \equiv \text{SOME } z. (P = \text{True} \longrightarrow z = x) \wedge (P = \text{False} \longrightarrow z = y)$

Intuition:

- for $P = \text{True}$, right hand side collapses to $\text{SOME } z. z = x$
- for $P = \text{False}$, right hand side collapses to $\text{SOME } z. z = y$

If-Then-Else



consts If $:: \text{bool} \Rightarrow \alpha \Rightarrow \alpha \Rightarrow \alpha$ (if_ then _ else _)

If $P \times y \equiv \text{SOME } z. (P = \text{True} \longrightarrow z = x) \wedge (P = \text{False} \longrightarrow z = y)$

Intuition:

- for $P = \text{True}$, right hand side collapses to $\text{SOME } z. z = x$
- for $P = \text{False}$, right hand side collapses to $\text{SOME } z. z = y$

Proof Rules:

$\frac{}{\text{if True then } s \text{ else } t = s}$ ifTrue

$\frac{}{\text{if False then } s \text{ else } t = t}$ ifFalse

Proof: Isabelle Demo

That was HOL

More on Automation



Last time: safe and unsafe, heuristics: use safe before unsafe

More on Automation



Last time: safe and unsafe, heuristics: use safe before unsafe

This can be automated

More on Automation



Last time: safe and unsafe, heuristics: use safe before unsafe

This can be automated

More on Automation



Last time: safe and unsafe, heuristics: use safe before unsafe

This can be automated

Syntax:

[<kind>!] for safe rules (<kind> one of intro, elim, dest)
[<kind>] for unsafe rules

More on Automation



Last time: safe and unsafe, heuristics: use safe before unsafe

This can be automated

Syntax:

[<kind>!] for safe rules (<kind> one of intro, elim, dest)
[<kind>] for unsafe rules

Application (roughly):

do safe rules first, search/backtrack on unsafe rules only

More on Automation



Last time: safe and unsafe, heuristics: use safe before unsafe

This can be automated

Syntax:

[<kind>!] for safe rules (<kind> one of intro, elim, dest)
[<kind>] for unsafe rules

Application (roughly):

do safe rules first, search/backtrack on unsafe rules only

Example:

declare attribute globally	declare conjI [intro!] allE [elim]
remove attribute globally	declare allE [rule del]
use locally	apply (blast intro: somel)
delete locally	apply (blast del: conjI)

Demo: Automation

We have learned today ...



→ Defining HOL

We have learned today ...



- Defining HOL
- Higher Order Abstract Syntax

We have learned today ...



- Defining HOL
- Higher Order Abstract Syntax
- Deriving proof rules

We have learned today ...



- Defining HOL
- Higher Order Abstract Syntax
- Deriving proof rules
- More automation