

---

## ***Overview of Isabelle/HOL***

# ***System Architecture***

---

<i>Isabelle</i>	generic theorem prover

# System Architecture

---

<i>Isabelle/HOL</i>	Isabelle instance for HOL
<i>Isabelle</i>	generic theorem prover

# System Architecture

---

<i>ProofGeneral</i>	(X)Emacs based interface
<i>Isabelle/HOL</i>	Isabelle instance for HOL
<i>Isabelle</i>	generic theorem prover

# ***HOL***

---

HOL = Higher-Order Logic

# ***HOL***

---

HOL = Higher-Order Logic

HOL = Functional programming + Logic

# ***HOL***

---

HOL = Higher-Order Logic

HOL = Functional programming + Logic

HOL has

- datatypes
- recursive functions
- logical operators ( $\wedge$ ,  $\longrightarrow$ ,  $\forall$ ,  $\exists$ ,  $\dots$ )

# ***HOL***

---

HOL = Higher-Order Logic

HOL = Functional programming + Logic

HOL has

- datatypes
- recursive functions
- logical operators ( $\wedge$ ,  $\longrightarrow$ ,  $\forall$ ,  $\exists$ , ...)

HOL is a programming language!



# *HOL*

---

HOL = Higher-Order Logic

HOL = Functional programming + Logic

HOL has

- datatypes
- recursive functions
- logical operators ( $\wedge$ ,  $\longrightarrow$ ,  $\forall$ ,  $\exists$ , ...)

HOL is a programming language!

Higher-order = functions are values, too!

# Formulae

---

Syntax (in decreasing priority):

$$\begin{array}{lll} \text{form} & ::= & (\text{form}) \quad | \quad \text{term} = \text{term} \quad | \quad \neg \text{form} \\ & & | \quad \text{form} \wedge \text{form} \quad | \quad \text{form} \vee \text{form} \quad | \quad \text{form} \longrightarrow \text{form} \\ & & | \quad \forall x. \text{form} \quad | \quad \exists x. \text{form} \end{array}$$

# Formulae

---

Syntax (in decreasing priority):

$$\begin{array}{llll} \text{form} & ::= & (\text{form}) & | \text{ term} = \text{term} & | \neg \text{form} \\ & & | \text{ form} \wedge \text{form} & | \text{ form} \vee \text{form} & | \text{ form} \longrightarrow \text{form} \\ & & | \forall x. \text{form} & | \exists x. \text{form} \end{array}$$

Examples

- $\neg A \wedge B \vee C \equiv ((\neg A) \wedge B) \vee C$

# Formulae

---

Syntax (in decreasing priority):

$$\begin{array}{llll} \text{form} & ::= & (\text{form}) & | \text{ term} = \text{term} & | \neg \text{form} \\ & & | \text{ form} \wedge \text{form} & | \text{ form} \vee \text{form} & | \text{ form} \longrightarrow \text{form} \\ & & | \forall x. \text{form} & | \exists x. \text{form} \end{array}$$

## Examples

- $\neg A \wedge B \vee C \equiv ((\neg A) \wedge B) \vee C$
- $A = B \wedge C \equiv (A = B) \wedge C$

# Formulae

---

Syntax (in decreasing priority):

$$\begin{array}{llll} \text{form} & ::= & (\text{form}) & | \text{ term} = \text{term} & | \neg \text{form} \\ & & | \text{ form} \wedge \text{form} & | \text{ form} \vee \text{form} & | \text{ form} \longrightarrow \text{form} \\ & & | \forall x. \text{form} & | \exists x. \text{form} \end{array}$$

## Examples

- $\neg A \wedge B \vee C \equiv ((\neg A) \wedge B) \vee C$
- $A = B \wedge C \equiv (A = B) \wedge C$
- $\forall x. P x \wedge Q x \equiv \forall x. (P x \wedge Q x)$

# Formulae

Syntax (in decreasing priority):

$$\begin{array}{llll} \text{form} & ::= & (\text{form}) & | \text{ term} = \text{term} & | \neg \text{form} \\ & & | \text{ form} \wedge \text{form} & | \text{ form} \vee \text{form} & | \text{ form} \longrightarrow \text{form} \\ & & | \forall x. \text{form} & | \exists x. \text{form} \end{array}$$

## Examples

- $\neg A \wedge B \vee C \equiv ((\neg A) \wedge B) \vee C$
- $A = B \wedge C \equiv (A = B) \wedge C$
- $\forall x. P x \wedge Q x \equiv \forall x. (P x \wedge Q x)$

Scope of quantifiers: as far to the right as possible

# *Formulae*

---

Abbreviation:  $\forall x y. P x y \equiv \forall x. \forall y. P x y$

# *Formulae*

---

Abbreviation:  $\forall x y. P x y \equiv \forall x. \forall y. P x y$  ( $\forall, \exists, \lambda, \dots$ )



# Formulae

---

Abbreviation:  $\forall x y. P x y \equiv \forall x. \forall y. P x y$  ( $\forall, \exists, \lambda, \dots$ )

Parentheses:

- $\wedge, \vee$  and  $\longrightarrow$  associate to the right:  
 $A \wedge B \wedge C \equiv A \wedge (B \wedge C)$

# Formulae

---

Abbreviation:  $\forall x y. P x y \equiv \forall x. \forall y. P x y$  ( $\forall, \exists, \lambda, \dots$ )

Parentheses:

- $\wedge, \vee$  and  $\longrightarrow$  associate to the right:

$$A \wedge B \wedge C \equiv A \wedge (B \wedge C)$$

- $A \longrightarrow B \longrightarrow C \equiv A \longrightarrow (B \longrightarrow C) \not\equiv (A \longrightarrow B) \longrightarrow C$  !

# Warning

---

Quantifiers have low priority and need to be parenthesized:

$$\text{! } P \wedge \forall x. Q x \leadsto P \wedge (\forall x. Q x) \text{ !}$$

---

# ***Types and Terms***

# Types

---

## Syntax:

$$\begin{array}{l} \tau ::= (\tau) \\ \quad | \textit{bool} \mid \textit{nat} \mid \dots \end{array} \quad \text{base types}$$

# Types

---

## Syntax:

$$\begin{array}{ll} \tau & ::= (\tau) \\ & | \textit{bool} \mid \textit{nat} \mid \dots & \text{base types} \\ & | 'a \mid 'b \mid \dots & \text{type variables} \end{array}$$

# Types

---

## Syntax:

$\tau$	$::=$	$(\tau)$	
		$bool \mid nat \mid \dots$	base types
		$'a \mid 'b \mid \dots$	type variables
		$\tau \Rightarrow \tau$	total functions

# Types

---

## Syntax:

$\tau ::=$	$(\tau)$	
	$bool \mid nat \mid \dots$	base types
	$'a \mid 'b \mid \dots$	type variables
	$\tau \Rightarrow \tau$	total functions
	$\tau \times \tau$	pairs (ascii: *)



# Types

---

## Syntax:

$\tau$	$::=$	$(\tau)$	
		$\mathit{bool} \mid \mathit{nat} \mid \dots$	base types
		$\mathit{'a} \mid \mathit{'b} \mid \dots$	type variables
		$\tau \Rightarrow \tau$	total functions
		$\tau \times \tau$	pairs (ascii: *)
		$\tau \mathit{list}$	lists

# Types

---

## Syntax:

$\tau$	$::=$	$(\tau)$	
		$bool \mid nat \mid \dots$	base types
		$'a \mid 'b \mid \dots$	type variables
		$\tau \Rightarrow \tau$	total functions
		$\tau \times \tau$	pairs (ascii: *)
		$\tau \text{ list}$	lists
		$\dots$	user-defined types

# Types

---

## Syntax:

$\tau ::=$	$(\tau)$	
	$bool \mid nat \mid \dots$	base types
	$'a \mid 'b \mid \dots$	type variables
	$\tau \Rightarrow \tau$	total functions
	$\tau \times \tau$	pairs (ascii: *)
	$\tau \text{ list}$	lists
	$\dots$	user-defined types

Parentheses:  $T1 \Rightarrow T2 \Rightarrow T3 \equiv T1 \Rightarrow (T2 \Rightarrow T3)$

# ***Terms: Basic syntax***

---

## Syntax:

$term$	$::=$	$(term)$	
		$a$	constant or variable (identifier)
		$term\ term$	function application
		$\lambda x. term$	function “abstraction”

# ***Terms: Basic syntax***

---

## Syntax:

$term$	$::=$	$(term)$	
		$a$	constant or variable (identifier)
		$term\ term$	function application
		$\lambda x. term$	function “abstraction”
		$\dots$	lots of syntactic sugar

# ***Terms: Basic syntax***

---

## Syntax:

$term$	$::=$	$(term)$	
		$a$	constant or variable (identifier)
		$term\ term$	function application
		$\lambda x. term$	function “abstraction”
		$\dots$	lots of syntactic sugar

Examples:       $f\ (g\ x)\ y$        $h\ (\lambda x. f\ (g\ x))$

# Terms: Basic syntax

---

## Syntax:

$term$	$::=$	$(term)$	
		$a$	constant or variable (identifier)
		$term\ term$	function application
		$\lambda x. term$	function “abstraction”
		$\dots$	lots of syntactic sugar

Examples:  $f\ (g\ x)\ y$        $h\ (\lambda x. f\ (g\ x))$

Parantheses:  $f\ a_1\ a_2\ a_3 \equiv ((f\ a_1)\ a_2)\ a_3$

# **$\lambda$ -calculus on one slide**

---

Informal notation:  $t[x]$



# $\lambda$ -calculus on one slide

---

Informal notation:  $t[x]$

- *Function application:*  
 $f\ a$  is the call of function  $f$  with argument  $a$

# $\lambda$ -calculus on one slide

---

Informal notation:  $t[x]$

- *Function application:*  
 $f\ a$  is the call of function  $f$  with argument  $a$
- *Function abstraction:*  
 $\lambda x.t[x]$  is the function with formal parameter  $x$  and body/result  $t[x]$ , i.e.  $x \mapsto t[x]$ .

# $\lambda$ -calculus on one slide

---

Informal notation:  $t[x]$

- *Function application:*

$f\ a$  is the call of function  $f$  with argument  $a$

- *Function abstraction:*

$\lambda x.t[x]$  is the function with formal parameter  $x$  and body/result  $t[x]$ , i.e.  $x \mapsto t[x]$ .

- *Computation:*

Replace formal by actual parameter (“ $\beta$ -reduction”):

$$(\lambda x.t[x])\ a \longrightarrow_{\beta} t[a]$$

# $\lambda$ -calculus on one slide

---

Informal notation:  $t[x]$

- *Function application:*

$f\ a$  is the call of function  $f$  with argument  $a$

- *Function abstraction:*

$\lambda x.t[x]$  is the function with formal parameter  $x$  and body/result  $t[x]$ , i.e.  $x \mapsto t[x]$ .

- *Computation:*

Replace formal by actual parameter (“ $\beta$ -reduction”):

$$(\lambda x.t[x])\ a \longrightarrow_{\beta} t[a]$$

Example:  $(\lambda x. x + 5)\ 3 \longrightarrow_{\beta} (3 + 5)$

$\longrightarrow_{\beta}$  *in Isabelle: Don't worry, be happy*

---

Isabelle performs  $\beta$ -reduction automatically

Isabelle considers  $(\lambda x.t[x])a$  and  $t[a]$  equivalent

# *Terms and Types*

---

Terms must be well-typed

(the argument of every function call must be of the right type)

# *Terms and Types*

---

Terms must be well-typed

(the argument of every function call must be of the right type)

Notation:  $t :: \tau$  means  $t$  is a well-typed term of type  $\tau$ .

# *Type inference*

---

Isabelle automatically computes (“*infers*”) the type of each variable in a term.



# *Type inference*

---

Isabelle automatically computes (“*infers*”) the type of each variable in a term.

In the presence of *overloaded* functions (functions with multiple types) not always possible.

# *Type inference*

---

Isabelle automatically computes (“*infers*”) the type of each variable in a term.

In the presence of *overloaded* functions (functions with multiple types) not always possible.

User can help with **type annotations** inside the term.

Example: *f (x::nat)*

# *Currying*

---

Thou shalt curry your functions

# Currying

---

Thou shalt curry your functions

- Curried:  $f :: \tau_1 \Rightarrow \tau_2 \Rightarrow \tau$
- Tupled:  $f' :: \tau_1 \times \tau_2 \Rightarrow \tau$

# Currying

---

Thou shalt curry your functions

- Curried:  $f :: \tau_1 \Rightarrow \tau_2 \Rightarrow \tau$
- Tupled:  $f' :: \tau_1 \times \tau_2 \Rightarrow \tau$

Advantage: *partial application*  $f\ a_1$  with  $a_1 :: \tau_1$

# *Terms: Syntactic sugar*

---

Some predefined syntactic sugar:

- *Infix*:  $+$ ,  $-$ ,  $*$ ,  $\#$ ,  $@$ , . . .
- *Mixfix*: *if* \_ *then* \_ *else* \_, *case* \_ *of*, . . .

# Terms: Syntactic sugar

---

Some predefined syntactic sugar:

- *Infix*:  $+$ ,  $-$ ,  $*$ ,  $\#$ ,  $@$ ,  $\dots$
- *Mixfix*: *if*  $\_$  *then*  $\_$  *else*  $\_$ , *case*  $\_$  *of*,  $\dots$

Prefix binds more strongly than infix:

$$\mathbf{!} \quad f\ x + y \equiv (f\ x) + y \not\equiv f\ (x + y) \quad \mathbf{!}$$

# Terms: Syntactic sugar

---

Some predefined syntactic sugar:

- *Infix*:  $+$ ,  $-$ ,  $*$ ,  $\#$ ,  $@$ ,  $\dots$
- *Mixfix*: *if*  $\_$  *then*  $\_$  *else*  $\_$ , *case*  $\_$  *of*,  $\dots$

Prefix binds more strongly than infix:

$$! \quad f \ x + y \equiv (f \ x) + y \not\equiv f \ (x + y) \quad !$$

Enclose *if* and *case* in parentheses:

$$! \quad (if \ \_ \ then \ \_ \ else \ \_) \quad !$$



---

***Base types: bool, nat, list***

# *Type bool*

---

Formulae = terms of type *bool*

# *Type bool*

---

Formulae = terms of type *bool*

*True* :: *bool*

*False* :: *bool*

$\wedge, \vee, \dots$  :: *bool*  $\Rightarrow$  *bool*  $\Rightarrow$  *bool*

$\vdots$

# *Type bool*

---

Formulae = terms of type *bool*

*True* :: *bool*

*False* :: *bool*

$\wedge, \vee, \dots$  :: *bool*  $\Rightarrow$  *bool*  $\Rightarrow$  *bool*

$\vdots$

if-and-only-if: =

## *Type nat*

---

$0 :: \text{nat}$

$\text{Suc} :: \text{nat} \Rightarrow \text{nat}$

$+, *, \dots :: \text{nat} \Rightarrow \text{nat} \Rightarrow \text{nat}$

$\vdots$

## *Type nat*

---

$0 :: \text{nat}$

$\text{Suc} :: \text{nat} \Rightarrow \text{nat}$

$+, *, \dots :: \text{nat} \Rightarrow \text{nat} \Rightarrow \text{nat}$

$\vdots$

**!** Numbers and arithmetic operations are overloaded:

$0, 1, 2, \dots :: 'a, \quad + :: 'a \Rightarrow 'a \Rightarrow 'a$

You need type annotations:  $1 :: \text{nat}, x + (y :: \text{nat})$

## *Type nat*

---

$0 :: \text{nat}$

$\text{Suc} :: \text{nat} \Rightarrow \text{nat}$

$+, *, \dots :: \text{nat} \Rightarrow \text{nat} \Rightarrow \text{nat}$

$\vdots$

**!** Numbers and arithmetic operations are overloaded:

$0, 1, 2, \dots :: 'a, \quad + :: 'a \Rightarrow 'a \Rightarrow 'a$

You need type annotations:  $1 :: \text{nat}, x + (y :: \text{nat})$

... unless the context is unambiguous:  $\text{Suc } z$

# Type list

---

- $[]$ : empty list
- $x \# xs$ : list with first element  $x$  ("*head*")  
and rest  $xs$  ("*tail*")
- Syntactic sugar:  $[x_1, \dots, x_n]$



# Type list

---

- $[]$ : empty list
- $x \# xs$ : list with first element  $x$  ("*head*") and rest  $xs$  ("*tail*")
- Syntactic sugar:  $[x_1, \dots, x_n]$

Large library:

*hd, tl, map, length, filter, set, nth, take, drop, distinct, ...*

Don't reinvent, reuse!

$\leadsto$  HOL/List.thy

---

# ***Isabelle Theories***

# ***Theory = Module***

---

Syntax:    *theory*  $MyTh$   
              *imports*  $ImpTh_1 \dots ImpTh_n$   
              *begin*  
              (declarations, definitions, theorems, proofs, ...)\*  
              *end*

- $MyTh$ : name of theory. Must live in file  $MyTh.thy$
- $ImpTh_i$ : name of *imported* theories. Import transitive.

# ***Theory = Module***

---

Syntax:    `theory` *MyTh*  
          `imports` *ImpTh*<sub>1</sub> ... *ImpTh*<sub>*n*</sub>  
          `begin`  
          (declarations, definitions, theorems, proofs, ...)\*  
          `end`

- *MyTh*: name of theory. Must live in file *MyTh.thy*
- *ImpTh*<sub>*i*</sub>: name of *imported* theories. Import transitive.

Usually:    `theory` *MyTh*  
          `imports` `Main`  
          `:`

---

## ***Proof General***



## ***An Isabelle Interface***

by David Aspinall

# ***Proof General***

---

Customized version of (x)emacs:

- all of emacs (info: C-h i)
- Isabelle aware (when editing `.thy` files)
- mathematical symbols (“x-symbols”)

# X-Symbols

## Input of funny symbols in Proof General

- via menu (“X-Symbol”)
- via ascii encoding (similar to  $\text{\LaTeX}$ ): `\<and>`, `\<or>`, ...
- via abbreviation: `/\`, `\/`, `-->`, ...

x-symbol	$\forall$	$\exists$	$\lambda$	$\neg$	$\wedge$	$\vee$	$\longrightarrow$	$\Rightarrow$
ascii (1)	<code>\&lt;forall&gt;</code>	<code>\&lt;exists&gt;</code>	<code>\&lt;lambda&gt;</code>	<code>\&lt;not&gt;</code>	<code>/\</code>	<code>\/</code>	<code>--&gt;</code>	<code>=&gt;</code>
ascii (2)	ALL	EX	%	~	&			

(1) is converted to x-symbol, (2) stays ascii.

---

## ***Demo: terms and types***