
NOTE : STANDARD FASTENER TORQUE AS PER STD-DES-01-00 FR-DES-006-00


HOLE TABLE				
Hole	X	Y	Size	REMARK
A.1	0.00	0.00	Ø 6.00 mm THRU'	H7
A.2	−12.50	114.00	Ø 6.00 mm THRU'	H7
A.3	117.50	114.00	Ø 6.00 mm THRU'	H7
A.4	35.00	0.00	Ø 6.00 mm THRU'	H7
A.5	70.00	0.00	Ø 6.00 mm THRU'	H7
A.6	105.00	0.00	Ø 6.00 mm THRU'	H7
B.1	−17.50	0.00	Ø 7.00 mm THRU'	
B.2	17.50	0.00	Ø 7.00 mm THRU'	
B.3	52.50	0.00	Ø 7.00 mm THRU'	
B.4	87.50	0.00	Ø 7.00 mm THRU'	
B.5	122.50	0.00	Ø 7.00 mm THRU'	
C.1	−12.50	42.00	Ø 10.00 mm THRU'	
C.2	117.50	42.00	Ø 10.00 mm THRU'	
C.3	−12.50	102.00	Ø 10.00 mm THRU'	
C.4	117.50	102.00	Ø 10.00 mm THRU'	

NOTE :−(English)
DEBURR ALL UNSPECIFIED HOLES AND SHARP EDGES.


NOTE :−(French)
ÉBAVUREZ TOUS LES TROUS NON SPÉCIFIÉS ET LES BORDS TRANCHANTS.



SCALE/ÉCHELLE 1:1



SCALE/ÉCHELLE 1:1



SCALE/ÉCHELLE 1:2

TOLERANCE NOTE :− (English)
1) ALL H7 HOLES C.D SHOULD BE CONTROLLED WITHIN +/− 0.02. / IT7
2) ALL HOLES,TAP & COUNTER BORE C.D,
SHOULD BE CONTROLLED WITHIN +/− 0.1

NOTE DE TOLERANCE :− (French)
1) TOUT TROU H7 C.D DOIT ÊTRE CONTRÔLÉ SOUS +/− 0.02 / IT7
2) TOUT TROU ET CONTRE−ALÉSAGE C.D,
DOIT ÊTRE CONTROLÉ SOUS +/− 0.1

NOTE : (English)
MATERIAL: HE 30
FINISH: SELF−ANODIZING
MACHINING: 3.2
WEIGHT(Kg): 0.36 kg

NOTE :−(French)
MATÉRIEL : HE 30
FINITION : SELF−ANODIZING
MACHINES : 3.2
POIDS (Kg): 0.36 kg

NOTE:
1)USE HELICOIL INSERT AT ALL TAPPING HOLES

NOTE FOR WIPRO PARI DESIGN -REF. ONLY
WEAR DETAILS : N.A

RESERVED SPACE FOR CONTROLLED COPY STAMP

CONTROLLED COPY

REVISION	DESCRIPTION	DATE	DRN.BY

DEBURR AND REMOVE SHARP EDGES UNLESS SHARP EDGE REQUIREMENT SPECIFIED	
UNSP.RADII	UNSP.CHF
0.5 R	0.5 X 45°
UNSPECIFIED TOL.(FAB) FOR ANGULAR IN mm.	
UP TO 10	±1.5°
10 UP TO 50	±0°50'
50 UP TO 120	±0°25'
120 UP TO 400	±0°15'
UNSPECIFIED TOL.(FAB) FOR LINEAR IN mm.	
0.5 UP TO 3	±0.1
3 UP TO 6	±0.2
6 UP TO 30	±0.5
30 UP TO 120	±0.8
120 UP TO 315	±1.2
315 UP TO 1000	±2
1000 UP TO 2000	±3
OVER 2000	±4
UNSPECIFIED TOL.(M/C) FOR ANGULAR IN mm.	
UP TO 10	±1°
10 UP TO 50	±0°30'
50 UP TO 120	±0°20'
120 UP TO 400	±0°10'
UNSPECIFIED TOL.(M/C) FOR LINEAR IN mm.	
0.5 UP TO 3	±0.1
3 UP TO 6	±0.1
6 UP TO 30	±0.2
30 UP TO 120	±0.3
120 UP TO 315	±0.5
315 UP TO 1000	±0.8
1000 UP TO 2000	±1.2
OVER 2000	±2
LIMITS	
Gen Tol.: IS 2102	

wipro PARI
www.wipropari.com

1.ALL DIMENSIONS ARE IN mm
2.DO NOT SCALE DRAWING.
3.IF IN DOUBT , ASK TEAM MEMBER
LOCATION : PUNE

© ALL RIGHTS OF REPRODUCTION & DISTRIBUTION ARE RESERVED

WIPRO PARI GROUP

DESCRIPTION: SUPPORT PLATE
DRAWING TYPE: MACHINING

SURFACE AREA	SURFACE TREATMENT	MACHINING	DESIGN UNIT	DESIGN UNIT CD.	TEAM NO.	SHEET SIZE
54.83 in^2	#	#	WPES	0300	PL-02	A2

REFERENCE DWG. --- | PART CLASS. B | HEAT TREATMENT ----

DRN.BY	CHKD.BY	APPD.BY	MATERIAL	DRG./PART CODE	REV.	SCALE
03004476	03004785	03004785	#	P23Y5B076049	00	1 : 1
27/06/2024	27/06/2024	27/06/2024	NET WEIGHT-Kg 0.36 kg			SHEET 1 OF 1

\\srv01102\ExDM Uploading\2022-23\P23Y5\P23Y5B076049.dft