

NOTE : STANDARD FASTENER TORQUE AS PER STD-DES-01-00 FR-DES-006-00




TOP VIEW
SCALE/ÉCHELLE 1:1



FRONT VIEW
SCALE/ÉCHELLE 1:1

HOLE TABLE

Hole	X	Y	Size	REMARK
A.1	0.00	0.00	Ø 6.00 mm THRU'	H7 HOLE
A.2	0.00	−60.00	Ø 6.00 mm THRU'	H7 HOLE
A.3	0.00	−48.00	Ø 6.00 mm THRU'	H7 HOLE
A.4	0.00	−12.00	Ø 6.00 mm THRU'	H7 HOLE
B.1	−11.00	−48.00	Ø 6.60 mm THRU' C'BORE Ø 11.00 mm − 6.80 mm DEEP	
B.2	11.00	−48.00	Ø 6.60 mm THRU' C'BORE Ø 11.00 mm − 6.80 mm DEEP	
B.3	−11.00	−24.00	Ø 6.60 mm THRU' C'BORE Ø 11.00 mm − 6.80 mm DEEP	
B.4	11.00	−24.00	Ø 6.60 mm THRU' C'BORE Ø 11.00 mm − 6.80 mm DEEP	
B.5	−11.00	0.00	Ø 6.60 mm THRU' C'BORE Ø 11.00 mm − 6.80 mm DEEP	
B.6	11.00	0.00	Ø 6.60 mm THRU' C'BORE Ø 11.00 mm − 6.80 mm DEEP	
C.1	−44.00	−13.00	Ø 5.80 mm THRU'	
C.2	44.00	−13.00	Ø 5.80 mm THRU'	



ISOMETRIC VIEW
SCALE/ÉCHELLE 1:1

TOLERANCE NOTE :− (English)
1) ALL H7 HOLES C.D SHOULD BE CONTROLLED WITHIN +/− 0.02. / IT7
2) ALL HOLES,TAP & COUNTER BORE C.D,
SHOULD BE CONTROLLED WITHIN +/− 0.1

NOTE DE TOLERANCE :− (French)
1) TOUT TROU H7 C.D DOIT ÊTRE CONTRÔLÉ SOUS +/− 0.02 / IT7
2) TOUT TROU ET CONTRE−ALÉSAGE C.D,
DOIT ÊTRE CONTROLÉ SOUS +/− 0.1

NOTE :−(English)
DEBURR ALL UNSPECIFIED HOLES AND SHARP EDGES.

NOTE :−(French)
ÉBAVUREZ TOUS LES TROUS NON SPÉCIFIÉS ET LES BORDS TRANCHANTS.

NOTE : (English)
MATERIAL: M.S.
FINISH: I.Z.B.P. (TRIVALENT)
MACHINING: 3.2
WEIGHT(Kg): 0.51 kg

NOTE :−(French)
MATÉRIEL : M.S.
FINITION : I.Z.B.P. (TRIVALENT)
MACHINES : 3.2
POIDS (Kg): 0.51 kg

RESERVED SPACE FOR STAMP

CONTROLLED COPY

NOTE FOR WIPRO PARI DESIGN -REF. ONLY
WEAR DETAILS : N.A.

DEBURR AND REMOVE SHARP EDGES UNLESS SHARP EDGE REQUIREMENT SPECIFIED

UNSP.RADII	UNSP.CHF.
0.5 R	0.5 X 45°

UNSPECIFIED TOL.(FAB) FOR ANGULAR IN mm.	
UP TO 10	±1.5°
10 UP TO 50	±0°50'
50 UP TO 120	±0°25'
120 UP TO 400	±0°15'

UNSPECIFIED TOL.(FAB) FOR LINEAR IN mm.	
0.5 UP TO 3	±0.1
3 UP TO 6	±0.2
6 UP TO 30	±0.5
30 UP TO 120	±0.8
120 UP TO 315	±1.2
315 UP TO 1000	±2
1000 UP TO 2000	±3
OVER 2000	±4

UNSPECIFIED TOL.(M/C) FOR ANGULAR IN mm.	
UP TO 10	±1°
10 UP TO 50	±0°30'
50 UP TO 120	±0°20'
120 UP TO 400	±0°10'

UNSPECIFIED TOL.(M/C) FOR LINEAR IN mm.	
0.5 UP TO 3	±0.1
3 UP TO 6	±0.1
6 UP TO 30	±0.2
30 UP TO 120	±0.3
120 UP TO 315	±0.5
315 UP TO 1000	±0.8
1000 UP TO 2000	±1.2
OVER 2000	±2

LIMITS
Gen Tol.: IS 2102

REVISION	DESCRIPTION	DATE	DRN.BY
.	.	.	.
.	.	.	.

www.wipropari.com
1.ALL DIMENSIONS ARE IN mm
2.DO NOT SCALE DRAWING.
3.IF IN DOUBT , ASK TEAM MEMBER
LOCATION : PUNE

© ALL RIGHTS OF REPRODUCTION & DISTRIBUTION ARE RESERVED

WIPRO PARI GROUP

DESCRIPTION: **PLATE 1**
DRAWING TYPE: MACHINING

SURFACE AREA	SURFACE TREATMENT	MACHINING	DESIGN UNIT	DESIGN UNIT CD.	TEAM NO.	SHEET SIZE
33.09 in^2	#	#	WPES	0300	PL-02	A2

REFERENCE DWG. | PART CLASS. B | HEAT TREATMENT ---

DRN.BY	CHKD.BY	APPD.BY	MATERIAL	DRG./PART CODE	REV.	SCALE
2891	03004785	03002882	#	P23Y5B076103	00	1 : 1
09/11/2024	09/11/2024	09/11/2024	NET WEIGHT-Kg 0.51 kg			SHEET 1 OF 1

\\srv01043\ExDM Uploading\2022-23\P23Y5\P23Y5B076103.dft