
NOTE : STANDARD FASTENER TORQUE AS PER STD-DES-01-00 FR-DES-006-00



SECTION A–A
SCALE/ÉCHELLE 1:2

SCALE/ÉCHELLE 1:2


SCALE/ÉCHELLE 1:2

HOLE TABLE				
Hole	X	Y	Size	REMARK
A.1	0.00	0.00	Ø 45.00 mm THRU'	H7 REFER SEC A–A
B.1	−16.25	−32.50	M6 THRU'	
B.2	16.25	−32.50	M6 THRU'	
B.3	−16.25	32.50	M6 THRU'	
B.4	16.25	32.50	M6 THRU'	
C.1	127.00	−20.00	Ø 11.00 mm THRU'	
C.2	267.00	−20.00	Ø 11.00 mm THRU'	
C.3	127.00	80.00	Ø 11.00 mm THRU'	
C.4	267.00	80.00	Ø 11.00 mm THRU'	
D.1	0.00	75.00	Ø 17.50 mm THRU'	

TOLERANCE NOTE :-
1) ALL H7 HOLES C.D SHOULD BE CONTROLLED WITHIN±0.02. / IT7
2) ALL HOLES,TAP & COUNTER BORE C.D,
SHOULD BE CONTROLLED WITHIN ±0.2.

NOTE :–(English)
DEBURR ALL UNSPECIFIED HOLES AND SHARP EDGES.

NOTE :–(French)
ÉBAVUREZ TOUS LES TROUS NON SPÉCIFIÉS ET LES BORDS TRANCHANTS.



SCALE/ÉCHELLE 1:2

NOTE : (English)
MATERIAL: M.S
FINISH: I.Z.B.P. (TRIVALENT)
MACHINING: 3.2
WEIGHT(Kg): 8.91 kg

NOTE :–(French)
MATÉRIEL : M.S
FINITION : I.Z.B.P. (TRIVALENT)
MACHINES : 3.2
POIDS (Kg): 8.91 kg

RESERVED SPACE FOR CONTROLLED COPY

CONTROLLED COPY

NOTE FOR WIPRO PARI DESIGN -REF. ONLY
WEAR DETAILS : N.A.

DEBURR AND REMOVE SHARP EDGES UNLESS SHARP EDGE REQUIREMENT SPECIFIED

UNSP.RADII	UNSP.CHF.
0.5 R	0.5 X 45°

UNSPECIFIED TOL.(FAB) FOR ANGULAR IN mm.	
UP TO 10	±1.5°
10 UP TO 50	±0°50'
50 UP TO 120	±0°25'
120 UP TO 400	±0°15'

UNSPECIFIED TOL.(FAB) FOR LINEAR IN mm.	
0.5 UP TO 3	±0.1
3 UP TO 6	±0.2
6 UP TO 30	±0.5
30 UP TO 120	±0.8
120 UP TO 315	±1.2
315 UP TO 1000	±2
1000 UP TO 2000	±3
OVER 2000	±4

UNSPECIFIED TOL.(M/C) FOR ANGULAR IN mm.	
UP TO 10	±1°
10 UP TO 50	±0°30'
50 UP TO 120	±0°20'
120 UP TO 400	±0°10'

UNSPECIFIED TOL.(M/C) FOR LINEAR IN mm.	
0.5 UP TO 3	±0.1
3 UP TO 6	±0.1
6 UP TO 30	±0.2
30 UP TO 120	±0.3
120 UP TO 315	±0.5
315 UP TO 1000	±0.8
1000 UP TO 2000	±1.2
OVER 2000	±2

LIMITS
Gen Tol.: IS 2102

REVISION	DESCRIPTION	DATE	DRN.BY
.	.	.	.
.	.	.	.

wipro PARI
www.wipropari.com

1.ALL DIMENSIONS ARE IN mm
2.DO NOT SCALE DRAWING.
3.IF IN DOUBT , ASK TEAM MEMBER

LOCATION : PUNE

© ALL RIGHTS OF REPRODUCTION & DISTRIBUTION ARE RESERVED

WIPRO PARI GROUP

DESCRIPTION: SHOCK ABSORBER MTG

DRAWING TYPE: MACHINING

SURFACE AREA	SURFACE TREATMENT	MACHINING	DESIGN UNIT	DESIGN UNIT CD.	TEAM NO.	SHEET SIZE
191.97 in^2	#	#	WPES	0300	PL-02	A2

REFERENCE DWG.	N.A.	PART CLASS.	B	HEAT TREATMENT	N.A.

DRN.BY	CHKD.BY	APPD.BY	MATERIAL	DRG./PART CODE	REV.	SCALE
030006810	03004785	03002882	#	P23Y5B091005	00	1 : 2
08/05/2024	08/05/2024	08/05/2024	NET WEIGHT-Kg 8.91 kg			SHEET 1 OF 1

\\srv01102\ExDM Uploading\2022-23\P23Y5\P23Y5B091005.dft