


NOTE : STANDARD FASTENER TORQUE AS PER STD-DES-01-00 FR-DES-006-00




SCALE/ÉCHELLE 1:2




SCALE/ÉCHELLE 1:2



SECTION A–A
SCALE/ÉCHELLE 1:1



SECTION B–B
SCALE/ÉCHELLE 1:1




SECTION C–C
SCALE/ÉCHELLE 1:1


HOLE TABLE				
Hole	X	Y	Size	REMARK
A.1	0.00	0.00	Ø 12.00 mm THRU'	REF SECTION A–A
A.2	250.20	−169.97	Ø 12.00 mm THRU'	REF SECTION A–A
A.3	290.20	100.03	Ø 12.00 mm THRU'	REF SECTION A–A
1 B.1	305.16	−140.31	M4 THRU'	REF SECTION B–B
1 B.2	69.35	−77.09	M4 THRU'	REF SECTION B–B
1 B.3	389.42	−69.60	M4 THRU'	REF SECTION B–B
1 B.4	153.62	−6.38	M4 THRU'	REF SECTION B–B
C.1	194.20	−114.67	Ø 18.00 mm THRU'	REF SECTION C–C
D.1	140.68	−93.57	Ø 55.00 mm THRU'	REF SECTION D–D
D.2	211.08	−53.57	Ø 55.00 mm THRU'	REF SECTION D–D
D.3	90.68	−13.57	Ø 55.00 mm THRU'	REF SECTION D–D
D.4	327.08	48.93	Ø 55.00 mm THRU'	REF SECTION D–D
E.1	295.53	−51.07	Ø 85.17 mm THRU'	REF SECTION D–D
F.1	7.31	10.75	Ø 5.00 mm THRU'	H7
G.1	385.42	17.40	Ø 13.99 mm THRU'	REF SECTION E–E

TOLERANCE NOTE :– (English)
1) ALL H7 HOLES C.D SHOULD BE CONTROLLED WITHIN +/– 0.02. / IT7
2) ALL HOLES,TAP & COUNTER BORE C.D. SHOULD BE CONTROLLED WITHIN +/– 0.1


NOTE DE TOLERANCE :– (French)
1) TOUT TROU H7 C.D DOIT ÊTRE CONTRÔLÉ SOUS +/– 0.02 / IT7
2) TOUT TROU ET CONTRE–ALÉSAGE C.D, DOIT ÊTRE CONTRÔLÉ SOUS +/– 0.1



SECTION E–E
SCALE/ÉCHELLE 1:2



SCALE/ÉCHELLE 1:2



SECTION D–D
SCALE/ÉCHELLE 1:1

HEAT TREATMENT :–
1) TO BE TOUGHENED UPTO 28–32 HRC.
2) RETAPPING TO BE DONE AFTER SURFACE TREATMENT AT SUPPLIER END.(IF APPLICABLE)

NOTE :–(English)
DEBURR ALL UNSPECIFIED HOLES AND SHARP EDGES.

NOTE :–(French)
ÉBAVUREZ TOUS LES TROUS NON SPÉCIFIÉS ET LES BORDS TRANCHANTS.

NOTE : (English)
MATERIAL: C45
FINISH: I.Z.B.P. (TRIVALENT)
MACHINING: 3.2 (0.8)
WEIGHT(Kg): 7.70 kg

NOTE :–(French)
MATÉRIEL : C45
FINITION : I.Z.B.P. (TRIVALENT)
MACHINES : 3.2 (0.8)
POIDS (Kg): 7.70 kg

RESERVED SPACE FOR CONTROLLED COPY

DEBURR AND REMOVE SHARP EDGES UNLESS SHARP EDGE REQUIREMENT SPECIFIED	
UNSP RADII 0.5 R	UNSP CHF. 0.5 X 45°
UNSPECIFIED TOL (FAB) FOR ANGULAR IN mm	
UP TO 10	±1.5°
10 UP TO 50	±0°50'
50 UP TO 120	±0°25'
120 UP TO 400	±0°15'
UNSPECIFIED TOL (FAB) FOR LINEAR IN mm	
0.5 UP TO 3	±0.1
3 UP TO 6	±0.2
6 UP TO 30	±0.5
30 UP TO 120	±0.8
120 UP TO 315	±1.2
315 UP TO 1000	±2
1000 UP TO 2000	±3
OVER 2000	±4
UNSPECIFIED TOL (MFC) FOR ANGULAR IN mm	
UP TO 10	±1°
10 UP TO 50	±0°30'
50 UP TO 120	±0°20'
120 UP TO 400	±0°10'
UNSPECIFIED TOL (MFC) FOR LINEAR IN mm	
0.5 UP TO 3	±0.1
3 UP TO 6	±0.1
6 UP TO 30	±0.2
30 UP TO 120	±0.3
120 UP TO 315	±0.5
315 UP TO 1000	±0.8
1000 UP TO 2000	±1.2
OVER 2000	±2

LIMITS
Gen Tol.: IS 2102

REVISION	DESCRIPTION	DATE	DRN.BY
1	HOLE SIZE UPDATE	01/07/24	03004476

WIPRO PARI GROUP
www.wipropari.com
DESCRIPTION: OP 1050 - ITEM 1
DRAWING TYPE: MACHINING

1.ALL DIMENSIONS ARE IN mm
2.DO NOT SCALE DRAWING.
3.IF IN DOUBT ASK TEAM MEMBER

SURFACE AREA	SURFACE TREATMENT	MACHINING	DESIGN UNIT	DESIGN UNIT CD.	TEAM NO.	SHEET SIZE
274.75 in^2	#	#	WPES	0300	PL-02	A1

REFERENCE DWG.	—	PART CLASS.	B	HEAT TREATMENT	REF NOTE

LOCATION : PUNE

DRN.BY	CHKD.BY	APPD.BY	MATERIAL	DRG./PART CODE	REV.	SCALE
03006751	03004785	03002882	#	P23Y5B099001	01	1 : 2
06/07/2024	06/07/2024	06/07/2024	NET WEIGHT-Kg 7.70 kg			SHEET 1 OF 1

© ALL RIGHTS OF REPRODUCTION & DISTRIBUTION ARE RESERVED

NOTE FOR WIPRO PARI DESIGN -REF. ONLY
WEAR DETAILS : N.A.

\\srv01043\E:\DM Uploading \2022-23\P23Y5\P23Y5B099001.dft