NOTE : STANDARD FASTENER TORQUE AS PER STD-DES-01


FR-DES-006-01


T + S NOTE :


H.T.PROCESS	: XXXXX
HARDNESS & DEPTH	: XXXXX
FINISH & DEPTH	: XXXXX
TEST COUPON SIZE	: 75 X60X49 (20mmLENGTH - 01NOS)
WELD CLASS	: B IF APPLICABLE


MTC REPORT REQURIED
NON DESTRUCTIVE TESTING (IF APPLICABLE)


RAW MATERIAL	HEAT TREATMENT	FINISH COMPOMENT
UT	DP+UT	MPI












SECTION A-A
SCALE 1:1



SECTION B-B
SCALE 1:1

DEBURR AND REMOVE SHARP EDGES UNLESS SHARP EDGE REQUIREMENT SPECIFIED	
UNSP.RADII 0.5 R	UNSP.CHF. 0.5 X 45°
UNSPECIFIED TOL.(FAB) FOR ANGULAR IN mm.	
UP TO 10	±1.5°
10 UP TO 50	±0°50'
50 UP TO 120	±0°25'
120 UP TO 400	±0°15'
UNSPECIFIED TOL.(FAB) FOR LINEAR IN mm.	
0.5 UP TO 3	±0.1
3 UP TO 6	±0.2
6 UP TO 30	±0.5
30 UP TO 120	±0.8
120 UP TO 315	±1.2
315 UP TO 1000	±2
1000 UP TO 2000	±3
OVER 2000	±4
UNSPECIFIED TOL.(M/C) FOR ANGULAR IN mm.	
UP TO 10	±1°
10 UP TO 50	±0°30'
50 UP TO 120	±0°20'
120 UP TO 400	±0°10'
UNSPECIFIED TOL.(M/C) FOR LINEAR IN mm.	
0.5 UP TO 3	±0.1
3 UP TO 6	±0.1
6 UP TO 30	±0.2
30 UP TO 120	±0.3
120 UP TO 315	±0.5
315 UP TO 1000	±0.8
1000 UP TO 2000	±1.2
OVER 2000	±2
LIMITS	
Gen Tol.: IS 2102	

REVISION	DESCRIPTION	DATE	DRN.BY

wipro pari
www.wipropari.com

1.ALL DIMENSIONS ARE IN mm
2.DO NOT SCALE DRAWING.
3.IF IN DOUBT , ASK TEAM MEMBER
LOCATION : ---

© ALL RIGHTS OF REPRODUCTION & DISTRIBUTION ARE RESERVED

CONTROLLED COPY

RESERVED STAMP COPY

WIPRO PARI GROUP

DESCRIPTION: ATB GRIPPER JAW RH

DRAWING TYPE: MACHINING

SURFACE AREA	SURFACE TREATMENT	MACHINING	DESIGN UNIT	DESIGN UNIT CD.	TEAM NO.	SHEET SIZE
15.00 in^2	SELF-ANODIZING	▽▽	WPES	0300	PL-02	A3

REFERENCE DWG.	PART CLASS.	HEAT TREATMENT
---	T+S	---

DRN.BY	CHKD.BY	APPD.BY	MATERIAL	DRG./PART CODE	REV.	SCALE
80151477	80151522	--- 80151522	Aluminum, HE30/6082	P23Y5B151021	00	1 :
09/02/26	09/02/26	09/02/26	NET WEIGHT-Kg 0.07 kg			SHEET 1 OF 1

NOTE FOR WIPRO PARI DESIGN -REF. ONLY
WEAR DETAILS : MW

Draft2