

NOTE : STANDARD FASTENER TORQUE AS PER STD-DES-01-00 FR-DES-006-00


HOLE TABLE				
Hole	X	Y	Size	REMARK
A.1	0.00	0.00	Ø 35.00 mm THRU'	REF SEC A–A
B.1	–27.50	–10.00	Ø 6.60 mm THRU' C'BORE Ø 11.00 mm – 9.00 mm DEEP	
B.2	–27.50	10.00	Ø 6.60 mm THRU' C'BORE Ø 11.00 mm – 9.00 mm DEEP	
B.3	27.50	–10.00	Ø 6.60 mm THRU' C'BORE Ø 11.00 mm – 9.00 mm DEEP	
B.4	27.50	10.00	Ø 6.60 mm THRU' C'BORE Ø 11.00 mm – 9.00 mm DEEP	REF SEC A–A
C.1	–44.50	44.50	Ø 11.00 mm THRU' C'BORE Ø 18.00 mm – 10.80 mm DEEP	REF SEC A–A
C.2	44.50	44.50	Ø 11.00 mm THRU' C'BORE Ø 18.00 mm – 10.80 mm DEEP	REF SEC A–A
C.3	44.50	–44.50	Ø 11.00 mm THRU' C'BORE Ø 18.00 mm – 10.80 mm DEEP	REF SEC A–A
C.4	–44.50	–44.50	Ø 11.00 mm THRU' C'BORE Ø 18.00 mm – 10.80 mm DEEP	REF SEC A–A



SCALE/ÉCHELLE 1:2



SECTION A–A
SCALE/ÉCHELLE 1:2



SCALE/ÉCHELLE 1:2

TOLERANCE NOTE :– (English)
1) ALL H7 HOLES C.D SHOULD BE CONTROLLED WITHIN +/– 0.02. / IT7
2) ALL HOLES,TAP & COUNTER BORE C.D,
SHOULD BE CONTROLLED WITHIN +/– 0.1

NOTE DE TOLERANCE :– (French)
1) TOUT TROU H7 C.D DOIT ÊTRE CONTRÔLÉ SOUS +/– 0.02 / IT7
2) TOUT TROU ET CONTRE–ALÉSAGE C.D,
DOIT ÊTRE CONTROLÉ SOUS +/– 0.1

NOTE : (English)
MATERIAL: M.S.
FINISH: I.Z.B.P. (TRIVALENT)
MACHINING: 3.2
WEIGHT(Kg): 1.68 kg

NOTE :–(French)
MATÉRIEL : M.S.
FINITION : I.Z.B.P. (TRIVALENT)
MACHINES : 3.2
POIDS (Kg): 1.68 kg

RESERVED SPACE FOR STAMP

CONTROLLED COPY

NOTE FOR WIPRO PARI DESIGN -REF. ONLY
WEAR DETAILS : NA

DEBURR AND REMOVE SHARP EDGES UNLESS SHARP EDGE REQUIREMENT SPECIFIED

UNSP.RADII	UNSP.CHF.
0.5 R	0.5 X 45°

UNSPECIFIED TOL.(FAB) FOR ANGULAR IN mm	
UP TO 10	±1.5°
10 UP TO 50	±0°50'
50 UP TO 120	±0°25'
120 UP TO 400	±0°15'
UNSPECIFIED TOL.(FAB) FOR LINEAR IN mm	
0.5 UP TO 3	±0.1
3 UP TO 6	±0.2
6 UP TO 30	±0.5
30 UP TO 120	±0.8
120 UP TO 315	±1.2
315 UP TO 1000	±2
1000 UP TO 2000	±3
OVER 2000	±4
UNSPECIFIED TOL.(M/C) FOR ANGULAR IN mm	
UP TO 10	±1°
10 UP TO 50	±0°30'
50 UP TO 120	±0°20'
120 UP TO 400	±0°10'
UNSPECIFIED TOL.(M/C) FOR LINEAR IN mm	
0.5 UP TO 3	±0.1
3 UP TO 6	±0.1
6 UP TO 30	±0.2
30 UP TO 120	±0.3
120 UP TO 315	±0.5
315 UP TO 1000	±0.8
1000 UP TO 2000	±1.2
OVER 2000	±2
LIMITS	
Gen Tol.: IS 2102	

REVISION	DESCRIPTION	DATE	DRN.BY

wipro PARI
www.wipropari.com

WIPRO PARI GROUP

1.ALL DIMENSIONS ARE IN mm
2.DO NOT SCALE DRAWING.
3.IF IN DOUBT , ASK TEAM MEMBER
LOCATION : PUNE

© ALL RIGHTS OF REPRODUCTION & DISTRIBUTION ARE RESERVED

DESCRIPTION					DRAWING TYPE
GRIPPER CYL MTG PL					MACHINING
SURFACE AREA	SURFACE TREATMENT	MACHINING	DESIGN UNIT	DESIGN UNIT CD.	TEAM NO.	SHEET SIZE
60.66 in^2	#	#	WPES	0300	PL-02	A2
REFERENCE DWG. ---		PART CLASS. B	HEAT TREATMENT ---			

DRN.BY	CHKD.BY	APPD.BY	MATERIAL	DRG./PART CODE	REV.	SCALE
80151477	80151522	80151522	#	P23Y5B154020	00	1 : 2
16/03/2026	16/03/2026	16/03/2026	NET WEIGHT-Kg 1.68 kg			SHEET 1 OF 1

\\srv01102\Ex-DM Uploading\2022-23\P23Y5\P23Y5B154020.dft