NOTE : STANDARD FASTENER TORQUE AS PER STD-DES-01-00 FR-DES-006-00


H.T.PROCESS : REF NOTE HARDNESS & DEPTH :REF NOTE FINISH & DEPTH : REF NOTE TEST COUPON SIZE :Ø15 (20mmLENGTH – 01NOS) WELD CLASS : B IF APPLICABLE	MTC REPORT REQURIED NON DESTRUCTIVE TESTING (IF APPLICABLE) RAW MATERIAL UT | HEAT TREATMENT DP+UT | FINISH COMPOMENT MPI

NOTE :–(English)
DEBURR ALL UNSPECIFIED HOLES AND SHARP EDGES.


NOTE :–(French)
ÉBAVUREZ TOUS LES TROUS NON SPÉCIFIÉS ET LES BORDS TRANCHANTS.

HEAT TREATMENT NOTE :– (English)
1) TO BE CASE HARDENED UPTO 56~60 HRC.
2) CASE DEPTH 0.8~1.2mm.
3) THREADS TO BE KEEP SOFT.
4) RETAPPING TO BE DONE AFTER SURFACE TREATMENT AT SUPPLIER END.(IF APPLICABLE)


NOTE POUR LE TRAITEMENT DE LA CHALEUR :–(French)
1) À ENDURCIR JUSQUÐA 56~60 HRC.
2) PROFONDEUR DU TRAITEMENT 0.8 ~ 1.2MM.
3) MAINTENIR LES FILTAGES PROPRE
4) RE–TARAUDAGE À FAIRE APRÈS TRAITEMENT DE SURFACE CHEZ LE FOURNISSEUR (SÐIL Y A LIEU)




TOP VIEW




DETAIL D
SCALE/ÉCHELLE 4:1




FRONT VIEW




SECTION E–E
SCALE/ÉCHELLE 2:1



SECTION C–C
SCALE/ÉCHELLE 2:1 330°





BOTTOM VIEW

NOTE FOR WIPRO PARI DESIGN -REF. ONLY
WEAR DETAILS : N.A.

NOTE : (English)
MATERIAL: 20MnCr5
FINISH: I.Z.B.P. (TRIVALENT)
MACHINING: 3.2 (0.8)
WEIGHT(Kg): 0.15 kg

NOTE :–(French)
MATÉRIEL : 20MnCr5
FINITION : I.Z.B.P. (TRIVALENT)
MACHINES : 3.2 (0.8)
POIDS (Kg): 0.15 kg

RESERVED SPACE FOR CONTROL
CONTROLLED COPY

DEBURR AND REMOVE SHARP EDGES UNLESS SHARP EDGE REQUIREMENT SPECIFIED.

UNSP.RADII 0.5 R	UNSP.CHF. 0.5 X 45°

UNSPECIFIED TOL.(FAB) FOR ANGULAR IN mm

UP TO 10	±1.5°
10 UP TO 50	±0°50'
50 UP TO 120	±0°25'
120 UP TO 400	±0°15'

UNSPECIFIED TOL.(FAB) FOR LINEAR IN mm

0.5 UP TO 3	±0.1
3 UP TO 6	±0.2
6 UP TO 30	±0.5
30 UP TO 120	±0.8
120 UP TO 315	±1.2
315 UP TO 1000	±2
1000 UP TO 2000	±3
OVER 2000	±4

UNSPECIFIED TOL.(M/C) FOR ANGULAR IN mm

UP TO 10	±1°
10 UP TO 50	±0°30'
50 UP TO 120	±0°20'
120 UP TO 400	±0°10'

UNSPECIFIED TOL.(M/C) FOR LINEAR IN mm

0.5 UP TO 3	±0.1
3 UP TO 6	±0.1
6 UP TO 30	±0.2
30 UP TO 120	±0.3
120 UP TO 315	±0.5
315 UP TO 1000	±0.8
1000 UP TO 2000	±1.2
OVER 2000	±2

LIMITS Gen Tol.: IS 2102

REVISION	DESCRIPTION	DATE	DRN.BY

WIPRO PARI GROUP
www.wipropari.com
1.ALL DIMENSIONS ARE IN mm
2.DO NOT SCALE DRAWING.
3.IF IN DOUBT , ASK TEAM MEMBER
LOCATION : PUNE

DESCRIPTION: **LOCATING PIN - 2**
DRAWING TYPE: MACHINING

SURFACE AREA	SURFACE TREATMENT	MACHINING	DESIGN UNIT	DESIGN UNIT CD.	TEAM NO	SHEET SIZE
9.48 in^2	#	#	WPP	0100	PL-02	A1

REFERENCE DWG.	PART CLASS.T+S	HEAT TREATMENT	REF.NOTE
P23Y5B154460			

DRN.BY	CHKD.BY	APPD.BY	MATERIAL	DRG./PART CODE	REV.	SCALE
03002987	5489	5489	#	P23Y5B154473	00	2 : 1
10/07/2024	10/07/2024	10/07/2024	NET WEIGHT-Kg 0.15 kg			SHEET 1 OF 1

© ALL RIGHTS OF REPRODUCTION & DISTRIBUTION ARE RESERVED

\\srv01043\E-cdm Uploading\2022-23\P23Y5\P23Y5B154473.dft