

NOTE : STANDARD FASTENER TORQUE AS PER STD-DES-01-00 FR-DES-006-00


TOLERANCE NOTE :-
1) ALL H7 HOLES C.D SHOULD BE CONTROLLED WITHIN=0.02. / IT7
2) ALL HOLES,TAP & COUNTER BORE C.D,
SHOULD BE CONTROLLED WITHIN =0.2.




SCALE/ÉCHELLE 1:1




SCALE/ÉCHELLE 1:1



SECTION A-A
SCALE/ECHELLE 1:1



DETAIL B
SCALE/ECHELLE 2:1



SCALE/ÉCHELLE 1:2

HOLE TABLE				
Hole	X	Y	Size	REMARK
A.1	0.00	0.00	Ø 6.00 mm THRU'	H7-REF SEC A-A
A.2	-35.00	226.00	Ø 6.00 mm THRU'	H7-REF SEC A-A
A.3	9.00	226.00	Ø 6.00 mm THRU'	H7-REF SEC A-A
A.4	52.00	200.00	Ø 6.00 mm THRU'	H7-REF SEC A-A
A.5	62.00	212.00	Ø 6.00 mm THRU'	H7-REF SEC A-A
A.6	52.00	2.50	Ø 6.00 mm THRU'	H7-REF SEC A-A
A.7	0.00	180.00	Ø 6.00 mm THRU'	H7-REF SEC A-A
A.8	62.00	14.50	Ø 6.00 mm THRU'	H7-REF SEC A-A
B.1	-13.00	0.00	M5 THRU'	
B.2	-13.00	60.00	M5 THRU'	
B.3	-13.00	120.00	M5 THRU'	
B.4	-13.00	180.00	M5 THRU'	
B.5	57.00	60.00	M5 THRU'	
B.6	57.00	120.00	M5 THRU'	
B.7	106.00	56.00	M5 THRU'	
B.8	128.00	56.00	M5 THRU'	
B.9	106.00	156.00	M5 THRU'	
B.10	128.00	156.00	M5 THRU'	
C.1	-35.00	237.00	M6 THRU'	
C.2	9.00	237.00	M6 THRU'	
C.3	-35.00	253.00	M6 THRU'	
C.4	9.00	253.00	M6 THRU'	
C.5	52.00	212.00	M6 THRU'	
C.6	62.00	200.00	M6 THRU'	
C.7	52.00	14.50	M6 THRU'	
C.8	62.00	2.50	M6 THRU'	

NOTE :-(English)
DEBURR ALL UNSPECIFIED HOLES AND SHARP EDGES.

NOTE :-(French)
ÉBAVUREZ TOUS LES TROUS NON SPÉCIFIÉS ET LES BORDS TRANCHANTS.

NOTE FOR WIPRO PARI DESIGN -REF. ONLY
WEAR DETAILS : NA

NOTE : (English)
MATERIAL: M.S.
FINISH: I.Z.B.P. (TRIVALENT)
MACHINING: 3.2
WEIGHT(Kg): 4.74 kg

NOTE :-(French)
MATÉRIEL : M.S.
FINITION : I.Z.B.P. (TRIVALENT)
MACHINES : 3.2
POIDS (Kg): 4.74 kg

RESERVED SPACE FOR CONTROLLED COPY

DEBURR AND REMOVE SHARP EDGES UNLESS SHARP EDGE REQUIREMENT SPECIFIED.	
UNSP.RADII 0.5 R	UNSP.CHF. 0.5 X 45°
UNSPECIFIED TOL.(FAB) FOR ANGULAR IN mm	
UP TO 10	±1.5°
10 UP TO 50	±0°50'
50 UP TO 120	±0°25'
120 UP TO 400	±0°15'
UNSPECIFIED TOL.(FAB) FOR LINEAR IN mm	
0.5 UP TO 3	±0.1
3 UP TO 6	±0.2
6 UP TO 30	±0.5
30 UP TO 120	±0.8
120 UP TO 315	±1.2
315 UP TO 1000	±2
1000 UP TO 2000	±3
OVER 2000	±4
UNSPECIFIED TOL.(MIC) FOR ANGULAR IN mm	
UP TO 10	±1°
10 UP TO 50	±0°30'
50 UP TO 120	±0°20'
120 UP TO 400	±0°10'
UNSPECIFIED TOL.(MIC) FOR LINEAR IN mm	
0.5 UP TO 3	±0.1
3 UP TO 6	±0.1
6 UP TO 30	±0.2
30 UP TO 120	±0.3
120 UP TO 315	±0.5
315 UP TO 1000	±0.8
1000 UP TO 2000	±1.2
OVER 2000	±2
LIMITS	
Gen Tol.: IS 2102	

REVISION	DESCRIPTION	DATE	DRN.BY

wipro PARI
www.wipropari.com

WIPRO PARI GROUP

DESCRIPTION: BASE PLATE
DRAWING TYPE: MACHINING

1.ALL DIMENSIONS ARE IN mm
2.DO NOT SCALE DRAWING.
3.IF IN DOUBT , ASK TEAM MEMBER
LOCATION : PUNE

SURFACE AREA	SURFACE TREATMENT	MACHINING	DESIGN UNIT	DESIGN UNIT CD.	TEAM NO	SHEET SIZE
214.11 in^2	#	#	WPES	0300	PL-02	A1

REFERENCE DWG. --- | PART CLASS. B | HEAT TREATMENT ---

DRN.BY	CHKD.BY	APPD.BY	MATERIAL	DRG./PART CODE	REV.	SCALE
03006330	03004785	03002882	#	P23Y5B154501	00	1 : 2
07/03/2024	07/03/2024	07/03/2024	NET WEIGHT-Kg 4.74 kg			SHEET 1 OF 1

© ALL RIGHTS OF REPRODUCTION & DISTRIBUTION ARE RESERVED

\\srv01102\E-cdm Uploading\2022-23\P23Y5\P23Y5B154501.dft