NOTE : STANDARD FASTENER TORQUE AS PER STD-DES-01-00 FR-DES-006-00





SECTION A-A
SCALE 1:1

NOTE:-
1) # USE STD. DIA. 30 g6 En- 8(D) BRIGHT BAR
2) STRAIGHTNESS:- 0.2mm/1000mm MAX.
3) RUNOUT:- 0.1mm/1000mm.
4) $ HARD CHROME PLATING 15 TO 20 MICRONS, HARDNESS 850 TO 1000 HV.
5) SURFACE FINISH:- Ra 0.2 TO 0.3 MICRONS.

DEBURR AND REMOVE SHARP EDGES UNLESS SHARP EDGE REQUIREMENT SPECIFIED	
UNSP.RADII 0.5 R	UNSP.CHF. 0.5 X 45°
UNSPECIFIED TOL.(FAB) FOR ANGULAR IN mm.	
UP TO 10	±1.5°
10 UP TO 50	±0°50'
50 UP TO 120	±0°25'
120 UP TO 400	±0°15'
UNSPECIFIED TOL.(FAB) FOR LINEAR IN mm.	
0.5 UP TO 3	±0.1
3 UP TO 6	±0.2
6 UP TO 30	±0.5
30 UP TO 120	±0.8
120 UP TO 315	±1.2
315 UP TO 1000	±2
1000 UP TO 2000	±3
OVER 2000	±4
UNSPECIFIED TOL.(M/C) FOR ANGULAR IN mm.	
UP TO 10	±1°
10 UP TO 50	±0°30'
50 UP TO 120	±0°20'
120 UP TO 400	±0°10'
UNSPECIFIED TOL.(M/C) FOR LINEAR IN mm.	
0.5 UP TO 3	±0.1
3 UP TO 6	±0.1
6 UP TO 30	±0.2
30 UP TO 120	±0.3
120 UP TO 315	±0.5
315 UP TO 1000	±0.8
1000 UP TO 2000	±1.2
OVER 2000	±2
LIMITS	
Gen Tol.: IS 2102	

REVISION	DESCRIPTION	DATE	DRN.BY

RESERVED SPACE FOR CONTROLLED COPY STAMP

CONTROLLED COPY

NOTE FOR WIPRO PARI DESIGN -REF. ONLY
WEAR DETAILS : NA

www.wipropari.com

1.ALL DIMENSIONS ARE IN mm
2.DO NOT SCALE DRAWING.
3.IF IN DOUBT , ASK TEAM MEMBER
LOCATION : PUNE

© ALL RIGHTS OF REPRODUCTION & DISTRIBUTION ARE RESERVED

WIPRO PARI GROUP

DESCRIPTION: **SHAFT**

DRAWING TYPE: MACHINING

SURFACE AREA	SURFACE TREATMENT	MACHINING	DESIGN UNIT	DESIGN UNIT CD.	TEAM NO.	SHEET SIZE
133.00 in^2	HARD CHROME PLATING	▽▽(▽▽▽)	WPP	0100	PL-01	A3

REFERENCE DWG.	PART CLASS.	HEAT TREATMENT
UEP000006097	B	---

DRN.BY	CHKD.BY	APPD.BY	MATERIAL	DRG./PART CODE	REV.	SCALE
01006879	03006174	03002519	EN8/EN9	P23N3D010118	00	1 : 5
25/04/2024	25/04/2024	25/04/2024	NET WEIGHT-Kg 4.74 kg			SHEET 1 OF 1

\\srv01042\eXDM Uploading\2023-24\P23N3\DRIVE SHAFT-W550.dft