


NOTE : STANDARD FASTENER TORQUE AS PER STD-DES-01-00 FR-DES-006-00




SECTION A–A
SCALE/ÉCHELLE 1:1




SCALE/ÉCHELLE 1:1



DETAIL B
SCALE/ÉCHELLE 5:1



DETAIL C
SCALE/ÉCHELLE 2:1



SCALE/ÉCHELLE 1:1

NOTE :–(English)
DEBURR ALL UNSPECIFIED HOLES AND SHARP EDGES.

NOTE :–(French)
ÉBAVUREZ TOUS LES TROUS NON SPÉCIFIÉS ET LES BORDS TRANCHANTS.

NOTE T + S :– (English)

HEAT TREATMANT PROCESS:REF NOTE HARDNESS & DEPTH : REF NOTE FINISH & DEPTH :REF NOTE TEST COUPON SIZE :DIA 110 X 75L(20mmLENGTH–01NOS) WELD CLASS : B IF APPLICABLE	MATERIAL TEST CERTIFICATE REPORT REQURIED NON DESTRUCTIVE TESTING RAW MATERIAL ULTRASONIC TEST | HEAT TREATMENT DIE PENETRATION TEST + ULTRASONIC TEST | FINISH COMPOMENT MAGNETIC PARTICLE INSPECTION

NOTE T + S :– (French)

PROCÉDÉ H.T. : XXXXXX DURETÉ ET PROFONDEUR : XXXX HRc FINITION ET PROFONDEUR : XXXXXXXX DIMENSION TEST COUPON :XXXX(20mmLENGTH–01NOS) CLASSE D'USINAGE : B IF APPLICABLE	RAPPORT DU CTM REQUIS CONTRÔLE NON DESTRUCTIF MATIÈRE PREMIÈRE TEST ULTRASONIQUE | TRAITEMENT DE LA CHALEUR TEST DE PÉNÉTRATION DE MATRICE + TEST ULTRASONIQUE | COMPOSANT DE FINITION INSPECTION MAGNÉTIQUE DES PARTICULES

HEAT TREATMENT NOTE :–
1) TO BE CASE HARDENED UPTO 56~60 HRC.
2) CASE DEPTH 0.8~1.2mm.
3) THREADS TO BE KEEP SOFT.
4) RETAPPING TO BE DONE AFTER SURFACE TREATMENT AT SUPPLIER END.(IF APPLICABLE)

NOTE : (English)
MATERIAL: 20MnCr5
FINISH: I.Z.B.P. (TRIVALENT)
MACHINING: 3.2
WEIGHT(Kg): 1.06 kg

NOTE :–(French)
MATÉRIEL : 20MnCr5
FINITION : I.Z.B.P. (TRIVALENT)
MACHINES : 3.2
POIDS (Kg): 1.06 kg

RESERVED SPACE FOR STAMP

CONTROLLED COPY

NOTE FOR WIPRO PARI DESIGN -REF. ONLY
WEAR DETAILS : M.W.

DEBURR AND REMOVE SHARP EDGES UNLESS SHARP EDGE REQUIREMENT SPECIFIED

UNSP.RADII	UNSP.CHF.
0.5 R	0.5 X 45°

UNSPECIFIED TOL.(FAB) FOR ANGULAR IN mm.	
UP TO 10	±1.5°
10 UP TO 50	±0°50'
50 UP TO 120	±0°25'
120 UP TO 400	±0°15'

UNSPECIFIED TOL.(FAB) FOR LINEAR IN mm.	
0.5 UP TO 3	±0.1
3 UP TO 6	±0.2
6 UP TO 30	±0.5
30 UP TO 120	±0.8
120 UP TO 315	±1.2
315 UP TO 1000	±2
1000 UP TO 2000	±3
OVER 2000	±4

UNSPECIFIED TOL.(M/C) FOR ANGULAR IN mm.	
UP TO 10	±1°
10 UP TO 50	±0°30'
50 UP TO 120	±0°20'
120 UP TO 400	±0°10'

UNSPECIFIED TOL.(M/C) FOR LINEAR IN mm.	
0.5 UP TO 3	±0.1
3 UP TO 6	±0.1
6 UP TO 30	±0.2
30 UP TO 120	±0.3
120 UP TO 315	±0.5
315 UP TO 1000	±0.8
1000 UP TO 2000	±1.2
OVER 2000	±2

LIMITS
Gen Tol.: IS 2102

REVISION	DESCRIPTION	DATE	DRN.BY
1	TOLERANCE ADDED	08/10/2024	03005829

wipro PARI
www.wipropari.com

1.ALL DIMENSIONS ARE IN mm
2.DO NOT SCALE DRAWING.
3.IF IN DOUBT , ASK TEAM MEMBER
LOCATION : PUNE

© ALL RIGHTS OF REPRODUCTION & DISTRIBUTION ARE RESERVED

WIPRO PARI GROUP

DESCRIPTION: **CENTER LOCATOR**
DRAWING TYPE: MACHINING

SURFACE AREA	SURFACE TREATMENT	MACHINING	DESIGN UNIT	DESIGN UNIT CD.	TEAM NO.	SHEET SIZE
74.62 in^2	#	#	WPES	0300	PL-02	A2

REFERENCE DWG. N.A. | PART CLASS. T+S | HEAT TREATMENT N.A.

DRN.BY	CHKD.BY	APPD.BY	MATERIAL	DRG./PART CODE	REV.	SCALE
03006810	03005766	03002882	#	P23Y5B091032	01	1 : 1
08/10/2024	08/10/2024	08/10/2024	NET WEIGHT-Kg 1.06 kg			SHEET 1 OF 1

\\srv01102\ExDM Uploading\2022-23\P23Y5\P23Y5B091032.dft