

NOTE : STANDARD FASTENER TORQUE AS PER STD-DES-01-00 FR-DES-006-00





SECTION A-A
SCALE 2:1

DEBURR AND REMOVE SHARP EDGES UNLESS SHARP EDGE REQUIREMENT SPECIFIED	
UNSP.RADII 0.5 R	UNSP.CHF. 0.5 X 45°
UNSPECIFIED TOL.(FAB) FOR ANGULAR IN mm.	
UP TO 10	±1.5°
10 UP TO 50	±0°50'
50 UP TO 120	±0°25'
120 UP TO 400	±0°15'
UNSPECIFIED TOL.(FAB) FOR LINEAR IN mm.	
0.5 UP TO 3	±0.1
3 UP TO 6	±0.2
6 UP TO 30	±0.5
30 UP TO 120	±0.8
120 UP TO 315	±1.2
315 UP TO 1000	±2
1000 UP TO 2000	±3
OVER 2000	±4
UNSPECIFIED TOL.(M/C) FOR ANGULAR IN mm.	
UP TO 10	±1°
10 UP TO 50	±0°30'
50 UP TO 120	±0°20'
120 UP TO 400	±0°10'
UNSPECIFIED TOL.(M/C) FOR LINEAR IN mm.	
0.5 UP TO 3	±0.1
3 UP TO 6	±0.1
6 UP TO 30	±0.2
30 UP TO 120	±0.3
120 UP TO 315	±0.5
315 UP TO 1000	±0.8
1000 UP TO 2000	±1.2
OVER 2000	±2
LIMITS	
Gen Tol.: IS 2102	

1

H.T.PROCESS : TOUGHENED
HARDNESS & DEPTH : 28~32 HRC.
FINISH & DEPTH : QPQ, 20 ~ 25 MICRON
TEST COUPON SIZE : (∅35 X 10 LENGTH QTY - 02NOS)
WELD CLASS : B IF APPLICABLE

MTC REPORT REQURIED
NON DESTRUCTIVE TESTING

RAW MATERIAL UT	HEAT TREATMENT DP+UT	FINISH COMPOMENT MPI

NOTE :
MATERIAL : EN-19
FINISH : QPQ
MACHINING : ▽▽(▽▽▽)

1

NOTE FOR WIPRO PARI DESIGN -REF. ONLY
WEAR DETAILS : N.A

RESERVED SPACE
CONTROLLED COPY
STAMP

REVISION	DESCRIPTION	DATE	DRN.BY
1	HEAT TREATMENT NOTE	04-11-2025	PCS

WIPRO PARI GROUP

www.wipropari.com

1.ALL DIMENSIONS ARE IN mm
2.DO NOT SCALE DRAWING.
3.IF IN DOUBT , ASK TEAM MEMBER
LOCATION : PUNE

© ALL RIGHTS OF REPRODUCTION & DISTRIBUTION ARE RESERVED

DESCRIPTION						DRAWING TYPE
PIN						MACHINING
SURFACE AREA	SURFACE TREATMENT	MACHINING	DESIGN UNIT	DESIGN UNIT CD.	TEAM NO.	SHEET SIZE
10.76 in^2	#	#	WPP	0100	PL-01	A2
REFERENCE DWG. --		PART CLASS. B	HEAT TREATMENT --			

DRN.BY	CHKD.BY	APPD.BY	MATERIAL	DRG./PART CODE	REV.	SCALE
PCS	NITIN G	SANDEEP J	#	P24DKA011012	01	2 : 1
04/11/2025	04/11/2025	04/11/2025	NET WEIGHT-Kg 0.24 kg			SHEET 1 OF 1

\\srv01101\E:\DM Uploading\2024-25\P24DKP24DKA011012.dft