


NOTE : STANDARD FASTENER TORQUE AS PER STD-DES-01

FR-DES-006-01







DEBURR AND REMOVE SHARP EDGES UNLESS SHARP EDGE REQUIREMENT SPECIFIED	
UNSP.RADII 0.5 R	UNSP.CHF. 0.5 X 45°
UNSPECIFIED TOL.(FAB) FOR ANGULAR IN mm.	
UP TO 10	±1.5°
10 UP TO 50	±0°50'
50 UP TO 120	±0°25'
120 UP TO 400	±0°15'
UNSPECIFIED TOL.(FAB) FOR LINEAR IN mm.	
0.5 UP TO 3	±0.1
3 UP TO 6	±0.2
6 UP TO 30	±0.5
30 UP TO 120	±0.8
120 UP TO 315	±1.2
315 UP TO 1000	±2
1000 UP TO 2000	±3
OVER 2000	±4
UNSPECIFIED TOL.(M/C) FOR ANGULAR IN mm.	
UP TO 10	±1°
10 UP TO 50	±0°30'
50 UP TO 120	±0°20'
120 UP TO 400	±0°10'
UNSPECIFIED TOL.(M/C) FOR LINEAR IN mm.	
0.5 UP TO 3	±0.1
3 UP TO 6	±0.1
6 UP TO 30	±0.2
30 UP TO 120	±0.3
120 UP TO 315	±0.5
315 UP TO 1000	±0.8
1000 UP TO 2000	±1.2
OVER 2000	±2
LIMITS	
Gen Tol.: IS 2102	

HEAT TREATMENT NOTE:-

1) TO BE CASE HARDENED UPTO 40 ~ 45 HRC.
2) CASE DEPTH 0.8~ 2 mm AFTER FINISH GRINDING.
3) THREADS TO BE KEEP SOFT
4) RETAPPING TO BE DONE AFTER SURFACE TREATMENT AT SUPPLIER END.(IF APPLICABLE)

NOTE :
MATERIAL : C45
FINISH : BLACK OXIDE
MACHINING : ▽▽(▽▽▽)

REVISION	DESCRIPTION	DATE	DRN.BY
	MATERIAL UPDATED	13/02/2026	NDK

wipro pari
www.wipropari.com

1.ALL DIMENSIONS ARE IN mm
2.DO NOT SCALE DRAWING.
3.IF IN DOUBT , ASK TEAM MEMBER
LOCATION : ---

RESERVED SPACE FOR CONT... COPY
CONTROLLED COPY
© ALL RIGHTS OF REPRODUCTION & DISTRIBUTION ARE RESERVED

WIPRO PARI GROUP

DESCRIPTION: PIN

DRAWING TYPE: MACHINING

SURFACE AREA	SURFACE TREATMENT	MACHINING	DESIGN UNIT	DESIGN UNIT CD.	TEAM NO.	SHEET SIZE
0.51 in^2	BLACK OXIDE		WPP	0600	PL-02	A3

REFERENCE DWG. Error: No reference | PART CLASS. B | HEAT TREATMENT Error: No reference

DRN.BY	CHKD.BY	APPD.BY	MATERIAL	DRG./PART CODE	REV.	SCALE
NDK	SSJ	SSJ	C45	P24DKB014110	01	1 :
13/02/2026	13/02/2026	13/02/2026	NET WEIGHT-Kg 0.00 kg			SHEET 1 OF 1

NOTE FOR WIPRO PARI DESIGN -REF. ONLY
WEAR DETAILS : Error: No reference

\\srv01101\Ex\DM Uploading\2024-25\P24DK\P24DKB014110.dft