

NOTE : STANDARD FASTENER TORQUE AS PER STD-DES-01-00 FR-DES-006-00


TOP VIEW
SCALE 1:1

SECTION B-B
SCALE 1:1




DETAIL C
SCALE 2:1





FRONT VIEW
SCALE 1:1



SECTION A-A
SCALE 1:1

HOLE TABLE				
Hole	X	Y	Size	REMARK
A.1	0.00	0.00		REF SEC A-A
B.1	0.00	-22.00	Ø 6.60 mm THRU' C'BORE Ø 11.00 mm - 7.00 mm DEEP	REF SEC A-A
B.2	-19.05	-11.00	Ø 6.60 mm THRU' C'BORE Ø 11.00 mm - 7.00 mm DEEP	REF SEC A-A
B.3	-19.05	11.00	Ø 6.60 mm THRU' C'BORE Ø 11.00 mm - 7.00 mm DEEP	REF SEC A-A
B.4	0.00	22.00	Ø 6.60 mm THRU' C'BORE Ø 11.00 mm - 7.00 mm DEEP	REF SEC A-A
B.5	19.05	11.00	Ø 6.60 mm THRU' C'BORE Ø 11.00 mm - 7.00 mm DEEP	REF SEC A-A
B.6	19.05	-11.00	Ø 6.60 mm THRU' C'BORE Ø 11.00 mm - 7.00 mm DEEP	REF SEC A-A

DEBURR AND REMOVE SHARP EDGES UNLESS SHARP EDGE REQUIREMENT SPECIFIED	
UNSP.RADII 0.5 R	UNSP.CHF. 0.5 X 45°
UNSPECIFIED TOL.(FAB) FOR ANGULAR IN mm.	
UP TO 10	±1.5°
10 UP TO 50	±0°50'
50 UP TO 120	±0°25'
120 UP TO 400	±0°15'
UNSPECIFIED TOL.(FAB) FOR LINEAR IN mm.	
0.5 UP TO 3	±0.1
3 UP TO 6	±0.2
6 UP TO 30	±0.5
30 UP TO 120	±0.8
120 UP TO 315	±1.2
315 UP TO 1000	±2
1000 UP TO 2000	±3
OVER 2000	±4
UNSPECIFIED TOL.(M/C) FOR ANGULAR IN mm.	
UP TO 10	±1°
10 UP TO 50	±0°30'
50 UP TO 120	±0°20'
120 UP TO 400	±0°10'
UNSPECIFIED TOL.(M/C) FOR LINEAR IN mm.	
0.5 UP TO 3	±0.1
3 UP TO 6	±0.1
6 UP TO 30	±0.2
30 UP TO 120	±0.3
120 UP TO 315	±0.5
315 UP TO 1000	±0.8
1000 UP TO 2000	±1.2
OVER 2000	±2
LIMITS	
Gen Tol.: IS 2102	

TOLERANCE NOTE :-
1) ALL H7 HOLES C.D SHOULD BE CONTROLLED WITHIN±0.02. / IT7
2) ALL HOLES,TAP & COUNTER BORE C.D,
SHOULD BE CONTROLLED WITHIN ±0.2.

NOTE FOR WIPRO PARI DESIGN -REF. ONLY
WEAR DETAILS : N.A.

RESERVED SPACE FOR CONTROLLED COPY STAMP

CONTROLLED COPY

REVISION	DESCRIPTION	DATE	DRN.BY

www.wipropari.com

1.ALL DIMENSIONS ARE IN mm
2.DO NOT SCALE DRAWING.
3.IF IN DOUBT , ASK TEAM MEMBER
LOCATION : PUNE

© ALL RIGHTS OF REPRODUCTION & DISTRIBUTION ARE RESERVED

WIPRO PARI GROUP

DESCRIPTION: **SHAFT**

DRAWING TYPE: MACHINING

SURFACE AREA	SURFACE TREATMENT	MACHINING	DESIGN UNIT	DESIGN UNIT CD.	TEAM NO.	SHEET SIZE
16.28 in^2	I.Z.B.P. (TRIVALENT)	▽▽(▽▽▽)	WPP	0100	PL-02	A2

REFERENCE DWG. N.A. | PART CLASS. B | HEAT TREATMENT --

DRN.BY	CHKD.BY	APPD.BY	MATERIAL	DRG./PART CODE	REV.	SCALE
03006144	5489	03002882	MS	P24G3A031009	00	1 : 1
26/08/2024	26/08/2024	26/08/2024	NET WEIGHT-Kg 0.25 kg			SHEET 1 OF 1

\\pune\engnew\EXDM Uploding\P24G3\P24G3A031009.dft