

CHIP COIL (CHIP INDUCTORS) LQP03TG□□□□02D Reference Specification

1.Scope

This reference specification applies to LQP03TG_02 series, Chip coil (Chip Inductors).

2.Part Numbering

(ex) LQ P 03 T G 0N1 B 0 2 D
 Product ID Structure Dimension Applications Category Inductance Tolerance Features Electrode Packaging
 (L × W) and Characteristics D:Taping
 *B: Bulk

*Bulk packing also available. (A product is put in the plastic bag under the taping conditions.)

3.Rating

- Operating Temperature Range. -55°C to +125°C
 (Ambient temperature: Rated current can be handled in this temperature range.)
- Storage Temperature Range. -55°C to +125°C

Customer Part Number	MURATA Part Number	Inductance		Q (min)	DC Resistance (Ω max)	Self Resonant Frequency (MHz)		Rated Current (mA)			
		(nH)	Tolerance			Min.	*Typ.				
	LQP03TG0N1B02D	0.1	B:±0.1nH	-	0.07	20000	20000	850			
	LQP03TG0N2B02D	0.2	B:±0.1nH C:±0.2nH		0.08						
	LQP03TG0N2C02D										
	LQP03TG0N3B02D	0.3									
	LQP03TG0N3C02D										
	LQP03TG0N4B02D	0.4									
	LQP03TG0N4C02D										
	LQP03TG0N5B02D	0.5									
	LQP03TG0N5C02D										
	LQP03TG0N6B02D	0.6									
	LQP03TG0N6C02D										
	LQP03TG0N7B02D	0.7									
	LQP03TG0N7C02D										
	LQP03TG0N8B02D	0.8	11	0.10	18000	20000	750				
	LQP03TG0N8C02D										
	LQP03TG0N9B02D	12						0.12	17000	20000	700
	LQP03TG0N9C02D										
	LQP03TG1N0B02D										
	LQP03TG1N0C02D										
	LQP03TG1N1B02D		0.20	12500	16400	500					
	LQP03TG1N1C02D										
	LQP03TG1N2B02D	0.25					15900	450			
	LQP03TG1N2C02D										
	LQP03TG1N3B02D										
	LQP03TG1N3C02D										
	LQP03TG1N4B02D										
	LQP03TG1N4C02D										
	LQP03TG1N5B02D										
	LQP03TG1N5C02D										
	LQP03TG1N6B02D										
	LQP03TG1N6C02D										
	LQP03TG1N7B02D										
	LQP03TG1N7C02D										
	LQP03TG1N8B02D										
	LQP03TG1N8C02D										
	LQP03TG1N9B02D										
	LQP03TG1N9C02D										

Customer Part Number	MURATA Part Number	Inductance		Q (min)	DC Resistance (Ω max)	Self Resonant Frequency (MHz)		Rated Current (mA)	
		(nH)	Tolerance			Min.	*Typ.		
	LQP03TG2N0B02D	2.0	B:±0.1nH C:±0.2nH	13	0.25	12500	14800	450	
	LQP03TG2N0C02D								
	LQP03TG2N1B02D	2.1				12000	14300		
	LQP03TG2N1C02D								
	LQP03TG2N2B02D	2.2				11500	14100		
	LQP03TG2N2C02D								
	LQP03TG2N3B02D	2.3				11000	13700		
	LQP03TG2N3C02D								
	LQP03TG2N4B02D	2.4				11000	13700		
	LQP03TG2N4C02D								
	LQP03TG2N5B02D	2.5				11000	13800		
	LQP03TG2N5C02D						13900		
	LQP03TG2N6B02D	2.6					13100		
	LQP03TG2N6C02D								
	LQP03TG2N7B02D	2.7				9500	12200		
	LQP03TG2N7C02D								
	LQP03TG2N8B02D	2.8							11500
	LQP03TG2N8C02D								
	LQP03TG2N9B02D	2.9					11500		
	LQP03TG2N9C02D								
	LQP03TG3N0B02D	3.0			0.32	11800			
	LQP03TG3N0C02D						11600		
	LQP03TG3N1B02D	11200							
	LQP03TG3N1C02D								
	LQP03TG3N2B02D	3.2				11200			
	LQP03TG3N2C02D								
	LQP03TG3N3B02D	3.3				8000	10300		
	LQP03TG3N3C02D							10000	
	LQP03TG3N4B02D	3.4			9400				
	LQP03TG3N4C02D								
	LQP03TG3N5B02D	3.5			7000	8600			
	LQP03TG3N5C02D								
	LQP03TG3N6B02D	3.6				8100			
	LQP03TG3N6C02D								
	LQP03TG3N7B02D	3.7					8000		
	LQP03TG3N7C02D								
	LQP03TG3N8B02D	3.8			7800				
	LQP03TG3N8C02D								
	LQP03TG3N9B02D	3.9			7500				
	LQP03TG3N9C02D								
	LQP03TG4N3H02D	4.3	H:±3% J:±5%	12	0.58	6500	8000	300	
	LQP03TG4N3J02D								
	LQP03TG4N7H02D	4.7			0.72	7800			
	LQP03TG4N7J02D								
	LQP03TG5N1H02D	5.1		0.88	6000	7400			
	LQP03TG5N1J02D								
	LQP03TG5N6H02D	5.6		1.15	5400	6300			
	LQP03TG5N6J02D								
	LQP03TG6N2H02D	6.2		1.22	4800	5600			
	LQP03TG6N2J02D								
	LQP03TG6N8H02D	6.8							
	LQP03TG6N8J02D								
	LQP03TG7N5H02D	7.5							
	LQP03TG7N5J02D								

Customer Part Number	MURATA Part Number	Inductance		Q (min)	DC Resistance (Ω max)	Self Resonant Frequency (MHz)		Rated Current (mA)
		(nH)	Tolerance			Min.	*Typ.	
	LQP03TG8N2H02D	8.2	H:±3% J:±5%	12	1.40	4800	6200	200
	LQP03TG8N2J02D							
	LQP03TG9N1H02D	9.1		4500		5200	190	
	LQP03TG9N1J02D							
	LQP03TG10NH02D	10		1.52	4100	4700	180	
	LQP03TG10NJ02D							
	LQP03TG11NH02D	11		1.65	3700	4400		
	LQP03TG11NJ02D							
	LQP03TG12NH02D	12		1.78	3400	3800	170	
	LQP03TG12NJ02D							
	LQP03TG13NH02D	13		1.82	3100	3600		
	LQP03TG13NJ02D							
	LQP03TG15NH02D	15		1.90	2900	3300	160	
	LQP03TG15NJ02D							
	LQP03TG16NH02D	16		2.03	2800	3200		
	LQP03TG16NJ02D							
	LQP03TG18NH02D	18		2.28	2600	2900	140	
	LQP03TG18NJ02D							
	LQP03TG20NH02D	20		2.57	2500	2900		
	LQP03TG20NJ02D							
	LQP03TG22NH02D	22		2.85	2000	2400	120	
	LQP03TG22NJ02D							
	LQP03TG24NH02D	24		3.17	1700	2200		
	LQP03TG24NJ02D							
	LQP03TG27NH02D	27		3.65	1600	2000	110	
	LQP03TG27NJ02D							
	LQP03TG33NJ02D	33	4.25	1500	1700			
	LQP03TG39NJ02D							
	LQP03TG47NJ02D	47	5.20	1300	1500	100		
	LQP03TG56NJ02D							
	LQP03TG68NJ02D	68	5.60	1200	1400			
	LQP03TG82NJ02D							
	LQP03TGR10J02D	100	7.15	1000	1300	90		
	LQP03TGR12J02D							
		120	8.05	900	1200		80	
			8.75	800	1000			

* Typical value is actual performance.

4. Testing Conditions

《Unless otherwise specified》


Temperature : Ordinary Temperature / 15°C to 35°C
 Humidity : Ordinary Humidity / 25%(RH) to 85 %(RH)

《In case of doubt》


Temperature : 20°C ± 2°C
 Humidity : 60%(RH) to 70 %(RH)
 Atmospheric Pressure : 86kPa to 106 kPa

5. Appearance and Dimensions

(0.1nH to 0.5nH)





(0.6nH to 120nH)



■ Unit Mass (Typical value)


0.0002g




(in mm)

6. Marking




Polarity Marking :white



7. Electrical Performance

No.	Item	Specification	Test Method
7.1	Inductance	Inductance shall meet item 3.	<p>Measuring Equipment: KEYSIGHT E4991A or equivalent</p> <p>Measuring Frequency: (0.1nH~27nH) 500MHz (33nH~120nH) 300MHz</p> <p>Measuring Condition: Test signal level / about 0dBm Electrical length / 10mm</p> <p>Measuring Fixture: KEYSIGHT 16197A Position coil under test as shown in below and contact coil with each terminal by adding weight. Coloring side should be a topside, and should be in the direction of the fixture for position of chip coil.</p>
7.2	Q	Q shall meet item 3.	 <p>↑ Polarity Marking</p> <p>Measuring Method: See P.12 <Electrical Performance: Measuring Method of Inductance/Q></p>
7.3	DC Resistance	DC Resistance shall meet item 3.	Measuring Equipment: Digital multi meter
7.4	Self Resonant Frequency(S.R.F)	S.R.F shall meet item 3.	<p>Measuring Equipment: KEYSIGHT 8753C or equivalent</p>
7.5	Rated Current	Self temperature rise shall be limited to 25°C max.	The rated current is applied.


8. Mechanical Performance

No.	Item	Specification	Test Method
8.1	Shear Test	Chip coil shall not be damaged after tested as test method.	<p>Substrate: Glass-epoxy substrate</p> <p>Land</p>  <p>(in mm)</p> <p>Force: 2N Hold Duration: 5 s \pm 1 s Applied Direction: Parallel to PCB.</p> <p>Chip coil</p>  <p>Substrate</p>
8.2	Bending Test	Chip coil shall not be damaged after tested as test method.	<p>Substrate: Glass-epoxy substrate (100mm \times 40mm \times 0.8mm)</p> <p>Speed of Applying Force: 1mm / s Deflection: 1mm Hold Duration: 30 s</p>  <p>Pressure jig</p> <p>R340</p> <p>Deflection</p> <p>Product (in mm)</p>
8.3	Vibration	Appearance: No damage Inductance Change: within \pm 10%	<p>Substrate: Glass-epoxy substrate</p> <p>Oscillation Frequency: 10Hz to 2000Hz to 10Hz for 20 min</p> <p>Total amplitude 1.5 mm or Acceleration amplitude 196 m/s² whichever is smaller.</p> <p>Testing Time: A period of 2h in each of 3 mutually perpendicular directions.</p>
8.4	Solderability	The electrode shall be at least 90% covered with new solder coating.	<p>Flux: Ethanol solution of rosin 25(wt)% (Immersed for 5s to 10s)</p> <p>Solder: Sn-3.0Ag-0.5Cu</p> <p>Pre-Heating: 150°C \pm 10°C / 60s to 90s</p> <p>Solder Temperature: 240°C \pm 5°C</p> <p>Immersion Time: 3s \pm 1s</p>
8.5	Resistance to Soldering Heat	Appearance: No damage Inductance Change: within \pm 10%	<p>Flux: Ethanol solution of rosin 25(wt)% (Immersed for 5s to 10s)</p> <p>Solder: Sn-3.0Ag-0.5Cu</p> <p>Pre-Heating: 150°C \pm 10°C / 60s to 90s</p> <p>Solder Temperature: 260°C \pm 5°C</p> <p>Immersion Time: 5s \pm 1s</p> <p>Then measured after exposure in the room condition for 24h \pm 2h.</p>

9.Environmental Performance

It shall be soldered on the substrate.

No.	Item	Specification	Test Method
9.1	Heat Resistance	Appearance:No damage Inductance Change: within $\pm 10\%$	Substrate: Glass-epoxy substrate Temperature:125°C Time:1000h (+48h,-0h) Then measured after exposure in the room condition for 24h \pm 2h.
9.2	Cold Resistance		Substrate: Glass-epoxy substrate Temperature:-55°C Time:1000 h (+48h,-0h) Then measured after exposure in the room condition for 24h \pm 2h.
9.3	Humidity		Substrate: Glass-epoxy substrate Temperature:40°C \pm 2°C Humidity:90%(RH) to 95%(RH) Time:1000 h(+48h,-0h) Then measured after exposure in the room condition for 24h \pm 2h.
9.4	Temperature Cycle		Substrate: Glass-epoxy substrate 1 cycle: 1 step: -55°C / 30min \pm 3 min 2 step: Ordinary temp. / 10~15 min 3 step: 125°C / 30min \pm 3 min 4 step: Ordinary temp. / 10~15 min Total of 10 cycles Then measured after exposure in the room condition for 24h \pm 2h.

10.Specification of Packaging**10.1 Appearance and Dimensions of paper tape (8mm-wide)****10.2 Specification of Taping**


- (1) Packing quantity (standard quantity)
15,000 pcs. / reel
- (2) Packing Method
Products shall be packed in the cavity of the base tape and sealed by cover tape.
- (3) Sprocket hole
Sprocket hole shall be located on the left-hand side toward the direction of feed.
- (4) Spliced point
Base tape and Cover tape has no spliced point.
- (5) Missing components number
Missing components number within 0.1 % of the number per reel or 1 pc. , whichever is greater, and are not continuous. The Specified quantity per reel is kept.

10.3 Pull Strength


Cover tape	5N min
------------	--------

10.4 Peeling off force of cover tape

Speed of Peeling off	300mm/min
Peeling off force	0.1N to 0.6N (minimum value is typical)

**10.5 Dimensions of Leader-tape, Trailer and Reel**

There shall be leader-tape (top tape and empty tape) and trailer-tape (empty tape) as follows.

**10.6 Marking for reel**

Customer part number, MURATA part number, Inspection number(*1) , RoHS Marking (*2), Quantity etc ...

*1) <Expression of Inspection No.>

$\square\square$ 0000 $\times\times\times$
(1) (2) (3)

(1) Factory Code

(2) Date

First digit : Year / Last digit of year

Second digit : Month / Jan. to Sep. → 1 to 9, Oct. to Dec. → O,N,D

Third, Fourth digit : Day

(3) Serial No.

*2) <Expression of RoHS Marking >


ROHS – Y (\triangle)
(1) (2)

(1) RoHS regulation conformity parts.

(2) MURATA classification number

10.7 Marking for Outside package (corrugated paper box)

Customer name, Purchasing order number, Customer part number, MURATA part number, RoHS Marking (*2) ,Quantity, etc ...

10.8 Specification of Outer Case

Outer Case Dimensions (mm)			Standard Reel Quantity in Outer Case (Reel)
W	D	H	
186	186	93	5

* Above Outer Case size is typical. It depends on a quantity of an order.

11. ⚠ Caution**Limitation of Applications**

Please contact us before using our products for the applications listed below which require especially high reliability for the prevention of defects which might directly cause damage to the third party's life, body or property.


- | | |
|-----------------------------------|--|
| (1) Aircraft equipment | (6) Transportation equipment (vehicles, trains, ships, etc.) |
| (2) Aerospace equipment | (7) Traffic signal equipment |
| (3) Undersea equipment | (8) Disaster prevention / crime prevention equipment |
| (4) Power plant control equipment | (9) Data-processing equipment |
| (5) Medical equipment | (10) Applications of similar complexity and /or reliability requirements to the applications listed in the above |

12. Notice

Products can only be soldered with reflow.

This product is designed for solder mounting.


Please consult us in advance for applying other mounting method such as conductive adhesive.

12.1 Land pattern designing**12.2 Flux, Solder**

- Use rosin-based flux.
Don't use highly acidic flux with halide content exceeding 0.2(wt)% (chlorine conversion value).
Don't use water-soluble flux.
- Use Sn-3.0Ag-0.5Cu solder.
- Standard thickness of solder paste : 100 μ m~150 μ m.

12.3 Reflow soldering conditions

- Pre-heating should be in such a way that the temperature difference between solder and product surface is limited to 150°C max. Cooling into solvent after soldering also should be in such a way that the temperature difference is limited to 100°C max.
Insufficient pre-heating may cause cracks on the product, resulting in the deterioration of products quality.
- Standard soldering profile and the limit soldering profile is as follows.
The excessive limit soldering conditions may cause leaching of the electrode and / or resulting in the deterioration of product quality.
- Reflow soldering profile



	Standard Profile	Limit Profile
Pre-heating	150°C~180°C , 90s±30s	
Heating	above 220°C, 30s~60s	above 230°C, 60s max.
Peak temperature	245°C±3°C	260°C, 10s
Cycle of reflow	2 times	2 times

12.4 Reworking with soldering iron


The following conditions must be strictly followed when using a soldering iron.

Pre-heating	150°C, 1 min
Tip temperature	350°C max.
Soldering iron output	80W max.
Tip diameter	φ 3mm max.
Soldering time	3(+1,-0)s
Time	2 times

Note : Do not directly touch the products with the tip of the soldering iron in order to prevent the crack on the products due to the thermal shock.

12.5 Solder Volume

- Solder shall be used not to be exceeded the upper limits as shown below.




Accordingly increasing the solder volume, the mechanical stress to Chip is also increased. Exceeding solder volume may cause the failure of mechanical or electrical performance.

12.6 Attention regarding P.C.B. bending

The following shall be considered when designing and laying out P.C.B.'s.


- P.C.B. shall be designed so that products are not subject to the mechanical stress due to warping the board.

[Products direction]



Products shall be located in the sideways direction (Length: $a < b$) to the mechanical stress.

- Products location on P.C.B. separation



Products (A,B,C,D) shall be located carefully so that products are not subject to the mechanical stress due to warping the board. Because they may be subjected the mechanical stress in order of $A > C > B \cong D$.

12.7 Cleaning Conditions

Products shall be cleaned on the following conditions.

- Cleaning temperature shall be limited to 60°C max. (40°C max for IPA)
- Ultrasonic cleaning shall comply with the following conditions with avoiding the resonance phenomenon at the mounted products and P.C.B.
Power : 20 W / l max. Frequency : 28kHz to 40kHz Time : 5 min max.
- Cleaner
 - Alcohol type cleaner
Isopropyl alcohol (IPA)
 - Aqueous agent
PINE ALPHA ST-100S
- There shall be no residual flux and residual cleaner after cleaning.
In the case of using aqueous agent, products shall be dried completely after rinse with de-ionized water in order to remove the cleaner.
- Other cleaning Please contact us.

12.8 Resin coating

When products are coated with resin, please contact us in advance.

12.9 Handling of a substrate

- (1) There is a possibility of chip cracking caused by PCB expansion/contraction with heat, because stress on a chip is different depending on PCB material and structure.

When the thermal expansion coefficient greatly differs between the board used for mounting and the chip, it will cause cracking of the chip due to the thermal expansion and contraction.

The chip is assumed to be mounted on the PCB of glass-epoxy material, and we don't test with other PCB material which has different thermal expansion coefficient from Glass-epoxy.

When other PCB materials are considered, please be sure to evaluate by yourself.


- (2) After mounting products on a substrate, do not apply any stress to the product caused by bending or twisting to the substrate when cropping the substrate, inserting and removing a connector from the substrate or tightening screw to the substrate.

Excessive mechanical stress may cause cracking in the product.


In case of the mounting on flexible PCB, there is a possibility of chip cracking caused by mechanical stress even from small bending or twisting.

When the flexible PCB is considered, please be sure to evaluate by yourself.

Bending



Twisting



12.10 Storage and Handling Requirements

(1) Storage period

Use the products within 12 months after delivered.

Solderability should be checked if this period is exceeded.

(2) Storage conditions

- Products should be stored in the warehouse on the following conditions.

Temperature : -10°C ~ 40°C

Humidity : 15% to 85% relative humidity No rapid change on temperature and humidity.

- Products should not be stored on bulk packaging condition to prevent the chipping of the core and the breaking of winding wire caused by the collision between the products.
- Products should be stored on the palette for the prevention of the influence from humidity, dust and so on.
- Products should be stored in the warehouse without heat shock, vibration, direct sunlight and so on.

(3) Handling Condition


Care should be taken when transporting or handling product to avoid excessive vibration or mechanical shock.

13. ⚠ Note

- (1) Please make sure that your product has been evaluated in view of your specifications with our product being mounted to your product.
- (2) You are requested not to use our product deviating from the reference specifications.
- (3) The contents of this reference specification are subject to change without advance notice.
Please approve our product specifications or transact the approval sheet for product specifications before ordering.

<Electrical Performance:Measuring Method of Inductance/Q>

(1) Residual elements and stray elements of test fixture can be described by F-parameter shown in following.



(2) The impedance of chip coil Z_x and measured value Z_m can be described by input/output current/voltage.

$$Z_m = \frac{V_1}{I_1}, \quad Z_x = \frac{V_2}{I_2}$$

(3) Thus, the relation between Z_x and Z_m is following;

$$Z_x = \alpha \frac{Z_m - \beta}{1 - Z_m \Gamma}$$

where, $\alpha = D / A = 1$
 $\beta = B / D = Z_{sm} - (1 - Y_{om} Z_{sm}) Z_{ss}$
 $\Gamma = C / A = Y_{om}$

$\left[\begin{array}{l} Z_{sm}: \text{measured impedance of short chip} \\ Z_{ss}: \text{residual impedance of short chip}(0nH) \\ Y_{om}: \text{measured admittance when opening the fixture} \end{array} \right]$

(4) L_x and Q_x shall be calculated with the following equation.

$$L_x = \frac{\text{Im}(Z_x)}{2\pi f}, \quad Q_x = \frac{\text{Im}(Z_x)}{\text{Re}(Z_x)}$$

L_x : Inductance of chip coil
 Q_x : Q of chip coil
 f : Measuring frequency