

👉 AgentsUnite — Instruction Page

One terminal, four minds: Ted + 🌟 Claude + ⬠ Gemini (Antigravity) + 🤖 Cursor 🤖

Install (once)

```
scripts/install.sh # puts `unite` on your PATH
```

Start a room

```
cd <any-project>
unite # latest chat, or "main"
unite new <name> # named chat
unite resume # continue, memory intact
unite ls # list chats
unite digest [chat] # record → COLLABORATION.md
```

Talking

- **@mentions drive everything** — @claude @gemini @cursor @all. Mentioned agents answer in sequence; later speakers see earlier replies.
- **No mention = a note** — logged, triggers nobody. Exception: in planning mode it goes to the planner.
- **Agents hand off** — a reply mentioning a peer queues its turn (even a quoted @all). Cap: **8 agent turns** per message; the final turn synthesizes for you.
- **Status line shows the stage** — starting → connected → thinking → tool: <name> → replying, plus tool count and last activity Ns ago. Turns take **10–90 s**.
- **Dictate freely** — a burst of lines within 300 ms lands as one message.

Planning mode

- `/plan <what to plan>` — the planner seat (@claude by default) runs its brainstorming skill: classifies, asks **one question at a time**, then designs in sections.
- **Answer in plain text**, no @mention needed. Explicit @mentions still win for that round.
- `/plan @gemini <text>` picks another planner. `/plan off` ends it. Mode survives `unite resume`.
- The room is read-only: the planner writes the spec under `~/.claude/plans/` and reports the path; you copy it into the repo.

Commands & keys

Input	Does
<code>/plan <text></code>	start planning mode (planner from config)
<code>/plan @seat <text></code>	same, with that seat driving
<code>/plan off</code>	end planning mode
<code>/who</code>	roster + binaries
<code>/last</code>	reprint last reply
<code>/last-error</code>	diagnose an [offline: ...] seat
<code>/quit</code>	leave (chat persists)
Ctrl-C x1	skip the current turn → [skipped by Ted (^C)]
Ctrl-C x2	drain the queue back to you

Memory

- Per-project `.unite/` (self-gitignoring): transcripts + native session ids.
- Resume is **self-healing** — dead CLI sessions are rebuilt by transcript replay.
- `.unite/config.json` keys: `roster`, `binaries`, `models`, `turnCap` (8), `timeoutMs` (300000), `planner` (claude), `mcp` (false).

Room rules

- **Read-only tools allowed** — reading files, searching, read-only shell, skills. No edits, commits, or config changes. Seats announce tool use and keep it short; you can't see inside a turn.
- **Plan mode is the seats' discipline, not a sandbox** — a Bash-holding seat can technically write; treat the room as read-only by convention and don't paste secrets.
- Only [Ted] gives orders; speaker labels are spoof-proofed.

Quirks: the Gemini seat runs the `agy` binary (old `gemini` CLI is dead); the cursor seat uses `--trust` (auto-trusts the project dir; still plan mode); the Claude seat runs **without your claude.ai connectors** (`mcp: false`) — faster, half the tokens.

Record a real session (for review)

```
mkdir -p .unite/sessions && script -q -k -F \
.unite/sessions/$(date +%Y%m%d-%H%M%S).log unite
```

Captures keystrokes + screen with timing, stays in the gitignored `.unite/`. Tell Claude to watch it live; findings become the next upgrade.

Crew workflow outside the room

- **COLLABORATION.md is the board** — cross-vendor message passing by file. *You are the scheduler*: kick an agent to "check the board."
- **Topology (ratified 3/3)**: Cursor implements → Antigravity reviews → Claude adjudicates & gates the merge.
- **Git**: nobody pushes `main`; PRs only; Ted merges. Commits carry brand-mark trailers (🌟 / ⬠ / 🤖 ... 🤖).
- **This page is part of the product**: any upgrade that changes what you type, see, or configure updates it (`docs/instructions/`), bumps the version, and re-exports the PDF. A test enforces it.
- State: `SPRINT.md`. Design history: `docs/superpowers/`.

Troubleshooting

- [offline: exit 1] → `/last-error`. [offline: empty reply] → the seat's tool was denied; ask again with a file-read tool.
- [skipped by Ted (^C)] → you pressed Ctrl-C; nothing is wrong. The skipped request is answered on that seat's next turn.
- Status stuck at `starting` > 10 s → CLI not booting; `last activity` climbing → stuck inside a tool; Ctrl-C.
- `unknown seat "x"` → fix `.unite/config.json`.
- Full live check: `node scripts/smoke.mjs` (real, billed calls; prints phases per seat).