

👉 AgentsUnite Desktop — Instruction Page

Hybrid Terminal Runner: Ted + 🟢 Claude Code CLI (tools on) + ⚡ Gemini Desktop (AX/JXA · NotebookLM)

Setup & macOS Permissions (Once)

- **Install CLI:** symlinked to `~/local/bin/AgentsUniteD` (or `unite-desktop`).
- **Prerequisites:** `claude` CLI on PATH; native `Gemini.app` installed.
- **macOS Permissions:** Grant your terminal (Terminal, iTerm2, Cursor) access under:
System Settings → Privacy & Security → Accessibility
System Settings → Privacy & Security → Automation → System Events

Starting a Room

```
AgentsUniteD           # resume latest chat, or start "main"
AgentsUniteD new <name> # start a new named chat room
AgentsUniteD resume     # pick an existing chat interactively
AgentsUniteD ls         # list all chat rooms
AgentsUniteD -g         # GLOBAL mode (unattached to any repo)
```

Talking & Multi-Agent Relay

- **@mentions drive routing** — `@claude @gemini`. Mentioned agents respond in turn sequence; later agents see previous replies.
- **No mention = a note** — logged to transcript, triggers nobody. (In planning mode, unadorned text routes straight to the planner).
- **Handoffs & Collaboration** — when Gemini mentions `@claude`, Claude takes a turn automatically (and vice versa). Cap: **8 turns** per round.
- **Real-time status line** — shows phase (`starting` → `connected` → `thinking` → `replying`), tool name, and elapsed seconds.

Planning Mode (/plan)

- `/plan` (or `/plans`) — **toggles planning mode ON/OFF**. When ON, `@claude` drives: all plain text goes directly to Claude without needing an `@claude` prefix.
- `/plan @seat` — assign another seat as lead planner (e.g. `/plan @gemini`).
- `/plan <topic>` — starts planning on a specific topic immediately.
- `/plan off` (or bare `/plan`) — ends planning mode; returns to mention routing.

Commands & Shortcuts

Input	Action
<code>/plan</code>	toggle planning mode ON / OFF (Claude drives by default)
<code>/plan @seat</code>	switch lead planner seat
<code>/plan <topic></code>	initiate planning on topic immediately
<code>/plan off</code>	exit planning mode
<code>/who</code>	display active roster and adapter execution modes
<code>/last</code>	reprint the last received assistant reply
<code>/last-error</code>	diagnose adapter or system failure logs
<code>/quit</code>	exit cleanly (chat state and session persist)
<code>Ctrl-C x1</code>	skip the currently thinking agent turn
<code>Ctrl-C x2</code>	drain the queue and return control to Ted

Storage & Finder QuickLook

- **Global Mode (-g):** Stored in visible `~/Documents/AgentsUnite/global/<chat>/`. Fully browseable and cleanable in Finder. To delete a chat, just drag its folder to macOS Trash!
- **Project Mode:** Stored locally in `<cwd>/unite/chats/<chat>/` with self-maintaining `.gitignore` so repo git status stays clean.
- **QuickLook Companion:** Every chat turn automatically updates a clean, human-readable `transcript.md` alongside `transcript.jsonl`. Tap Spacebar in Finder to read the conversation instantly!

How the Hybrid Architecture Works

- **Claude Code CLI:** Spawns headlessly with `--permission-mode acceptEdits`, giving Claude full tool, terminal, and filesystem editing power in project mode.
- **Gemini Desktop:** Bridges to `Gemini.app` via macOS Accessibility (AX/JXA). Gives the terminal room full access to private NotebookLM sources and desktop features without API token limits.
- **Prompt Preamble:** Claude receives CLI tool instructions; Gemini receives clean conversational framing with the explicit directive to yield high-stakes architecture decisions to Ted.
- **Instant Feedback:** Startup spinner and rotating status messages run during preflight so you know the bridge is alive.

Tip: If you want to brainstorm, review documents, or query your NotebookLM notebooks without touching any code repo, run `AgentsUniteD -g` from any terminal. It keeps all global chats neatly together in your Documents folder.

Troubleshooting

- `[offline: -1743]` → macOS Apple Events denied. Enable System Events permission for your terminal in *System Settings* → *Privacy & Security* → *Automation*.
- `[offline: -25211]` → Accessibility denied. Enable Accessibility for your terminal in *System Settings* → *Privacy & Security* → *Accessibility*.
- `Gemini.app: no chat open` → Open `Gemini.app` and ensure a conversation is open with an active composer message box.
- `Status stuck at starting` → Press `Ctrl-C` to skip the turn, or run `/last-error`.