

Claude Code Commands Cheat Sheet

Right now you're guessing why Claude Code follows old instructions or slows down.

By the end of this page, you'll know which command shows each cause, so you can see it instead of guessing.

/doctor prompt-audit

WHAT IT DOES	It checks your CLAUDE.md, AGENTS.md, skills, rules, and other files under <code>.claude/</code> for outdated or conflicting instructions. That includes dead file references, instructions written for older models, and files that contradict each other.
WHEN TO RUN IT	Run it after you retire a plan, rename a folder, or add a skill, because your files may still say what used to be true.
HOW TO RUN IT	Check your version with <code>claude --version</code> , then run <code>claude update</code> if needed, because the audit requires v2.1.283 or later. Then type <code>/doctor prompt-audit</code> , or add a path like <code>/doctor prompt-audit .claude/skills/deploy</code> to check only the part you changed.
WHAT YOU'LL SEE	You'll get a report with proposed edits, and nothing changes until you approve it. Our Sep 25 run took 6m 50s across 25 skills and found 19 issues.

/context

WHAT IT DOES	It shows what's filling Claude's context window as a colored grid by category. The categories include CLAUDE.md and memory files, skill descriptions, and MCP tools and server instructions. By default, only skill descriptions and MCP tool names load, not everything.
WHEN TO RUN IT	Run it when a session feels sluggish, before a long task, and after adding a skill or MCP server, because each one adds to what loads before you type a word.
HOW TO RUN IT	Type <code>/context</code> . In fullscreen, type <code>/context all</code> , because fullscreen collapses the per-item list.
WHAT YOU'LL SEE	You'll see the grid plus suggestions about context-heavy tools, memory bloat, and capacity. It deletes nothing, so you decide whether to <code>/compact</code> , <code>/clear</code> , or edit your files with <code>/memory</code> .

Recap: Instructions drift and context windows fill up, and guessing fixes neither. `/doctor prompt-audit` checks what Claude is told, and `/context` shows what Claude is carrying.

You're at B if you can now audit your instructions after any setup change and read your context grid before a long task.