The Aurora Protocol: A Framework for Distributed Quantum Computing

Dr. Elena Vasquez, Institute for Advanced Computation, 2025

Abstract

The Aurora Protocol introduces a novel framework for distributed quantum computing that achieves fault-tolerant operation across heterogeneous quantum processors. Our key innovation is the Triadic Entanglement Relay (TER), which maintains coherence across up to 47 interconnected nodes with a fidelity rate of 99.3%. The protocol was validated on a network spanning three continents: Node Alpha in Zurich, Node Beta in Tokyo, and Node Gamma in Montreal.

1. Introduction

Quantum computing faces a fundamental scaling challenge. Individual quantum processors are limited to approximately 1,200 qubits with current technology. The Aurora Protocol addresses this by distributing computation across multiple processors connected via quantum networks. Unlike previous approaches such as the Cascade Method (Chen et al., 2023) and the Photonic Bridge Protocol (Nakamura, 2024), our approach does not require homogeneous hardware. The Aurora Protocol can coordinate processors from IBM, Google, and Rigetti simultaneously.

2. The Triadic Entanglement Relay

The Triadic Entanglement Relay (TER) is the core mechanism of the Aurora Protocol. It operates in three phases:

Phase 1 - Initialization: Three anchor qubits are prepared in a GHZ state across three nodes. This requires exactly 14 microseconds under optimal conditions.

Phase 2 - Propagation: The entangled state is extended to neighboring nodes using a chain of Bell measurements. Each hop adds approximately 2.3 microseconds of latency.

Phase 3 - Verification: A distributed parity check confirms entanglement fidelity. If fidelity drops below 97.5%, the relay is re-initialized automatically.

The TER achieved a maximum throughput of 8,400 entangled pairs per second in laboratory conditions, and 6,100 pairs per second in the intercontinental deployment.

3. Experimental Results

We tested the Aurora Protocol on three benchmark problems:

Benchmark A - Shor's Algorithm: Factored a 2,048-bit RSA key in 4.7 hours using 17 distributed processors

with a combined 14,600 logical qubits.

Benchmark B - Molecular Simulation: Simulated the folding pathway of the protein ubiquitin (76 amino acids) with chemical accuracy, completing in 23 minutes.

Benchmark C - Optimization: Solved a 500-city traveling salesman problem to within 0.3% of the known optimum in 8.2 minutes.

The protocol demonstrated a 340% speedup over single-processor approaches for Benchmark A and a 180% speedup for Benchmark B.

4. Conclusion

The Aurora Protocol represents a significant advance in distributed quantum computing. The Triadic Entanglement Relay enables practical multi-node quantum computation with minimal overhead. Future work will focus on extending the protocol to support more than 100 nodes and integrating error correction codes specifically designed for distributed architectures. The protocol is available as open-source software under the MIT license at github.com/aurora-protocol/core.