

Full Title

Full Author Name



Date

- `\DocumentMetadata{`
 `lang=en,`
 `tagging=on,`
 `pdfstandard=ua-2,`
 `% check-tagging-status,`
 `tagging-setup={`
 `% math/alt/use, % <=> Formulas must have description/alt text`
 `% role/new-tag=frametitle/H1, % <=> headings must begin at level 1`
 `math/setup=mathml-SE`
 `}`
 `}`
 `\documentclass{ltx-talk}`
- `Lua $\TeX$`
- tagged PDF + overlays: `\command<xyz>` $\rightarrow$ `\command` only on slides xyz
- defined colors: `alert`, `example`, `structure`
- `{frame*}` $\Leftrightarrow$ `\verb|...|`, `{verbatim}`, `{lstlisting}`, etc. (like Beamer's `fragile`)

Overlays: `\command<xyz>` → `\command` only on slides `xyz`

- Color commands with overlays: `\color`, `\mathcolor`, `\textcolor`
- Text commands with overlays: `\textbf`, `\textit`, `\textmd`, `\textnormal`, `\textrm`, `\textsc`, `\textsf`, `\textsl`, `\texttt`, `\textup`, `\emph`
- Also: `\includegraphics`; `\label`
- ★ `\only`, `\uncover`, `\visible`, `\invisible`, `\alert`
- Environments `{onlyenv}`, `{invisibleenv}`, `{uncoverenv}`, `{visibleenv}`, `{alertenv}`
- Also: `\onslide`, `\alt`, `\temporal`
- `\item`, `\action`, `{actionenv}` can take an *action specification* (combine several ★ actions into one `<...>`)

The Basics

Sectioning

Examples

- List Environments

Customizations

- Adjusting the Header

- Adjusting the Footer

- Adjusting the Title Page

- More Customizations

Future Work

Default tocdepth is 2 (\subsection).

The Basics

Sectioning

Examples

List Environments

Customizations

Adjusting the Header

Adjusting the Footer

Adjusting the Title Page

More Customizations

Future Work

Default `tocdepth` is 2 (`\subsection`).

- `{itemize}`, `{enumerate}`, `{description}` as in usual classes
- templates mean we can pass options to the environments,
see `texdoc blocks-doc`
- extra (default) key `action-spec`
- `action-spec=<+->` uncover one item at a time
- `action-spec=<+-|alert@+>` and `\alert` the new item

`\EditInstance{header}{std}{<key=value>}` or
`\EditInstance{frametitle}{header}{font=<value>}`

Key	Default Value
background-color	(none)
color	structure
font	\normalfont
height	topmargin (10 mm) + headsep (2 mm)
left-hspace	leftmargin (10 mm)
right-hspace	rightmargin (10 mm)
print-frame-title	true

```
\newsavebox\logobox
\savebox\logobox{%
  \includegraphics[artifact, height=\baselineskip]{logo-file}}
% after \maketitle frame
\AddToHook{shipout/foreground}{%
  \put(\paperwidth - \wd\logobox - 10mm,
    -8.5mm){\usebox\logobox}} % -\ht\logobox
```

```
\EditInstance{footer}{std}{<key=value>}
```

Key	Default Value
background-color	(none)
color	black
element-order	(empty)
font	\tiny
left-hspace	leftmargin (10 mm)
right-hspace	rightmargin (10 mm)
separator	\hfil

Available footer elements:

author, date, institute, title, subtitle, framenumbers, totalframes

(=`\RefProperty{lastpage}{totalframes}`)

For example:

```
\EditInstance{footer}{std}{element-order={date,author,title,framenumbers}}
```

```
\DeclareInstance{footer-element}{myelement}{talk}{...}
% and then
\makeatletter
\newcommand\@myelement{...}
% or
\newcommand\@shortmyelement{...} % used if both available
\makeatother
% or
\ExpandArgs{c}\newcommand{\@myelement}{...}
% or
\ExpandArgs{c}\newcommand{\@shortmyelement}{...} % used if both available
```

and then pass myelement to element-order

For example:

```
\ExpandArgs{c}\newcommand{\@framesoftotal}{%
  \arabic{frame}/\RefProperty{lastpage}{totalframes}%
}
```

```
\maketitle
% same as
\maketitle[
  element-order      = {
    title, subtitle, author,
    institute, date
  },
  framestyle          = talk,
  horizontal-alignment = center,
  vertical-alignment  = center
]
```

```
\thispagestyle{framestyle}
options are talk, plain & wallpaper
```

Full Title

Subtitle

Full Author Name

University of North Dakota

Date

Adjusted title page:

```
\maketitle[  
  element-order = {  
    title, author,  
    titlegraphic, date},  
  framestyle     = plain,  
]
```

talk default header and footer

plain no header and footer

wallpaper header and footer have
background color but no text

Full Title

Full Author Name



Date

```
\DeclareInstance{titlepage-element}{myelement}{talk}{<key=value>}
```

% and then

```
\makeatletter
```

```
\newcommand\@myelement{...}
```

```
\makeatother
```

% or

```
\ExpandArgs{c}\newcommand{\@myelement}{...}
```

and then pass myelement to \maketitle's element-order

For example:

```
\ExpandArgs{c}\newcommand{\@titlegraphic}{%
```

```
\includegraphics[
```

```
  actualtext={University of North Dakota, Mathematics \& Statistics},
```

```
  width=5cm
```

```
]{graphic-file}%
```

```
}
```

```
\EditInstance{floatenv}{std}{horizontal-alignment = <alignment>}  
% left (default), center, or right
```

```
\EditInstance{hidden}{std}{opacity = <value>}  
% 0 <= value <= 1 for how opaque hidden things should be  
% default is 0
```

- tagging
- frame layout
- blocks
- header / footer templates
- frame title
- heading structure?