

Full Title

Full Author Name



Date

- `\DocumentMetadata{`  
    `lang=en,`  
    `tagging=on,`  
    `pdfstandard=ua-2,`  
    `% check-tagging-status,`  
    `tagging-setup={`  
        `% math/alt/use, % <=> Formulas must have description/alt text`  
        `% role/new-tag=frametitle/H1, % <=> headings must begin at level 1`  
        `math/setup=mathml-SE`  
    `}`  
    `}`  
    `\documentclass{ltx-talk}`
- `Lua $\TeX$`
- tagged PDF + overlays: `\command<xyz>`  $\rightarrow$  `\command` only on slides xyz
- defined colors: `alert`, `example`, `structure`
- `{frame*}`  $\Leftrightarrow$  `\verb|...|`, `{verbatim}`, `{lstlisting}`, etc. (like Beamer's `fragile`)

Overlays: `\command<xyz>` → `\command` only on slides `xyz`

- Color commands with overlays: `\color`, `\mathcolor`, `\textcolor`
- Text commands with overlays: `\textbf`, `\textit`, `\textmd`, `\textnormal`, `\textrm`, `\textsc`, `\textsf`, `\textsl`, `\texttt`, `\textup`, `\emph`
- Also: `\includegraphics`; `\label`
- ★ `\only`, `\uncover`, `\visible`, `\invisible`, `\alert`
- Environments `{onlyenv}`, `{invisibleenv}`, `{uncoverenv}`, `{visibleenv}`, `{alertenv}`
- Also: `\onslide`, `\alt`, `\temporal`
- `\item`, `\action`, `{actionenv}` can take an *action specification* (combine several ★ actions into one `<...>`)

---

Default tocdepth is 2 (\subsection).

---

Default `tocdepth` is 2 (`\subsection`).

- `{itemize}`, `{enumerate}`, `{description}` as in usual classes
- templates mean we can pass options to the environments,  
see `texdoc blocks-doc`
- extra (default) key `action-spec`
- `action-spec=<+->` uncover one item at a time
- `action-spec=<+-|alert@+>` and `\alert` the new item

`\EditInstance{header}{std}{<key=value>}` or  
`\EditInstance{frametitle}{header}{font=<value>}`

| Key               | Default Value                         |
|-------------------|---------------------------------------|
| background-color  | (none)                                |
| color             | structure                             |
| font              | <code>\normalfont</code>              |
| height            | topmargin (10 mm)<br>+ headsep (2 mm) |
| left-hspace       | leftmargin (10 mm)                    |
| right-hspace      | rightmargin (10 mm)                   |
| print-frame-title | true                                  |

```
\newsavebox\logobox
\savebox\logobox{%
  \includegraphics[artifact, height=\baselineskip]{logo-file}}
% after \maketitle frame
\AddToHook{shipout/foreground}{%
  \put(\paperwidth - \wd\logobox - 10mm,
    -8.5mm){\usebox\logobox}} % -\ht\logobox
```



```
\EditInstance{footer}{std}{<key=value>}
```

| Key              | Default Value       |
|------------------|---------------------|
| background-color | (none)              |
| color            | black               |
| element-order    | (empty)             |
| font             | \tiny               |
| left-hspace      | leftmargin (10 mm)  |
| right-hspace     | rightmargin (10 mm) |
| separator        | \hfil               |

Available footer elements:

author, date, institute, title, subtitle, framenumbers, totalframes

(=\RefProperty{lastpage}{totalframes})

For example:

```
\EditInstance{footer}{std}{element-order={date,author,title,framenumbers}}
```

```
\DeclareInstance{footer-element}{myelement}{talk}{...}  
% and then  
\makeatletter  
\newcommand\@myelement{...}  
% or  
\newcommand\@shortmyelement{...} % used if both available  
\makeatother  
% or  
\ExpandArgs{c}\newcommand{\@myelement}{...}  
% or  
\ExpandArgs{c}\newcommand{\@shortmyelement}{...} % used if both available
```

and then pass myelement to element-order

For example:

```
\ExpandArgs{c}\newcommand{\@framesoftotal}{%  
  \arabic{frame}/\RefProperty{lastpage}{totalframes}%  
}
```

```
\maketitle
% same as
\maketitle[
  element-order      = {
    title, subtitle, author,
    institute, date
  },
  framestyle         = talk,
  horizontal-alignment = center,
  vertical-alignment  = center
]
```

```
\thispagestyle{framestyle}
options are talk, plain & wallpaper
```

Full Title  
Subtitle

Full Author Name  
University of North Dakota  
Date

Adjusted title page:

```
\maketitle[  
  element-order = {  
    title, author,  
    titlegraphic, date},  
  framestyle     = plain,  
]
```

**talk** default header and footer

**plain** no header and footer

**wallpaper** header and footer have  
background color but no text

Full Title

Full Author Name



Date

```
\DeclareInstance{titlepage-element}{myelement}{talk}{<key=value>}
```

% and then

```
\makeatletter
```

```
\newcommand\@myelement{...}
```

```
\makeatother
```

% or

```
\ExpandArgs{c}\newcommand{\@myelement}{...}
```

and then pass myelement to \maketitle's element-order

For example:

```
\ExpandArgs{c}\newcommand{\@titlegraphic}{%
```

```
\includegraphics[
```

```
  actualtext={University of North Dakota, Mathematics \& Statistics},
```

```
  width=5cm
```

```
]{graphic-file}%
```

```
}
```

```
\EditInstance{floatenv}{std}{horizontal-alignment = <alignment>}  
% left (default), center, or right
```

```
\EditInstance{hidden}{std}{opacity = <value>}  
% 0 <= value <= 1 for how opaque hidden things should be  
% default is 0
```

- tagging
- frame layout
- blocks
- header / footer templates
- frame title
- heading structure?

### **Temporary page!**

$\text{\LaTeX}$  was unable to guess the total number of pages correctly. As there was some unprocessed data that should have been added to the final page this extra page has been added to receive it. If you rerun the document (without altering it) this surplus page will go away, because  $\text{\LaTeX}$  now knows how many pages to expect for this document.