

JavaScript Assignment

[Back to JS page](#)

Table of Contents

- [JavaScript Assignment](#)
 - [The = Operator](#)
 - [Example 1](#)
 - [The += Operator](#)
 - [Example 2](#)
 - [The -= Operator](#)
 - [Example 3](#)
 - [The *= Operator](#)
 - [Example 4](#)
 - [The **= Operator](#)
 - [Example 5](#)
 - [The /= Operator](#)
 - [Example 6](#)
 - [The %= Operator](#)
 - [Example 7](#)
 - [String Assignment](#)
 - [Example 8](#)
 - [Document](#)
 - [Reference](#)

JavaScript Assignment Operators

Assignment operators assign values to JavaScript variables.

Given that `x = 10` and `y = 5` , the table below explains the assignment operators:

Operator	Example	Same As	Result
=	x = y	x = y	x = 5
+=	x += y	x = x + y	x = 15
-=	x -= y	x = x - y	x = 5
*=	x *= y	x = x * y	x = 50
/=	x /= y	x = x / y	x = 2
%=	x %= y	x = x % y	x = 0
**=	x **= y	x = x ** y	x = 100000

The = Operator

The **Simple Assignment Operator** assigns a simple value to a variable:

```
<!DOCTYPE html>
<html>
<body>

<h2>JavaScript Assignment</h2>
<p>From w3schools.com, Experiment by Teeratus_R</p>

<h4>The = Operator</h4>
<p id="demo"></p>

<script>
let x = 10;
document.getElementById("demo").innerHTML = "x = " + x;
</script>

</body>
</html>
```

Example 1

Result [View Example](#)

The += Operator

The **Addition Assignment Operator** adds a value to a variable:

```
<!DOCTYPE html>
<html>
<body>

<h2>JavaScript Assignment</h2>
<p>From w3schools.com, Experiment by Teeratus_R</p>

<h4>The += Operator</h4>
<p id="demo"></p>

<script>
let x = 10;
x += 5;
document.getElementById("demo").innerHTML = "x += 5 => " + x;
</script>

</body>
</html>
```

Example 2

Result [View Example](#)

The -= Operator

The **Subtraction Assignment Operator** subtracts a value from a variable:

```
<!DOCTYPE html>
<html>
<body>

<h2>JavaScript Assignment</h2>
<p>From w3schools.com, Experiment by Teeratus_R</p>

<h4>The -= Operator</h4>
<p id="demo"></p>

<script>
let x = 10;
x -= 5;
document.getElementById("demo").innerHTML = "x -= 5 => " + x;
</script>

</body>
</html>
```

Example 3

Result [View Example](#)

The *= Operator

The **Multiplication Assignment Operator** multiplies a variable:

```
<!DOCTYPE html>
<html>
<body>

<h2>JavaScript Assignment</h2>
<p>From w3schools.com, Experiment by Teeratus_R</p>

<h4>The *= Operator</h4>
<p id="demo"></p>

<script>
let x = 10;
x *= 5;
document.getElementById("demo").innerHTML = "x *= 5 => " + x;
</script>

</body>
</html>
```

Example 4

Result [View Example](#)

The **= Operator

The **Exponentiation Assignment Operator** raises a variable to the power of the operand:

```
<!DOCTYPE html>
<html>
<body>

<h2>JavaScript Assignment</h2>
<p>From w3schools.com, Experiment by Teeratus_R</p>

<h4>The **= Operator</h4>
<p id="demo"></p>

<script>
let x = 10;
x **= 5;
document.getElementById("demo").innerHTML = "x **= 5 => " + x;
</script>

</body>
</html>
```

Example 5

Result [View Example](#)

The /= Operator

The **Division Assignment Operator** divides a variable:

```
<!DOCTYPE html>
<html>
<body>

<h2>JavaScript Assignment</h2>
<p>From w3schools.com, Experiment by Teeratus_R</p>

<h4>The /= Operator</h4>
<p id="demo"></p>

<script>
let x = 10;
x /= 5;
document.getElementById("demo").innerHTML = "x /= 5 => " + x;
</script>

</body>
</html>
```

Example 6

Result [View Example](#)

The %= Operator

The **Remainder Assignment Operator** assigns a remainder to a variable:

```
<!DOCTYPE html>
<html>
<body>

<h2>JavaScript Assignment</h2>
<p>From w3schools.com, Experiment by Teeratus_R</p>

<h4>The %= Operator</h4>
<p id="demo"></p>

<script>
let x = 10;
x %= 5;
document.getElementById("demo").innerHTML = "x %= 5 => " + x;
</script>

</body>
</html>
```

Example 7

Result [View Example](#)

String Assignment

Two assignment operators can assign values to strings:

The **Simple Assignment Operator** (`=`) assigns a simple value to a string.

The **Addition Assignment Operator** (`+=`) adds (concatenates) strings:


```
<!DOCTYPE html>
<html>
<body>

<h2>JavaScript Assignment</h2>
<p>From w3schools.com, Experiment by Teeratus_R</p>

<h4>String Assignment</h4>
<p id="demo1"></p>
<p id="demo2"></p>

<script>
let text1 = "Hello";
let text2 = "World";
text2 += "!";
document.getElementById("demo1").innerHTML = "text1 = " + text1;
document.getElementById("demo2").innerHTML = "text2 += \"!\\" => " + text2;
</script>

</body>
</html>
```

Example 8

Result [View Example](#)

Document

Document in project

You can [Download PDF](#) file.

Reference

- [W3Schools JavaScript Assignment](#)