

JavaScript Function Parameters

[Back to JS page](#)

Table of Contents

- [JavaScript Function Parameters](#)
 - [Parameters \(Function Input\)](#)
 - [Example 1](#)
 - [Functions with One Parameter](#)
 - [Example 2](#)
 - [Functions with Multiple Parameters](#)
 - [Example 3](#)
 - [Incorrect Parameters](#)
 - [Example 4](#)
 - [Default Parameter Values](#)
 - [Example 5](#)
 - [Document](#)
 - [Reference](#)

Parameters (Function Input)

Function **parameters** are the names listed in the function definition.

Function **arguments** are the real values passed to (and received by) the function.

```
<!DOCTYPE html>
<html>
<body>

<h2>JavaScript Function Parameters</h2>
<p>From w3schools.com, Experiment by Teeratus_R</p>

<h4>Parameters (Function Input)</h4>
<p id="demo"></p>

<script>
function myFunction(firstName, lastName) {
  return "Hello " + firstName + " " + lastName;
}
document.getElementById("demo").innerHTML = myFunction("John", "Doe");
</script>

</body>
</html>
```

Example 1

Result [View Example](#)

Functions with One Parameter

A function can have a single parameter:

```
<!DOCTYPE html>
<html>
<body>

<h2>JavaScript Function Parameters</h2>
<p>From w3schools.com, Experiment by Teeratus_R</p>

<h4>Functions with One Parameter</h4>
<p id="demo"></p>

<script>
function square(x) {
    return x * x;
}
document.getElementById("demo").innerHTML = "Square of 5: " + square(5);
</script>

</body>
</html>
```

Example 2

Result [View Example](#)

Functions with Multiple Parameters

A function can have multiple parameters separated by commas:

```
<!DOCTYPE html>
<html>
<body>

<h2>JavaScript Function Parameters</h2>
<p>From w3schools.com, Experiment by Teeratus_R</p>

<h4>Functions with Multiple Parameters</h4>
<p id="demo"></p>

<script>
function sum(a, b, c) {
    return a + b + c;
}
document.getElementById("demo").innerHTML = "Sum of 5, 10, 15 = " + sum(5, 10, 15);
</script>

</body>
</html>
```

Example 3

Result [View Example](#)

Incorrect Parameters

If a function is called with missing arguments (fewer than declared), the missing values are set to `undefined` :

```
<!DOCTYPE html>
<html>
<body>

<h2>JavaScript Function Parameters</h2>
<p>From w3schools.com, Experiment by Teeratus_R</p>

<h4>Incorrect Parameters</h4>
<p id="demo"></p>

<script>
function multiply(a, b) {
    return a * b;
}
// Only one argument passed, b will be undefined
document.getElementById("demo").innerHTML = "multiply(5) = " + multiply(5) + " (NaN because b is
</script>

</body>
</html>
```

Example 4

Result [View Example](#)

Default Parameter Values

ES6 allows function parameters to have default values:

```
<!DOCTYPE html>
<html>
<body>

<h2>JavaScript Function Parameters</h2>
<p>From w3schools.com, Experiment by Teeratus_R</p>

<h4>Default Parameter Values</h4>
<p id="demo1"></p>
<p id="demo2"></p>

<script>
function myFunction(x, y = 10) {
  return x + y;
}
document.getElementById("demo1").innerHTML = "myFunction(5) = " + myFunction(5);
document.getElementById("demo2").innerHTML = "myFunction(5, 3) = " + myFunction(5, 3);
</script>

</body>
</html>
```

Example 5

Result [View Example](#)

Document

Document in project

You can [Download PDF](#) file.

Reference

- [W3Schools JavaScript Function Parameters](#)