

JavaScript Date Reference

[Back to JS page](#)

Table of Contents

- [JavaScript Date Reference](#)
 - [Date Get Methods](#)
 - [Example 1](#)
 - [Date Set Methods](#)
 - [Example 2](#)
 - [Date Display Methods](#)
 - [Example 3](#)
 - [Document](#)
 - [Reference](#)

Date Get Methods

Reference table for all Date get methods:

Method	Description
<code>getFullYear()</code>	Year (4 digits)
<code>getMonth()</code>	Month (0-11)
<code>getDate()</code>	Day of month (1-31)
<code>getDay()</code>	Day of week (0=Sunday)
<code>getHours()</code>	Hours (0-23)
<code>getMinutes()</code>	Minutes (0-59)
<code>getSeconds()</code>	Seconds (0-59)
<code>getMilliseconds()</code>	Milliseconds (0-999)
<code>getTime()</code>	Milliseconds since Jan 1, 1970
<code>Date.now()</code>	Same as <code>getTime()</code> but static
<code>getTimezoneOffset()</code>	Minutes between local and UTC

```
<!DOCTYPE html>
<html>
<body>

<h2>JavaScript Date Reference</h2>
<p>From w3schools.com, Experiment by Teeratus_R</p>

<h4>Date Get Methods</h4>
<p id="demo"></p>

<script>
const d = new Date(2024, 5, 15, 12, 30, 45, 123);

document.getElementById("demo").innerHTML =
  "getFullYear(): " + d.getFullYear() + "<br>" +
  "getMonth(): " + d.getMonth() + "<br>" +
  "getDate(): " + d.getDate() + "<br>" +
  "getDay(): " + d.getDay() + "<br>" +
  "getHours(): " + d.getHours() + "<br>" +
  "getMinutes(): " + d.getMinutes() + "<br>" +
  "getSeconds(): " + d.getSeconds() + "<br>" +
  "getMilliseconds(): " + d.getMilliseconds() + "<br>" +
  "getTime(): " + d.getTime();
</script>

</body>
</html>
```

Example 1

Result [View Example](#)

Date Set Methods

Reference table for all Date set methods:

Method	Description
<code>setFullYear()</code>	Set year
<code>setMonth()</code>	Set month (0-11)
<code>setDate()</code>	Set day of month (1-31)
<code>setHours()</code>	Set hours (0-23)
<code>setMinutes()</code>	Set minutes (0-59)
<code>setSeconds()</code>	Set seconds (0-59)
<code>setMilliseconds()</code>	Set milliseconds (0-999)
<code>setTime()</code>	Set time (milliseconds)

```

<!DOCTYPE html>
<html>
<body>

<h2>JavaScript Date Reference</h2>
<p>From w3schools.com, Experiment by Teeratus_R</p>

<h4>Date Set Methods</h4>
<p id="demo"></p>

<script>
const d = new Date();
d.setFullYear(2024);
d.setMonth(5);
d.setDate(15);
d.setHours(12);
d.setMinutes(30);
d.setSeconds(45);

document.getElementById("demo").innerHTML = "After using set methods:<br>" + d;
</script>

</body>
</html>

```

Example 2

Result [View Example](#)

Date Display Methods

Reference table for display methods:

Method	Description
<code>toString()</code>	Standard string format
<code>toDateString()</code>	Date only, no time
<code>toISOString()</code>	ISO 8601 format
<code>toUTCString()</code>	UTC string format
<code>toLocaleDateString()</code>	Local date format
<code>toLocaleTimeString()</code>	Local time format

```
<!DOCTYPE html>
<html>
<body>

<h2>JavaScript Date Reference</h2>
<p>From w3schools.com, Experiment by Teeratus_R</p>

<h4>Date Display Methods</h4>
<p id="demo"></p>

<script>
const d = new Date(2024, 5, 15, 12, 30);

document.getElementById("demo").innerHTML =
  "toString(): " + d.toString() + "<br>" +
  "toDateString(): " + d.toDateString() + "<br>" +
  "toISOString(): " + d.toISOString() + "<br>" +
  "toUTCString(): " + d.toUTCString() + "<br>" +
  "toLocaleDateString(): " + d.toLocaleDateString() + "<br>" +
  "toLocaleTimeString(): " + d.toLocaleTimeString();
</script>

</body>
</html>
```

Example 3

Result [View Example](#)

Document

Document in project

You can [Download PDF](#) file.

Reference

- [W3Schools JavaScript Date Reference](#)