

JavaScript Array Reference

[Back to JS page](#)

Table of Contents

- [JavaScript Array Reference](#)
 - [Array Properties](#)
 - [Example 1](#)
 - [Basic Methods](#)
 - [Example 2](#)
 - [Search Methods](#)
 - [Example 3](#)
 - [Iteration Methods](#)
 - [Example 4](#)
 - [Add/Remove Methods](#)
 - [Example 5](#)
 - [Document](#)
 - [Reference](#)

Array Properties

The complete `Array` object reference:

Property	Description
<code>length</code>	Number of elements in the array
<code>constructor</code>	The array constructor function

```
<!DOCTYPE html>
<html>
<body>

<h2>JavaScript Array Reference</h2>
<p>From w3schools.com, Experiment by Teeratus_R</p>

<h4>Array Properties</h4>
<p id="demo"></p>

<script>
const fruits = ["Banana", "Orange", "Apple", "Mango"];

document.getElementById("demo").innerHTML =
  "Array: " + fruits + "<br>" +
  "length: " + fruits.length + "<br>" +
  "constructor: " + fruits.constructor;
</script>

</body>
</html>
```

Example 1

Result [View Example](#)

Basic Methods

Basic array methods for converting and joining:

Method	Description
<code>toString()</code>	Convert array to comma-separated string
<code>join(sep)</code>	Join elements with a separator
<code>at(index)</code>	Get element at index (supports negative)
<code>fill(value)</code>	Fill all elements with a value

```
<!DOCTYPE html>
<html>
<body>

<h2>JavaScript Array Reference</h2>
<p>From w3schools.com, Experiment by Teeratus_R</p>

<h4>Basic Methods</h4>
<p id="demo"></p>

<script>
const fruits = ["Banana", "Orange", "Apple"];

// Create a copy for fill demonstration
const filled = new Array(3);
filled.fill("Kiwi");

document.getElementById("demo").innerHTML =
  "toString(): " + fruits.toString() + "<br>" +
  "join(' - '): " + fruits.join(" - ") + "<br>" +
  "at(-1): " + fruits.at(-1) + "<br>" +
  "fill('Kiwi'): " + filled;
</script>

</body>
</html>
```

Example 2

Result [View Example](#)

Search Methods

Array search methods reference:

Method	Description
<code>indexOf(item)</code>	First index of item (-1 if not found)
<code>lastIndexOf(item)</code>	Last index of item
<code>includes(item)</code>	True if item exists
<code>find(fn)</code>	First value passing test
<code>findIndex(fn)</code>	First index passing test

```
<!DOCTYPE html>
<html>
<body>

<h2>JavaScript Array Reference</h2>
<p>From w3schools.com, Experiment by Teeratus_R</p>

<h4>Search Methods</h4>
<p id="demo"></p>

<script>
const numbers = [10, 20, 30, 20, 40];

document.getElementById("demo").innerHTML =
  "Array: " + numbers + "<br><br>" +
  "indexOf(20): " + numbers.indexOf(20) + "<br>" +
  "lastIndexOf(20): " + numbers.lastIndexOf(20) + "<br>" +
  "includes(30): " + numbers.includes(30) + "<br>" +
  "find(v > 25): " + numbers.find(v => v > 25) + "<br>" +
  "findIndex(v > 25): " + numbers.findIndex(v => v > 25);
</script>

</body>
</html>
```

Example 3

Result [View Example](#)

Iteration Methods

Array iteration methods reference:

Method	Description
<code>forEach(fn)</code>	Call function for each element
<code>map(fn)</code>	Create new array from results
<code>filter(fn)</code>	Keep elements passing test
<code>reduce(fn)</code>	Reduce to a single value
<code>every(fn)</code>	True if all pass
<code>some(fn)</code>	True if any pass

```

<!DOCTYPE html>
<html>
<body>

<h2>JavaScript Array Reference</h2>
<p>From w3schools.com, Experiment by Teeratus_R</p>

<h4>Iteration Methods</h4>
<p id="demo"></p>

<script>
const numbers = [1, 2, 3, 4, 5];

let text = "Array: " + numbers + "<br><br>";

// forEach
let sum = 0;
numbers.forEach(v => sum += v);
text += "forEach (sum): " + sum + "<br>";

// map
text += "map(v * 10): " + numbers.map(v => v * 10) + "<br>";

// filter
text += "filter(v % 2 == 0): " + numbers.filter(v => v % 2 === 0) + "<br>";

// reduce
text += "reduce(sum): " + numbers.reduce((acc, v) => acc + v, 0) + "<br>";

// every/some
text += "every(v > 0): " + numbers.every(v => v > 0) + "<br>";
text += "some(v > 4): " + numbers.some(v => v > 4);

document.getElementById("demo").innerHTML = text;
</script>

</body>
</html>

```

Example 4

Result [View Example](#)

Add/Remove Methods

Methods for adding and removing elements:

Method	Description
<code>push(item)</code>	Add to the end
<code>pop()</code>	Remove from the end
<code>shift()</code>	Remove from the beginning
<code>unshift(item)</code>	Add to the beginning
<code>splice(start, count)</code>	Add/remove in the middle
<code>concat(arr)</code>	Merge arrays

```
<!DOCTYPE html>
<html>
<body>

<h2>JavaScript Array Reference</h2>
<p>From w3schools.com, Experiment by Teeratus_R</p>

<h4>Add/Remove Methods</h4>
<p id="demo"></p>

<script>
const arr = ["A", "B"];

let text = "Start: " + arr + "<br><br>";

arr.push("C");
text += "push('C'): " + arr + "<br>";

arr.unshift("Z");
text += "unshift('Z'): " + arr + "<br>";

arr.pop();
text += "pop(): " + arr + "<br>";

arr.shift();
text += "shift(): " + arr + "<br>";

arr.splice(1, 0, "X");
text += "splice(1,0,'X'): " + arr + "<br>";

text += "concat(['Y']): " + arr.concat(['Y']);

document.getElementById("demo").innerHTML = text;
</script>

</body>
</html>
```

Example 5

Result [View Example](#)

Document

Document in project

You can [Download PDF](#) file.

Reference

- [W3Schools JavaScript Array Reference](#)