

JavaScript Set Methods

[Back to JS page](#)

Table of Contents

- [JavaScript Set Methods](#)
 - [The add\(\) Method](#)
 - [Example 1](#)
 - [The has\(\) Method](#)
 - [Example 2](#)
 - [The values\(\) and keys\(\) Methods](#)
 - [Example 3](#)
 - [The entries\(\) Method](#)
 - [Example 4](#)
 - [Document](#)
 - [Reference](#)

Set Methods & Properties

Set has the following methods and properties:

Method/Property	Description
<code>new Set()</code>	Create a new Set
<code>add(value)</code>	Add a new element
<code>delete(value)</code>	Delete an element
<code>has(value)</code>	Check if element exists
<code>clear()</code>	Remove all elements
<code>forEach(fn)</code>	Call function for each element
<code>values()</code>	Returns iterator of values
<code>keys()</code>	Same as values() for Set
<code>entries()</code>	Returns [value, value] pairs
<code>size</code>	Number of elements

The add() Method

`add()` adds a new element to the Set. Chain multiple `add()` calls for cleaner code:

```
<!DOCTYPE html>
<html>
<body>

<h2>JavaScript Set Methods</h2>
<p>From w3schools.com, Experiment by Teeratus_R</p>

<h4>The add() Method</h4>
<p id="demo"></p>

<script>
const letters = new Set();

// Chained add() calls
letters.add("a").add("b").add("c").add("d");

document.getElementById("demo").innerHTML =
  "Set: " + [...letters] + "<br>" +
  "size: " + letters.size;
</script>

</body>
</html>
```

Example 1

Result [View Example](#)

The has() Method

`has()` returns true if the Set contains a specific value:

```
<!DOCTYPE html>
<html>
<body>

<h2>JavaScript Set Methods</h2>
<p>From w3schools.com, Experiment by Teeratus_R</p>

<h4>The has() Method</h4>
<p id="demo"></p>

<script>
const letters = new Set(["a", "b", "c"]);

let text = "Set: " + [...letters] + "<br><br>";
text += "has('a'): " + letters.has("a") + "<br>";
text += "has('x'): " + letters.has("x") + "<br><br>";

// delete() removes an element
letters.delete("b");
text += "After delete('b'): " + [...letters] + "<br>";
text += "has('b') after delete: " + letters.has("b");

document.getElementById("demo").innerHTML = text;
</script>

</body>
</html>
```

Example 2

Result [View Example](#)

The values() and keys() Methods

For a Set, `values()` and `keys()` are the same - both return an iterator of all values:

```
<!DOCTYPE html>
<html>
<body>

<h2>JavaScript Set Methods</h2>
<p>From w3schools.com, Experiment by Teeratus_R</p>

<h4>The values() and keys() Methods</h4>
<p id="demo"></p>

<script>
const letters = new Set(["a", "b", "c"]);

// values() returns iterator
let text = "values(): ";
for (let v of letters.values()) {
  text += v + " ";
}
text += "<br>";

// keys() returns same as values() for Set
text += "keys(): ";
for (let k of letters.keys()) {
  text += k + " ";
}

document.getElementById("demo").innerHTML = text;
</script>

</body>
</html>
```

Example 3

Result [View Example](#)

The entries() Method

`entries()` returns an iterator with [value, value] pairs:

```
<!DOCTYPE html>
<html>
<body>

<h2>JavaScript Set Methods</h2>
<p>From w3schools.com, Experiment by Teeratus_R</p>

<h4>The entries() Method</h4>
<p id="demo"></p>

<script>
const letters = new Set(["a", "b", "c"]);

let text = "entries():<br>";
for (let entry of letters.entries()) {
  text += "[" + entry[0] + ", " + entry[1] + "]<br>";
}

document.getElementById("demo").innerHTML = text;
</script>

</body>
</html>
```

Example 4

Result [View Example](#)

Document

Document in project

You can [Download PDF](#) file.

Reference

- [W3Schools JavaScript Set Methods](#)