

JavaScript Set Reference

[Back to JS page](#)

Table of Contents

- [JavaScript Set Reference](#)
 - [Set Properties](#)
 - [Example 1](#)
 - [Set Add/Delete Methods](#)
 - [Example 2](#)
 - [Set Iteration Methods](#)
 - [Example 3](#)
 - [Set Logic Methods](#)
 - [Example 4](#)
 - [Document](#)
 - [Reference](#)

Set Properties

The complete `Set` object reference:

Property	Description
<code>size</code>	Number of elements in the Set
<code>constructor</code>	The Set constructor function

```
<!DOCTYPE html>
<html>
<body>

<h2>JavaScript Set Reference</h2>
<p>From w3schools.com, Experiment by Teeratus_R</p>

<h4>Set Properties</h4>
<p id="demo"></p>

<script>
const letters = new Set(["a", "b", "c", "d"]);

document.getElementById("demo").innerHTML =
  "Set: " + [...letters] + "<br>" +
  "size: " + letters.size + "<br>" +
  "constructor: " + letters.constructor;
</script>

</body>
</html>
```

Example 1

Result [View Example](#)

Set Add/Delete Methods

Methods for adding and removing elements:

Method	Description
<code>add(value)</code>	Add a new element
<code>delete(value)</code>	Remove an element
<code>has(value)</code>	Check if element exists
<code>clear()</code>	Remove all elements

```
<!DOCTYPE html>
<html>
<body>

<h2>JavaScript Set Reference</h2>
<p>From w3schools.com, Experiment by Teeratus_R</p>

<h4>Set Add/Delete Methods</h4>
<p id="demo"></p>

<script>
const letters = new Set(["a", "b"]);

let text = "Start: " + [...letters] + "<br><br>";

letters.add("c");
text += "add('c'): " + [...letters] + "<br>";
text += "has('c'): " + letters.has("c") + "<br><br>";

letters.delete("a");
text += "delete('a'): " + [...letters] + "<br><br>";

letters.clear();
text += "clear(): " + [...letters] + " (empty)<br>";
text += "size: " + letters.size;

document.getElementById("demo").innerHTML = text;
</script>

</body>
</html>
```

Example 2

Result [View Example](#)

Set Iteration Methods

Methods for iterating over Set elements:

Method	Description
<code>forEach(fn)</code>	Call function for each element
<code>values()</code>	Iterator of all values
<code>keys()</code>	Same as <code>values()</code> for Set
<code>entries()</code>	Iterator of [value, value] pairs

```

<!DOCTYPE html>
<html>
<body>

<h2>JavaScript Set Reference</h2>
<p>From w3schools.com, Experiment by Teeratus_R</p>

<h4>Set Iteration Methods</h4>
<p id="demo"></p>

<script>
const letters = new Set(["a", "b", "c"]);

let text = "<b>forEach():</b> ";
letters.forEach(v => text += v + " ");
text += "<br>";

text += "<b>values():</b> ";
for (let v of letters.values()) text += v + " ";
text += "<br>";

text += "<b>keys():</b> ";
for (let k of letters.keys()) text += k + " ";
text += "<br>";

text += "<b>entries():</b> ";
for (let e of letters.entries()) text += "[" + e[0] + "," + e[1] + " ";

document.getElementById("demo").innerHTML = text;
</script>

</body>
</html>

```

Example 3

Result [View Example](#)

Set Logic Methods

Set logic methods (newer Set methods):

Method	Description
<code>union(set)</code>	All elements from both Sets
<code>intersection(set)</code>	Elements in both Sets
<code>difference(set)</code>	Elements in this but not other
<code>symmetricDifference(set)</code>	Elements in either, not both
<code>isSubsetOf(set)</code>	Every element in this also in other
<code>isSupersetOf(set)</code>	Every element in other also in this
<code>isDisjointFrom(set)</code>	No common elements

```

<!DOCTYPE html>
<html>
<body>

<h2>JavaScript Set Reference</h2>
<p>From w3schools.com, Experiment by Teeratus_R</p>

<h4>Set Logic Methods</h4>
<p id="demo"></p>

<script>
const setA = new Set(["a", "b", "c"]);
const setB = new Set(["c", "d"]);

let text = "Set A: " + [...setA] + "<br>";
text += "Set B: " + [...setB] + "<br><br>";

if (setA.union) {
  text += "A.union(B): " + [...setA.union(setB)] + "<br>";
  text += "A.intersection(B): " + [...setA.intersection(setB)] + "<br>";
  text += "A.difference(B): " + [...setA.difference(setB)] + "<br>";
  text += "A.symmetricDifference(B): " + [...setA.symmetricDifference(setB)] + "<br>";
  text += "A.isSubsetOf(B): " + setA.isSubsetOf(setB) + "<br>";
  text += "A.isDisjointFrom(new Set(['x'])): " + setA.isDisjointFrom(new Set(['x']));
} else {
  text += "Logic methods are not supported in this browser yet.";
}

document.getElementById("demo").innerHTML = text;
</script>

</body>
</html>

```

Example 4

Result [View Example](#)

Document

Document in project

You can [Download PDF](#) file.

Reference

- [W3Schools JavaScript Set Reference](#)