

JavaScript undefined

[Back to JS page](#)

Table of Contents

- [JavaScript undefined](#)
 - [Undefined Variables](#)
 - [Example 1](#)
 - [The Type of undefined](#)
 - [Example 2](#)
 - [Empty Values](#)
 - [Example 3](#)
 - [Objects and undefined](#)
 - [Example 4](#)
 - [Functions and undefined](#)
 - [Example 5](#)
 - [You Can Empty an Object](#)
 - [Example 6](#)
 - [Document](#)
 - [Reference](#)

Undefined Variables

In JavaScript, a variable without a value has the value `undefined`. The type is also `undefined`.

A variable declared without a value will automatically have the value `undefined`.

```
<!DOCTYPE html>
<html>
<body>

<h2>JavaScript undefined</h2>
<p>From w3schools.com, Experiment by Teeratus_R</p>

<h4>Undefined Variables</h4>
<p id="demo"></p>

<script>
let car;

// car is declared but has no value
document.getElementById("demo").innerHTML = car;
</script>

</body>
</html>
```

Example 1

Result [View Example](#)

The Type of undefined

You can use `typeof` to check if a variable is `undefined` .

```
<!DOCTYPE html>
<html>
<body>

<h2>JavaScript undefined</h2>
<p>From w3schools.com, Experiment by Teeratus_R</p>

<h4>The Type of undefined</h4>
<p id="demo"></p>

<script>
let car;

// typeof returns "undefined"
document.getElementById("demo").innerHTML = typeof car;
</script>

</body>
</html>
```

Example 2

Result [View Example](#)

Empty Values

An empty string has a value and a type. It is **not** the same as `undefined` .

```
<!DOCTYPE html>
<html>
<body>

<h2>JavaScript undefined</h2>
<p>From w3schools.com, Experiment by Teeratus_R</p>

<h4>Empty Values</h4>
<p id="demo"></p>

<script>
let text = "";

// Empty string has a value and a type
document.getElementById("demo").innerHTML =
  text + "<br>" + typeof text;
</script>

</body>
</html>
```

Example 3

Result [View Example](#)

Objects and undefined

Accessing a non-existing object property returns `undefined` .

```
<!DOCTYPE html>
<html>
<body>

<h2>JavaScript undefined</h2>
<p>From w3schools.com, Experiment by Teeratus_R</p>

<h4>Objects and undefined</h4>
<p id="demo"></p>

<script>
const person = {firstName: "John", lastName: "Doe"};

// person.age does not exist → undefined
document.getElementById("demo").innerHTML = person.age;
</script>

</body>
</html>
```

Example 4

Result [View Example](#)

Functions and undefined

A function without a return value returns `undefined` .

```
<!DOCTYPE html>
<html>
<body>

<h2>JavaScript undefined</h2>
<p>From w3schools.com, Experiment by Teeratus_R</p>

<h4>Functions and undefined</h4>
<p id="demo"></p>

<script>
function myFunction() {
    let x = 5;
}

// No return statement → undefined
document.getElementById("demo").innerHTML = myFunction();
</script>

</body>
</html>
```

Example 5

Result [View Example](#)

You Can Empty an Object

Objects can be emptied by setting the value to `undefined`. Objects can also be emptied by setting the value to `null`.

Note: `undefined` is a JavaScript value. It means that a variable has been declared, but no value has been assigned.

```
<!DOCTYPE html>
<html>
<body>

<h2>JavaScript undefined</h2>
<p>From w3schools.com, Experiment by Teeratus_R</p>

<h4>You Can Empty an Object</h4>
<p id="demo"></p>

<script>
let person = {firstName: "John", lastName: "Doe"};

let text = "Before: " + person.firstName + " " + person.lastName + "<br>";

// Empty the object by setting it to undefined
person = undefined;

text += "After (undefined): " + person;

document.getElementById("demo").innerHTML = text;
</script>

</body>
</html>
```

Example 6

Result [View Example](#)

Document

Document in project

You can [Download PDF](#) file.

Reference

- [W3Schools JavaScript undefined](#)