

JavaScript Error Reference

[Back to JS page](#)

Table of Contents

- [JavaScript Error Reference](#)
 - [The Error Object](#)
 - [Example 1](#)
 - [Error Object Properties & Methods](#)
 - [Example 2](#)
 - [EvalError](#)
 - [Example 3](#)
 - [RangeError](#)
 - [Example 4](#)
 - [ReferenceError](#)
 - [Example 5](#)
 - [TypeError](#)
 - [Example 6](#)
 - [Document](#)
 - [Reference](#)

The Error Object

The **Error Object** provides error information when an error occurs. JavaScript has a built-in error object that provides error information when an error occurs. The error object provides two useful properties: `name` and `message` .

You can also create a new Error object with the `new Error()` constructor.

```
<!DOCTYPE html>
<html>
<body>

<h2>JavaScript Error Reference</h2>
<p>From w3schools.com, Experiment by Teeratus_R</p>

<h4>The Error Object</h4>
<p id="demo"></p>

<script>
// Create a new Error object
const err = new Error("Something went wrong!");

document.getElementById("demo").innerHTML =
  "Error Name: " + err.name + "<br>" +
  "Error Message: " + err.message;
</script>

</body>
</html>
```

Example 1

Result [View Example](#)

Error Object Properties & Methods

The Error object has the following important **properties**:

- **name:** Returns or sets the error name
- **message:** Returns or sets an error message (a string)

```
<!DOCTYPE html>
<html>
<body>

<h2>JavaScript Error Reference</h2>
<p>From w3schools.com, Experiment by Teeratus_R</p>

<h4>Error Object Properties & Methods</h4>
<p id="demo"></p>

<script>
let text = "";

try {
  adddler("Welcome guest!");
}
catch(err) {
  text += "Error Name: " + err.name + "<br>";
  text += "Error Message: " + err.message + "<br><br>";
  text += "typeof err: " + typeof err;
}

document.getElementById("demo").innerHTML = text;
</script>

</body>
</html>
```

Example 2

Result [View Example](#)

EvalError

An `EvalError` indicates an error regarding the global `eval()` function. These errors are no longer thrown by JavaScript, but the `EvalError` object remains for compatibility.

```
<!DOCTYPE html>
<html>
<body>

<h2>JavaScript Error Reference</h2>
<p>From w3schools.com, Experiment by Teeratus_R</p>

<h4>EvalError</h4>
<p id="demo"></p>

<script>
let text = "";

try {
  throw new EvalError("Hello", "someFile.js", 10);
}
catch(err) {
  text += "Error Name: " + err.name + "<br>";
  text += "Error Message: " + err.message;
}

document.getElementById("demo").innerHTML = text;
</script>

</body>
</html>
```

Example 3

Result [View Example](#)

RangeError

A `RangeError` is thrown when a value is not in the set or range of allowed values.

```
<!DOCTYPE html>
<html>
<body>

<h2>JavaScript Error Reference</h2>
<p>From w3schools.com, Experiment by Teeratus_R</p>

<h4>RangeError</h4>
<p id="demo"></p>

<script>
let text = "";
let num = 1;

try {
  num.toPrecision(500);  // A number cannot have 500 significant digits
}
catch(err) {
  text += "Error Name: " + err.name + "<br>";
  text += "Error Message: " + err.message;
}

document.getElementById("demo").innerHTML = text;
</script>

</body>
</html>
```

Example 4

Result [View Example](#)

ReferenceError

A `ReferenceError` is thrown when a variable that doesn't exist (hasn't been declared) is referenced.

```
<!DOCTYPE html>
<html>
<body>

<h2>JavaScript Error Reference</h2>
<p>From w3schools.com, Experiment by Teeratus_R</p>

<h4>ReferenceError</h4>
<p id="demo"></p>

<script>
let text = "";

try {
  x = y + 1;    // y is not defined
}
catch(err) {
  text += "Error Name: " + err.name + "<br>";
  text += "Error Message: " + err.message;
}

document.getElementById("demo").innerHTML = text;
</script>

</body>
</html>
```

Example 5

Result [View Example](#)

TypeError

A `TypeError` is thrown when an operation cannot be performed, typically when a value is not of the expected type.

```
<!DOCTYPE html>
<html>
<body>

<h2>JavaScript Error Reference</h2>
<p>From w3schools.com, Experiment by Teeratus_R</p>

<h4>TypeError</h4>
<p id="demo"></p>

<script>
let text = "";

try {
  let num = 1;
  num.toUpperCase();    // Numbers don't have toUpperCase()
}
catch(err) {
  text += "Error Name: " + err.name + "<br>";
  text += "Error Message: " + err.message;
}

document.getElementById("demo").innerHTML = text;
</script>

</body>
</html>
```

Example 6

Result [View Example](#)

Document

Document in project

You can [Download PDF](#) file.

Reference

- [W3Schools JavaScript Error Reference](#)