

# JavaScript HTML DOM Content

---

[Back to JS page](#)

## Table of Contents

- [JavaScript HTML DOM Content](#)
  - [Changing HTML Content](#)
    - [Example 1](#)
  - [The innerHTML Property](#)
    - [Example 2](#)
  - [Changing an Attribute](#)
    - [Example 3](#)
  - [Dynamic HTML content](#)
    - [Example 4](#)
  - [document.write\(\)](#)
    - [Example 5](#)
  - [Document](#)
  - [Reference](#)

## Changing HTML Content

---

The easiest way to change the content of an HTML element is by using the `innerHTML` property.

To change the content of an HTML element, use this syntax:

```
document.getElementById(id).innerHTML = new text
```

```
<!DOCTYPE html>
<html>
<body>

<h2>JavaScript HTML DOM Content</h2>
<p>From w3schools.com, Experiment by Teeratus_R</p>

<h4>Changing HTML Content</h4>
<p id="demo">Original text</p>
<button type="button" onclick="document.getElementById('demo').innerHTML = 'Hello JavaScript!'">

</body>
</html>
```

## Example 1

---

Result [View Example](#)

## The innerHTML Property

---

The `innerHTML` property can be used to get or change any HTML element, including `<html>` and `<body>` :

```
<!DOCTYPE html>
<html>
<body>

<h2>JavaScript HTML DOM Content</h2>
<p>From w3schools.com, Experiment by Teeratus_R</p>

<h4>The innerHTML Property</h4>
<p id="demo1">First paragraph</p>
<p id="demo2">Second paragraph</p>

<script>
document.getElementById("demo1").innerHTML = "Content changed!";
document.getElementById("demo2").innerHTML = "<b>Bold text</b> with HTML tags";
</script>

</body>
</html>
```

## Example 2

---

Result [View Example](#)

## Changing an Attribute

---

To change an HTML attribute, use this syntax:

```
document.getElementById(id).attribute = new value
```

```
<!DOCTYPE html>
<html>
<body>

<h2>JavaScript HTML DOM Content</h2>
<p>From w3schools.com, Experiment by Teeratus_R</p>

<h4>Changing an Attribute</h4>

<p>
<button type="button" onclick="document.getElementById('image').src='https://www.w3schools.com/j
<button type="button" onclick="document.getElementById('image').src='https://www.w3schools.com/j
</p>

</body>
</html>
```

## Example 3

---

Result [View Example](#)

## Dynamic HTML content

---

JavaScript can create dynamic HTML content:

```
<!DOCTYPE html>
<html>
<body>

<h2>JavaScript HTML DOM Content</h2>
<p>From w3schools.com, Experiment by Teeratus_R</p>

<h4>Dynamic HTML content</h4>
<p id="demo"></p>

<script>
const date = new Date();
document.getElementById("demo").innerHTML = "Today's date: " + date;
</script>

</body>
</html>
```

## Example 4

---

Result [View Example](#)

## document.write()

---

The `document.write()` method can be used to write directly to the HTML output stream:

```
<!DOCTYPE html>
<html>
<body>

<h2>JavaScript HTML DOM Content</h2>
<p>From w3schools.com, Experiment by Teeratus_R</p>

<h4>document.write()</h4>
<p>Note: document.write() clears the document if used after the document has loaded.</p>

<script>
document.write("Hello from document.write!");
</script>

</body>
</html>
```

## Example 5

---

Result [View Example](#)

## Document

---

Document in project

You can [Download PDF](#) file.

## Reference

---

- [W3Schools JavaScript HTML DOM Content](#)